Package: rtables (via r-universe)

October 31, 2026

Title Reporting Tables

Version 0.6.17.9000

Date 2026-10-01

Description Reporting tables often have structure that goes beyond simple rectangular data. The 'rtables' package provides a framework for declaring complex multi-level tabulations and then applying them to data. This framework models both tabulation and the resulting tables as hierarchical, tree-like objects which support sibling sub-tables, arbitrary splitting or grouping of data in row and column dimensions, cells containing multiple values, and the concept of contextual summary computations. A convenient pipe-able interface is provided for declaring table layouts and the corresponding computations, and then applying them to data.

License Apache License 2.0 | file LICENSE

URL https://github.com/pharmaverse/rtables, https://pharmaverse.github.io/rtables/

BugReports https://github.com/pharmaverse/rtables/issues

Depends formatters (>= 0.5.12), methods, R (>= 4.1)

Imports checkmate (>= 2.1.0), htmltools (>= 0.5.8.1), lifecycle (>= 1.0.4), stats, stringi (>= 1.8.4)

Suggests broom (>= 1.0.8), car (>= 3.1-3), dplyr (>= 1.0.5), knitr (>= 1.42), lme4 (>= 1.1-35.5), r2rtf (>= 0.3.2), rmarkdown (>= 2.28), survival (>= 3.3-1), testthat (>= 3.3.0), tibble (>= 3.2.1), tidyr (>= 1.1.3), withr (>= 2.0.0), xml2 (>= 1.3.5)

VignetteBuilder knitr, rmarkdown

Config/Needs/verdepcheck pharmaverse/formatters, mllg/checkmate, rstudio/htmltools, gagolews/stringi, tidymodels/broom, cran/car, tidyverse/dplyr, davidgohel/flextable, yihui/knitr, r-lib/lifecycle, davidgohel/officer, Merck/r2rtf, rstudio/rmarkdown, therneau/survival, r-lib/testthat, tidyverse/tibble, tidyverse/tidyr, r-lib/withr, r-lib/xml2

Config/roxygen2/version 8.1.0

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE)

Collate '00tabletrees.R' 'Viewer.R' 'argument_conventions.R' 'as_html.R' 'utils.R' 'nesting_impl.R' 'colby_constructors.R' 'compare_rtables.R' 'format_rcell.R' 'indent.R' 'make_subset_expr.R' 'custom_split_funs.R' 'default_split_funs.R' 'make_split_fun.R' 'summary.R' 'package.R' 'tree_accessors.R' 'tt_afun_utils.R' 'tt_as_df.R' 'tt_compare_tables.R' 'tt_compatibility.R' 'tt_dotabulation.R' 'tt_paginate.R' 'tt_pos_and_access.R' 'tt_showmethods.R' 'tt_sort.R' 'tt_test_afuns.R' 'tt_toString.R' 'tt_export.R' 'index_footnotes.R' 'tt_from_df.R' 'validate_table_struct.R' 'zzz_constants.R'

Config/pak/sysreqs libicu-dev

Repository https://pharmaverse.r-universe.dev

Date/Publication 2026-10-01 14:15:56 UTC

RemoteUrl https://github.com/pharmaverse/rtables

RemoteRef HEAD

RemoteSha c47782622cb475729eaf95edc0cf963feb4c2804

Contents

add_colcounts . . . 5
add_combo_facet . . . 6
add_existing_table . . . 7
add_overall_col . . . 8
add_overall_level . . . 9
additional_fun_params . . . 12
all_zero_or_na . . . 13
analyze . . . 15
analyze_colvars . . . 20
AnalyzeVarSplit . . . 23
append_topleft . . . 26
as_html . . . 27
asvec . . . 29
basic_table . . . 30
brackets . . . 32
build_table . . . 35
c.RowsVerticalSection . . . 37
cbind_rtables . . . 38
cell_values . . . 39

CellValue . . . 41
clayout . . . 42
clear_indent_mods . . . 46
colcount_visible . . . 47
collect_leaves . . . 48
coltree_structure . . . 48
compare_rtables . . . 49
compat_args . . . 51
cont_n_allcols . . . 52
content_table . . . 53
counts_wpcts . . . 53
custom_split_funs . . . 54
data.frame_export . . . 55
df_to_tt . . . 58
do_base_split . . . 59
drop_facet_levels . . . 60
ElementaryTable-class . . . 61
EmptyColInfo . . . 64
export_as_tsv . . . 64
facet_colcount . . . 65
facet_colcounts_visible<- . . . 67
find_degen_struct . . . 68
format_rcell . . . 68
get_formatted_cells . . . 70
get_full_lyt_df . . . 71
head . . . 75
horizontal_sep . . . 76
in_rows . . . 77
indent . . . 79
indent_string . . . 80
insert_row_at_path . . . 80
insert_rrow . . . 82
InstantiatedColumnInfo-class . . . 83
is_rtable . . . 84
label_at_path . . . 85
LabelRow . . . 86
length,CellValue-method . . . 88
list_wrap_x . . . 89
make_afun . . . 90
make_col_df . . . 93
make_split_fun . . . 94
make_split_result . . . 96
make_subset_expr . . . 98
manual_cols . . . 99
ManualSplit . . . 100
matrix_form,VTableTree-method . . . 102
MultiVarSplit . . . 104
names,VTableNodeInfo-method . . . 106

no_colinfo . . . 107
nrow,VTableTree-method . . . 107
obj_avar . . . 108
obj_name,VNodeInfo-method . . . 109
pag_tt_indices . . . 116
prune_table . . . 120
qtable_layout . . . 122
rbindl_rtables . . . 124
rcell . . . 126
RefFootnote . . . 128
restrict_facets . . . 129
rheader . . . 131
rm_all_colcounts . . . 132
row_footnotes . . . 133
row_paths . . . 135
row_paths_summary . . . 136
rrow . . . 137
rrowl . . . 138
rtable . . . 139
sanitize_table_struct . . . 142
section_div . . . 143
sf_args . . . 147
simple_analysis . . . 148
sort_at_path . . . 149
spl_context . . . 152
spl_context_to_disp_path . . . 153
spl_variable . . . 154
split_cols_by . . . 155
split_cols_by_cuts . . . 158
split_cols_by_multivar . . . 164
split_funcs . . . 166
split_rows_by . . . 170
split_rows_by_multivar . . . 174
SplitValue . . . 177
splv_extra . . . 178
subset_cols . . . 179
summarize_row_groups . . . 182
table_shell . . . 184
table_structure . . . 186
top_left . . . 187
toString,VTableTree-method . . . 188
tree_children . . . 190
trim_levels_in_facets . . . 190
trim_levels_to_map . . . 191
trim_rows . . . 192
tt_at_path . . . 193
tt_row_path_exists . . . 194
update_ref_indexing . . . 197

validate_table_struct 197
value_expr 198
value_formats 199
VarLevelSplit-class 200
vars_in_layout 203
VarStaticCutSplit-class 205
Viewer 208

Index **210**

`add_colcounts` *Add the column population counts to the header*

Description

Add the data derived column counts.

Usage

```
add_colcounts(lyt, format = "(N=xx)")
```

Arguments

`lyt`	(`PreDataTableLayouts`) layout object pre-data used for tabulation.
`format`	(`string`, `function`, or `list`) format associated with this split. Formats can be declared via strings (`"xx.x"`) or function. In cases such as `analyze` calls, they can be character vectors or lists of functions. See `formatters::list_valid_format_labels()` for a list of all available format strings.

Details

It is often the case that the the column counts derived from the input data to `build_table()` is not representative of the population counts. For example, if events are counted in the table and the header should display the number of subjects and not the total number of events.

Value

A `PreDataTableLayouts` object suitable for passing to further layouting functions, and to `build_table()`.

Author(s)

Gabriel Becker

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  add_colcounts() |>
  split_rows_by("RACE", split_fun = drop_split_levels) |>
  analyze("AGE", afun = function(x) list(min = min(x), max = max(x)))
lyt

tbl <- build_table(lyt, DM)
tbl
```

---

add_combo_facet *Add a combination facet in post-processing*

Description

Add a combination facet during the post-processing stage in a custom split fun.

Usage

```
add_combo_facet(name, label = name, levels, extra = list())

add_overall_facet(name, label, extra = list())
```

Arguments

name	(string) name for the resulting facet (for use in pathing, etc.).
label	(string) label for the resulting facet.
levels	(character) vector of levels to combine within the resulting facet.
extra	(list) extra arguments to be passed to analysis functions applied within the resulting facet.

Details

For add_combo_facet, the data associated with the resulting facet will be the data associated with the facets for each level in levels, row-bound together. In particular, this means that if those levels are overlapping, data that appears in both will be duplicated.

Value

A function which can be used within the post argument in make_split_fun().

See Also

make_split_fun()

Other make_custom_split: drop_facet_levels(), make_split_fun(), make_split_result(), restrict_facets(), trim_levels_in_facets()

Examples

```
mysplfun <- make_split_fun(post = list(
  add_combo_facet("A_B",
    label = "Arms A+B",
    levels = c("A: Drug X", "B: Placebo")
  ),
  add_overall_facet("ALL", label = "All Arms")
))

lyt <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM", split_fun = mysplfun) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
```

---

add_existing_table *Add an already calculated table to the layout*

Description

Add an already calculated table to the layout

Usage

```
add_existing_table(lyt, tt, indent_mod = 0)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
tt	(TableTree or related class) a TableTree object representing a populated table.
indent_mod	(numeric) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Author(s)

Gabriel Becker

Examples

```
lyt1 <- basic_table() |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = mean, format = "xx.xx")

tbl1 <- build_table(lyt1, DM)
tbl1

lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = sd, format = "xx.xx") |>
  add_existing_table(tbl1)

tbl2 <- build_table(lyt2, DM)
tbl2

table_structure(tbl2)
row_paths_summary(tbl2)
```

---

add_overall_col *Add overall column*

Description

This function will *only* add an overall column at the *top* level of splitting, NOT within existing column splits. See `add_overall_level()` for the recommended way to add overall columns more generally within existing splits.

Usage

```
add_overall_col(lyt, label)
```

Arguments

`lyt`	(`PreDataTableLayouts`) layout object pre-data used for tabulation.
`label`	(`string`) a label (not to be confused with the name) for the object/structure.

Value

A `PreDataTableLayouts` object suitable for passing to further layouting functions, and to `build_table()`.

See Also

add_overall_level()

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  add_overall_col("All Patients") |>
  analyze("AGE")
lyt

tbl <- build_table(lyt, DM)
tbl
```

---

add_overall_level *Add overall or combination levels to split groups*

Description

add_overall_level is a split function that adds a global level to the current levels in the split. Similarly, add_combo_levels uses a user-provided data.frame to define the combine the levels to be added. If you need a single overall column, after all splits, please check add_overall_col(). Consider also defining your custom split function if you need more flexibility (see custom_split_funs).

Usage

```
add_overall_level(
  valname = "Overall",
  label = valname,
  extra_args = list(),
  first = TRUE,
  trim = FALSE
)

select_all_levels

add_combo_levels(combosdf, trim = FALSE, first = FALSE, keep_levels = NULL)
```

Arguments

valname	(string) value to be assigned to the implicit all-observations split level. Defaults to "Overall".
label	(string) a label (not to be confused with the name) for the object/structure.

`extra_args` (`list`)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

`first` (`flag`)
whether the implicit level should appear first (`TRUE`) or last (`FALSE`). Defaults to `TRUE`.

`trim` (`flag`)
whether splits corresponding with 0 observations should be kept when tabulating.

`combosdf` (`data.frame` or `tbl_df`)
a data frame with columns `valname`, `label`, `levelcombo`, and `exargs`. `levelcombo` and `exargs` should be list columns. Passing the `select_all_levels` object as a value in `comblevels` column indicates that an overall/all-observations level should be created.

`keep_levels` (`character` or `NULL`)
if non-`NULL`, the levels to retain across both combination and individual levels.

Value

A splitting function (`splfun`) that adds or changes the levels of a split.

Note

Analysis or summary functions for which the order matters should never be used within the tabulation framework.

See Also

custom_split_funs and split_funcs.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM", split_fun = add_overall_level("All Patients",
    first = FALSE
  )) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("RACE",
    split_fun = add_overall_level("All Ethnicities")
  ) |>
  summarize_row_groups(label_fstr = "%s (n)") |>
```

```
  analyze("AGE")
lyt2

tbl2 <- build_table(lyt2, DM)
tbl2



library(tibble)
combodf <- tribble(
  ~valname, ~label, ~levelcombo, ~exargs,
  "A_B", "Arms A+B", c("A: Drug X", "B: Placebo"), list(),
  "A_C", "Arms A+C", c("A: Drug X", "C: Combination"), list()
)

lyt <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM", split_fun = add_combo_levels(combodf)) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

lyt1 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM",
    split_fun = add_combo_levels(combodf,
      keep_levels = c(
        "A_B",
        "A_C"
      )
    )
  ) |>
  analyze("AGE")

tbl1 <- build_table(lyt1, DM)
tbl1

smallerDM <- droplevels(subset(DM, SEX %in% c("M", "F") &
  grepl("^(A|B)", ARM)))
lyt2 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM", split_fun = add_combo_levels(combodf[1, ])) |>
  split_cols_by("SEX",
    split_fun = add_overall_level("SEX_ALL", "All Genders")
  ) |>
  analyze("AGE")

lyt3 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM", split_fun = add_combo_levels(combodf)) |>
  split_rows_by("SEX",
    split_fun = add_overall_level("SEX_ALL", "All Genders")
  ) |>
  summarize_row_groups() |>
  analyze("AGE")
```

```
tbl3 <- build_table(lyt3, smallerDM)
tbl3
```

`additional_fun_params` *Additional parameters within analysis and content functions (*`afun/cfun`*)*

Description

It is possible to add specific parameters to `afun` and `cfun`, in `analyze()` and `summarize_row_groups()`, respectively. These parameters grant access to relevant information like the row split structure (see spl_context) and the predefined baseline (`.ref_group`).

Details

We list and describe all the parameters that can be added to a custom analysis function below:

.N_col Column-wise N (column count) for the full column being tabulated within.

.N_total Overall N (all observation count, defined as sum of column counts) for the tabulation.

.N_row Row-wise N (row group count) for the group of observations being analyzed (i.e. with no column-based subsetting).

.df_row `data.frame` for observations in the row group being analyzed (i.e. with no column-based subsetting).

.var Variable being analyzed.

.ref_group `data.frame` or vector of subset corresponding to the `ref_group` column including subsetting defined by row-splitting. Only required/meaningful if a `ref_group` column has been defined.

.ref_full `data.frame` or vector of subset corresponding to the `ref_group` column without subsetting defined by row-splitting. Only required/meaningful if a `ref_group` column has been defined.

.in_ref_col Boolean indicating if calculation is done for cells within the reference column.

.spl_context `data.frame` where each row gives information about a previous 'ancestor' split state. See spl_context.

.alt_df_row `data.frame`, i.e. the `alt_counts_df` after row splitting. It can be used with `.all_col_exprs` and `.spl_context` information to retrieve current faceting, but for `alt_count_df`. It can be an empty table if all the entries are filtered out.

.alt_df `data.frame`, `.alt_df_row` but filtered by columns expression. This data present the same faceting of main data `df`. This also filters `NA`s out if related parameters are set to do so (e.g. `inclNAs` in `analyze()`). Similarly to `.alt_df_row`, it can be an empty data.frame if all the entries are filtered out.

.alt_df_full `data.frame`, the full `alt_counts_df` as passed into `build_table`. Unlike `.alt_df` and `.alt_df_row`, this parameter can be used in cases where the variables required for row splitting are not present in `alt_counts_df`.

.all_col_exprs List of expressions. Each of them represents a different column splitting.

.all_col_counts Vector of integers. Each of them represents the global count for each column. It differs if `alt_counts_df` is used (see `build_table()`).

For the `.alt_df*` family of parameters, these will be passed data subsets based on `df` if no `alt_counts_df` is specified in the `build_table` call. In `rtables` versions `<= 0.6.16` this resulted in an error.

Note

If any of these formals is specified incorrectly or not present in the tabulation machinery, it will be treated as if missing. For example, `.ref_group` will be missing if no baseline is previously defined during data splitting (via `ref_group` parameters in, e.g., `split_rows_by()`). Arguments derived from the alt_counts_df will be passed subsets of the primary data (`df`) when no `alt_counts_df` is provided to `build_table()`.

---

all_zero_or_na *Trimming and pruning criteria*

Description

Criteria functions (and constructors thereof) for trimming and pruning tables.

Usage

```
all_zero_or_na(tr)

all_zero(tr)

content_all_zeros_nas(tt, criteria = all_zero_or_na)

prune_empty_level(tt)

prune_zeros_only(tt)

low_obs_pruner(min, type = c("sum", "mean"))
```

Arguments

`tr`	(`TableRow` or related class) a `TableRow` object representing a single row within a populated table.
`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`criteria`	(`function`) function which takes a `TableRow` object and returns `TRUE` if that row should be removed. Defaults to `all_zero_or_na()`.

min	(numeric(1)) (used by low_obs_pruner only). Minimum aggregate count value. Subtables whose combined/average count are below this threshold will be pruned.
type	(string) how count values should be aggregated. Must be "sum" (the default) or "mean".

Details

all_zero_or_na returns TRUE (and thus indicates trimming/pruning) for any *non*-LabelRow TableRow which contain only any mix of NA (including NaN), 0, Inf and -Inf values.

all_zero returns TRUE for any non-LabelRow which contains only (non-missing) zero values.

content_all_zeros_nas prunes a subtable if both of the following are true:

- It has a content table with exactly one row in it.
- all_zero_or_na returns TRUE for that single content row. In practice, when the default summary/content function is used, this represents pruning any subtable which corresponds to an empty set of the input data (e.g. because a factor variable was used in split_rows_by() but not all levels were present in the data).

prune_empty_level combines all_zero_or_na behavior for TableRow objects, content_all_zeros_nas on content_table(tt) for TableTree objects, and an additional check that returns TRUE if the tt has no children.

prune_zeros_only behaves as prune_empty_level does, except that like all_zero it prunes only in the case of all non-missing zero values.

low_obs_pruner is a *constructor function* which, when called, returns a pruning criteria function which will prune on content rows by comparing sum or mean (dictated by type) of the count portions of the cell values (defined as the first value per cell regardless of how many values per cell there are) against min.

Value

A logical value indicating whether tr should be included (TRUE) or pruned (FALSE) during pruning.

See Also

prune_table(), trim_rows()

Examples

```
adsl <- ex_adsl
levels(adsl$SEX) <- c(levels(ex_adsl$SEX), "OTHER")
adsl$AGE[adsl$SEX == "UNDIFFERENTIATED"] <- 0
adsl$BMRKR1 <- 0

tbl_to_prune <- basic_table() |>
  analyze("BMRKR1") |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  summarize_row_groups() |>
```

```
  split_rows_by("STRATA1") |>
  summarize_row_groups() |>
  analyze("AGE") |>
  build_table(adsl)

tbl_to_prune |> prune_table(all_zero_or_na)

tbl_to_prune |> prune_table(all_zero)

tbl_to_prune |> prune_table(content_all_zeros_nas)

tbl_to_prune |> prune_table(prune_empty_level)

tbl_to_prune |> prune_table(prune_zeros_only)

min_prune <- low_obs_pruner(70, "sum")
tbl_to_prune |> prune_table(min_prune)
```

---

analyze *Generate rows analyzing variables across columns*

Description

Adding *analyzed variables* to our table layout defines the primary tabulation to be performed. We do this by adding calls to analyze and/or analyze_colvars() into our layout pipeline. As with adding further splitting, the tabulation will occur at the current/next level of nesting by default.

Usage

```
analyze(
  lyt,
  vars,
  afun = simple_analysis,
  var_labels = vars,
  table_names = vars,
  parent_name = NULL,
  format = NULL,
  formats_var = NULL,
  na_str = NA_character_,
  na_strs_var = NULL,
  nested = TRUE,
  at_sibling = NULL,
  inclNAs = FALSE,
  extra_args = list(),
  show_labels = c("default", "visible", "hidden"),
  indent_mod = 0L,
  section_div = NA_character_
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
vars	(character) vector of variable names.
afun	(function) analysis function. Must accept x or df as its first parameter. Can optionally take other parameters which will be populated by the tabulation framework. See Details in analyze().
var_labels	(character) vector of labels for one or more variables.
table_names	(character) names for the tables representing each atomic analysis. Defaults to var.
parent_name	(character(1)) Name to assign to the table corresponding to the *split* or *group of sibling analyses*, for split_rows_by* and analyze* when analyzing more than one variable, respectively. Ignored when analyzing a single variable.
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.
formats_var	(string or NULL) NULL (the default) or the name of the list column containing named lists of default formats to use. These will be applied with the same precedence as the format argument; i.e., they will not override formats (other than "default") set within the afun. Cannot be used simultaneously with format.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".
na_strs_var	(string or NULL) NULL (the default) or the name of the list column containing named lists of default NA strings to use. These will be applied with the same precedence as the format argument; i.e., they will not override formats (other than "default") set within the afun. Cannot be used simultaneously with format. Cannot be used if formats_var is NULL.
nested	(logical) whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.
at_sibling	(character(1) or NULL) If non-null, a preceding split or analyze to anchor this instruction to as a direct sibling. Cannot select an instruction that is downstream of a point where a previously used anchor (See Nesting Anchor Resolution for details).

inclNAs (logical)
whether NA observations in the var variable(s) should be included when performing the analysis. Defaults to FALSE.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

show_labels (string)
whether the variable labels corresponding to the variable(s) in vars should be visible in the resulting table.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

section_div (string)
string which should be repeated as a section divider after the set of rows defined by (each sub-analysis/variable) of this analyze instruction, or NA_character_ (the default) for no section divider. This section divider will be overridden by a split-level section divider when both apply to the same position in the rendered output.

Details

When length(vars) > 1 and when two calls to analyze are done in sequence (the second with the default nested = TRUE), the analyses will be combined into a multi-variable analysis that will be reflected in the row structure of the resulting table. In these cases, the default is to show the label describing the variable analyzed for each of the resulting subtables, while that is hidden by default in one-variable cases.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Specifying Default Formatting Behavior

Default formatting behavior for rows generated by afun can be specified by one of format or formats_var. In both cases, these default formatting instructions *will not* supersede formatting specified from within afun at either the rcell or in_rows call levels; They will only apply to rows/cells whose formatting as returned by afun is either NULL or "default". When non-NULL, format is used to specify formats for all generated rows, and can be a character vector, a function, or a list of functions. It will be repped out to the number of rows once this is calculated during the tabulation process, but will be overridden by formats specified within rcell calls in afun.

format can accept a format label string (see formatters::list_valid_format_labels()), a formatting function, an unnamed list, or a named list.

When format is an unnamed list - or a named list where not all values of vars appear in the names - its elements will be repped out to the number of rows generated by afun (separately) within each

row facet afun is applied within. **This includes recycling behavior, even in the case where the number of rows is not cleanly divisible by the number of specified formats**. This behavior is retained largely for legacy reasons and switching to the new named-list behavior is advised where applicable.

When format is a named list whose names contain all values in vars, the elements of format are taken to be specific to the analysis of the corresponding variable; this allows us to specify a multi-variable analysis where e.g., the different variables are analyzed by the same afun but have different levels of measurement precision (and thus different formatting needs). In this case the var-specific formatting can be a single format (label string or function) or can be a named list whose names will be matched up to those of the rows generated by applying afun in each row facet. Matching of formats to rows is performed the same as in the formats_var case and is described below.

When formats_var is non-NULL, it specifies the name of a list column containing formatting instructions for one or more rows afun will generate when applied within a row facet. This can be used when the analysis results for a single variable (e.g., value or AVAL in long-form data) should be formatted differently within different row facets (e.g., when faceting on statistic or PARAMCD). The value of df[[formats_var]] is assumed without verification to be constant within each row facet afun is applied within, and the first (list) value of the column within the row facet data will be used.

In the formats_var case as well as the case of format being a named list containing the values of vars, after rows are created during tabulation, the default formats are matched and applied to them as follows:

1. When the generated row's name (as given by obj_name) matches a name in the list, the corresponding default format is applied,
2. for those without exact matches, the default format whose name provides *the best partial match* to each row name is applied,
3. For those without default format names that partially match the row name, no default format is applied.

Note carefully that in (2), it is the names of the list of formats that are partially matching the row names not the other way around.

The Analysis Function

The analysis function (afun) should take as its first parameter either x or df. Whichever of these the function accepts will change the behavior when tabulation is performed as follows:

- If afun's first parameter is x, it will receive the corresponding subset *vector* of data from the relevant column (from var here) of the raw data being used to build the table.
- If afun's first parameter is df, it will receive the corresponding subset *data frame* (i.e. all columns) of the raw data being tabulated.

In addition to differentiation on the first argument, the analysis function can optionally accept a number of other parameters which, *if and only if* present in the formals, will be passed to the function by the tabulation machinery. These are listed and described in additional_fun_params.

Nesting Anchor Resolution

When `nested` is `TRUE`, `at_sibling` allows you to set a *nesting anchor* that your new `split_rows_by*` or `analyze*` directive should be placed as a sibling to. The lookup for this anchor occurs *only in the currently active top-level nesting stack*, meaning the directives that have occurred since the last split or analysis with `nested == FALSE`.

Furthermore, resolution occurs against the first element of each arm of a branching point caused by any previous uses of `at_sibling` but *only descends into the last arm*.

So for example if our previous layout was generated via:

```
lyt <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR2", nested = FALSE) |>
  split_rows_by("RACE") |>
  analyze("AGE") |>
  split_rows_by("SEX", at_sibling = "RACE") |>
  analyze("BMRKR1")
```

The eligible anchor points would be `"BMRKR2"`, `"RACE"`, `"SEX"` and `"BMRKR1"`. `"AGE"` is masked by the branching caused by anchoring our `SEX` split on `RACE`.

Finally, while `at_sibling` does support de-duplication of `"<name>[i]"` anchors, it does so **within the set of available anchors**, which can be counter-intuitive. It is strongly suggested that the `parent_name` and `table_names` argument(s) of `split_rows_by*` and `analyze` be used to prevent the need for this. `at_sibling` will resolve to table names overridden in this manner.

Note

None of the arguments described in additional_fun_params can be overridden via `extra_args` or when calling `make_afun()`. `.N_col` and `.N_total` can be overridden via the `col_counts` argument to `build_table()`. Alternative values for the others must be calculated within `afun` based on a combination of extra arguments and the unmodified values provided by the tabulation framework.

Author(s)

Gabriel Becker

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = list_wrap_x(summary), format = "xx.xx")
lyt

tbl <- build_table(lyt, DM)
tbl

lyt2 <- basic_table() |>
  split_cols_by("Species") |>
```

```
  analyze(head(names(iris), -1), afun = function(x) {
    list(
      "mean / sd" = rcell(c(mean(x), sd(x)), format = "xx.xx (xx.xx)"),
      "range" = rcell(diff(range(x)), format = "xx.xx")
    )
  })
lyt2

tbl2 <- build_table(lyt2, iris)
tbl2
```

`analyze_colvars` *Generate rows analyzing different variables across columns*

Description

Generate rows analyzing different variables across columns

Usage

```
analyze_colvars(
  lyt,
  afun,
  parent_name = get_acolvar_name(lyt),
  format = NULL,
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  extra_args = list(),
  indent_mod = 0L,
  inclNAs = FALSE
)
```

Arguments

`lyt`	(`PreDataTableLayouts`) layout object pre-data used for tabulation.
`afun`	(`function` or `list`) function(s) to be used to calculate the values in each column. The list will be repped out as needed and matched by position with the columns during tabulation. This functions accepts the same parameters as `analyze()` like `afun` and `format`. For further information see additional_fun_params.
`parent_name`	(`character(1)`) Name to assign to the table corresponding to the *split* or *group of sibling analyses*, for `split_rows_by*` and `analyze*` when analyzing more than one variable, respectively. Ignored when analyzing a single variable.

format (string, function, or list)
format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.

na_str (string)
string that should be displayed when the value of x is missing. Defaults to "NA".

nested (logical)
whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.

at_sibling (character(1) or NULL)
If non-null, a preceding split or analyze to anchor this instruction to as a direct sibling. Cannot select an instruction that is downstream of a point where a previously used anchor (See Nesting Anchor Resolution for details).

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

inclNAs (logical)
whether NA observations in the var variable(s) should be included when performing the analysis. Defaults to FALSE.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Nesting Anchor Resolution

When nested is TRUE, at_sibling allows you to set a *nesting anchor* that your new split_rows_by* or analyze* directive should be placed as a sibling to. The lookup for this anchor occurs *only in the currently active top-level nesting stack*, meaning the directives that have occurred since the last split or analysis with nested == FALSE.

Furthermore, resolution occurs against the first element of each arm of a branching point caused by any previous uses of at_sibling but *only descends into the last arm*.

So for example if our previous layout was generated via:

```
lyt <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR2", nested = FALSE) |>
```

```
  split_rows_by("RACE") |>
  analyze("AGE") |>
  split_rows_by("SEX", at_sibling = "RACE") |>
  analyze("BMRKR1")
```

The eligible anchor points would be "BMRKR2", "RACE", "SEX" and "BMRKR1". "AGE" is masked by the branching caused by anchoring our SEX split on RACE.

Finally, while at_sibling does support de-duplication of "<name>[i]" anchors, it does so **within the set of available anchors**, which can be counter-intuitive. It is strongly suggested that the parent_name and table_names argument(s) of split_rows_by* and analyze be used to prevent the need for this. at_sibling will resolve to table names overridden in this manner.

Author(s)

Gabriel Becker

See Also

split_cols_by_multivar()

Examples

```
library(dplyr)

ANL <- DM |> mutate(value = rnorm(n()), pctdiff = runif(n()))

## toy example where we take the mean of the first variable and the
## count of >.5 for the second.
colfuns <- list(
  function(x) rcell(mean(x), format = "xx.x"),
  function(x) rcell(sum(x > .5), format = "xx")
)

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_multivar(c("value", "pctdiff")) |>
  split_rows_by("RACE",
    split_label = "ethnicity",
    split_fun = drop_split_levels
  ) |>
  summarize_row_groups() |>
  analyze_colvars(afun = colfuns)
lyt

tbl <- build_table(lyt, ANL)
tbl

lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_multivar(c("value", "pctdiff"),
    varlabels = c("Measurement", "Pct Diff")
```

```
  ) |>
  split_rows_by("RACE",
    split_label = "ethnicity",
    split_fun = drop_split_levels
  ) |>
  summarize_row_groups() |>
  analyze_colvars(afun = mean, format = "xx.xx")

tbl2 <- build_table(lyt2, ANL)
tbl2
```

AnalyzeVarSplit *Define a subset tabulation/analysis*

Description

Define a subset tabulation/analysis

Define a subset tabulation/analysis

Usage

```
AnalyzeVarSplit(
  var,
  split_label = var,
  afun,
  defrowlab = "",
  cfun = NULL,
  cformat = NULL,
  split_format = NULL,
  split_na_str = NA_character_,
  inclNAs = FALSE,
  split_name = var,
  extra_args = list(),
  indent_mod = 0L,
  label_pos = "default",
  cvar = "",
  section_div = NA_character_,
  formats_var = NULL,
  na_strs_var = NULL
)

AnalyzeColVarSplit(
  afun,
  defrowlab = "",
  cfun = NULL,
  cformat = NULL,
```

```
  split_format = NULL,
  split_na_str = NA_character_,
  inclNAs = FALSE,
  split_name = "",
  extra_args = list(),
  indent_mod = 0L,
  label_pos = "default",
  cvar = "",
  section_div = NA_character_
)

AnalyzeMultiVars(
  var,
  split_label = "",
  afun,
  defrowlab = "",
  cfun = NULL,
  cformat = NULL,
  split_format = NULL,
  split_na_str = NA_character_,
  inclNAs = FALSE,
  .payload = NULL,
  split_name = NULL,
  extra_args = list(),
  indent_mod = 0L,
  child_labels = c("default", "topleft", "visible", "hidden"),
  child_names = var,
  cvar = "",
  section_div = NA_character_,
  formats_var = NULL,
  na_strs_var = NULL
)
```

Arguments

var	(string) variable name.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
afun	(function) analysis function. Must accept `x` or `df` as its first parameter. Can optionally take other parameters which will be populated by the tabulation framework. See Details in `analyze()`.
defrowlab	(character) default row labels, if not specified by the return value of `afun`.

cfun (list, function, or NULL)
tabulation function(s) for creating content rows. Must accept x or df as first parameter. Must accept labelstr as the second argument. Can optionally accept all optional arguments accepted by analysis functions. See analyze().

cformat (string, function, or list)
format for content rows.

split_format (string, function, or list)
default format associated with the split being created.

split_na_str (character)
NA string vector for use with split_format.

inclNAs (logical)
whether NA observations in the var variable(s) should be included when performing the analysis. Defaults to FALSE.

split_name (string)
name associated with the split (for pathing, etc.).

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

label_pos (string)
location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

cvar (string)
the variable, if any, that the content function should accept. Defaults to NA.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

formats_var (string or NULL)
NULL (the default) or the name of the list column containing named lists of default formats to use. These will be applied with the same precedence as the format argument; i.e., they will not override formats (other than "default") set within the afun. Cannot be used simultaneously with format.

na_strs_var (string or NULL)
NULL (the default) or the name of the list column containing named lists of default NA strings to use. These will be applied with the same precedence as the format argument; i.e., they will not override formats (other than "default") set within the afun. Cannot be used simultaneously with format. Cannot be used if formats_var is NULL.

.payload	(list) used internally, not intended to be set by end users.
child_labels	(string) the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.
child_names	(character) names to be given to the subsplits contained by a compound split (typically an AnalyzeMultiVars split object).

Value

An AnalyzeVarSplit object.

An AnalyzeMultiVars split object.

Author(s)

Gabriel Becker

---

append_topleft *Append a description to the 'top-left' materials for the layout*

Description

This function *adds* newlines to the current set of "top-left materials".

Usage

```
append_topleft(lyt, newlines)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
newlines	(character) the new line(s) to be added to the materials.

Details

Adds newlines to the set of strings representing the 'top-left' materials declared in the layout (the content displayed to the left of the column labels when the resulting tables are printed).

Top-left material strings are stored and then displayed *exactly as is*, no structure or indenting is applied to them either when they are added or when they are displayed.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Note

Currently, where in the construction of the layout this is called makes no difference, as it is independent of the actual splitting keywords. This may change in the future.

This function is experimental, its name and the details of its behavior are subject to change in future versions.

See Also

top_left()

Examples

```
library(dplyr)

DM2 <- DM |> mutate(RACE = factor(RACE), SEX = factor(SEX))

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  split_rows_by("RACE") |>
  append_topleft("Ethnicity") |>
  analyze("AGE") |>
  append_topleft("  Age")

tbl <- build_table(lyt, DM2)
tbl
```

---

as_html *Convert an* rtable *object to a* shiny.tag *HTML object*

Description

The returned HTML object can be immediately used in shiny and rmarkdown.

Usage

```
as_html(
  x,
  width = NULL,
  class_table = "table table-condensed table-hover",
  class_tr = NULL,
  class_th = NULL,
  link_label = NULL,
  bold = c("header"),
  header_sep_line = TRUE,
  no_spaces_between_cells = FALSE,
  expand_newlines = FALSE,
```

```
  round_type = if (is(x, "VTableTree")) obj_round_type(x) else valid_round_type
)
```

Arguments

x	(VTableTree) a TableTree object.
width	(character) a string to indicate the desired width of the table. Common input formats include a percentage of the viewer window width (e.g. "100%") or a distance value (e.g. "300px"). Defaults to NULL.
class_table	(character) class for table tag.
class_tr	(character) class for tr tag.
class_th	(character) class for th tag.
link_label	(character) link anchor label (not including tab: prefix) for the table.
bold	(character) elements in table output that should be bold. Options are "main_title", "subtitles", "header", "row_names", "label_rows", and "content_rows" (which includes any non-label rows). Defaults to "header".
header_sep_line	(flag) whether a black line should be printed to under the table header. Defaults to TRUE.
no_spaces_between_cells	(flag) whether spaces between table cells should be collapsed. Defaults to FALSE.
expand_newlines	(flag) Defaults to FALSE, relying on html output to solve newline characters (\n). Doing this keeps the structure of the cells but may depend on the output device.
round_type	("iec", "iec_mod" or "sas") the type of rounding to perform. See round_fmt() for details.

Value

A shiny.tag object representing x in HTML.

Examples

```
tbl <- rtable(
  header = LETTERS[1:3],
  format = "xx",
  rrow("r1", 1, 2, 3),
```

```
  rrow("r2", 4, 3, 2, indent = 1),
  rrow("r3", indent = 2)
)

as_html(tbl)

as_html(tbl, class_table = "table", class_tr = "row")

as_html(tbl, bold = c("header", "row_names"))

## Not run:
Viewer(tbl)

## End(Not run)
```

---

asvec *Convert to a vector*

Description

Convert an `rtables` framework object into a vector, if possible. This is unlikely to be useful in realistic scenarios.

Usage

```
## S4 method for signature 'VTableTree'
as.vector(x, mode = "any")
```

Arguments

x	(ANY) the object to be converted to a vector.
mode	(string) passed on to `as.vector()`.

Value

A vector of the chosen mode (or an error is raised if more than one row was present).

Note

This only works for a table with a single row or a row object.

basic_table *Layout with 1 column and zero rows*

Description

Every layout must start with a basic table.

Usage

```
basic_table(
  title = "",
  subtitles = character(),
  main_footer = character(),
  prov_footer = character(),
  show_colcounts = NA,
  colcount_format = "(N=xx)",
  header_section_div = NA_character_,
  top_level_section_div = NA_character_,
  inset = 0L,
  round_type = valid_round_type
)
```

Arguments

title	(string) single string to use as main title (formatters::main_title()). Ignored for subtables.
subtitles	(character) a vector of strings to use as subtitles (formatters::subtitles()), where every element is printed on a separate line. Ignored for subtables.
main_footer	(character) a vector of strings to use as main global (non-referential) footer materials (formatters::main_footer()) where every element is printed on a separate line.
prov_footer	(character) a vector of strings to use as provenance-related global footer materials (formatters::prov_footer()), where every element is printed on a separate line.
show_colcounts	(logical(1)) Indicates whether the lowest level of applied to data. NA, the default, indicates that the show_colcounts argument(s) passed to the relevant calls to split_cols_by* functions. Non-missing values will override the behavior specified in column splitting layout instructions which create the lowest level, or leaf, columns.
colcount_format	(string) format for use when displaying the column counts. Must be 1d, or 2d where one component is a percent. This will also apply to any displayed higher level column counts where an explicit format was not specified. Defaults to "(N=xx)". See Details below.

header_section_div
: (string)
string which will be used to divide the header from the table. See header_section_div() for the associated getter and setter. Please consider changing last element of section_div() when concatenating tables that require a divider between them.

top_level_section_div
: (character(1))
if assigned a single character, the first (top level) split or division of the table will be highlighted by a line made of that character. See section_div for more information.

inset
: (numeric(1))
number of spaces to inset the table header, table body, referential footnotes, and main_footer, as compared to alignment of title, subtitle, and provenance footer. Defaults to 0 (no inset).

round_type
: ("iec" (default), "iec_mod" or "sas")
the type of rounding to perform. See formatters::format_value() for details.

Details

colcount_format is ignored if show_colcounts is FALSE (the default). When show_colcounts is TRUE, and colcount_format is 2-dimensional with a percent component, the value component for the percent is always populated with 1 (i.e. 100%). 1d formats are used to render the counts exactly as they normally would be, while 2d formats which don't include a percent, and all 3d formats result in an error. Formats in the form of functions are not supported for colcount format. See formatters::list_valid_format_labels() for the list of valid format labels to select from.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Note

- Because percent components in colcount_format are *always* populated with the value 1, we can get arguably strange results, such as that individual arm columns and a combined "all patients" column all list "100%" as their percentage, even though the individual arm columns represent strict subsets of the "all patients" column.
- Note that subtitles (formatters::subtitles()) and footers (formatters::main_footer() and formatters::prov_footer()) that span more than one line can be supplied as a character vector to maintain indentation on multiple lines.

Examples

```
lyt <- basic_table() |>
  analyze("AGE", afun = mean)

tbl <- build_table(lyt, DM)
tbl
```

```
lyt2 <- basic_table(
  title = "Title of table",
  subtitles = c("a number", "of subtitles"),
  main_footer = "test footer",
  prov_footer = paste(
    "test.R program, executed at",
    Sys.time()
  )
) |>
  split_cols_by("ARM") |>
  analyze("AGE", mean)

tbl2 <- build_table(lyt2, DM)
tbl2

lyt3 <- basic_table(
  show_colcounts = TRUE,
  colcount_format = "xx. (xx.%)"
) |>
  split_cols_by("ARM")
```

---

brackets *Retrieve and assign elements of a* TableTree

Description

Retrieve and assign elements of a TableTree

Usage

```
## S4 replacement method for signature 'VTableTree,ANY,ANY,list'
x[i, j, ...] <- value

## S4 method for signature 'VTableTree,logical,logical'
x[i, j, ..., drop = FALSE]
```

Arguments

x	(TableTree) a TableTree object.
i	(numeric(1)) index.
j	(numeric(1)) index.
...	additional arguments. Includes:

keep_topleft (flag) ([only) whether the top-left material for the table should be retained after subsetting. Defaults to TRUE if all rows are included (i.e. subsetting was by column), and drops it otherwise.

keep_titles (flag) whether title information should be retained. Defaults to FALSE.

keep_footers (flag) whether non-referential footer information should be retained. Defaults to keep_titles.

reindex_refs (flag) whether referential footnotes should be re-indexed as if the resulting subset is the entire table. Defaults to TRUE.

value (list, TableRow, or TableTree)
replacement value.

drop (flag)
whether the value in the cell should be returned if one cell is selected by the combination of i and j. It is not possible to return a vector of values. To do so please consider using cell_values(). Defaults to FALSE.

Details

By default, subsetting drops the information about title, subtitle, main footer, provenance footer, and topleft. If only a column is selected and all rows are kept, the topleft information remains as default. Any referential footnote is kept whenever the subset table contains the referenced element.

Value

A TableTree (or ElementaryTable) object, unless a single cell was selected with drop = TRUE, in which case the (possibly multi-valued) fully stripped raw value of the selected cell.

Note

Subsetting always preserve the original order, even if provided indexes do not preserve it. If sorting is needed, please consider using sort_at_path(). Also note that character indices are treated as paths, not vectors of names in both [and [<-.

See Also

- sort_at_path() to understand sorting.
- summarize_row_groups() to understand path structure.

Examples

```
lyt <- basic_table(
  title = "Title",
  subtitles = c("Sub", "titles"),
  prov_footer = "prov footer",
  main_footer = "main footer"
) |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  analyze(c("AGE"))
```

```
tbl <- build_table(lyt, DM)
top_left(tbl) <- "Info"
tbl

# As default header, footer, and topleft information is lost
tbl[1, ]
tbl[1:2, 2]

# Also boolean filters can work
tbl[, c(FALSE, TRUE, FALSE)]

# If drop = TRUE, the content values are directly retrieved
tbl[2, 1]
tbl[2, 1, drop = TRUE]

# Drop works also if vectors are selected, but not matrices
tbl[, 1, drop = TRUE]
tbl[2, , drop = TRUE]
tbl[1, 1, drop = TRUE] # NULL because it is a label row
tbl[2, 1:2, drop = TRUE] # vectors can be returned only with cell_values()
tbl[1:2, 1:2, drop = TRUE] # no dropping because it is a matrix

# If all rows are selected, topleft is kept by default
tbl[, 2]
tbl[, 1]

# It is possible to deselect values
tbl[-2, ]
tbl[, -1]

# Values can be reassigned
tbl[4, 2] <- rcell(999, format = "xx.x")
tbl[2, ] <- list(rrow("FFF", 888, 666, 777))
tbl[6, ] <- list(-111, -222, -333)
tbl

# We can keep some information from the original table if we need
tbl[1, 2, keep_titles = TRUE]
tbl[1, 2, keep_footers = TRUE, keep_titles = FALSE]
tbl[1, 2, keep_footers = FALSE, keep_titles = TRUE]
tbl[1, 2, keep_footers = TRUE]
tbl[1, 2, keep_topleft = TRUE]

# Keeps the referential footnotes when subset contains them
fnotes_at_path(tbl, rowpath = c("SEX", "M", "AGE", "Mean")) <- "important"
tbl[4, 1]
tbl[2, 1] # None present

# We can reindex referential footnotes, so that the new table does not depend
#  on the original one
fnotes_at_path(tbl, rowpath = c("SEX", "U", "AGE", "Mean")) <- "important"
tbl[, 1] # both present
```

```
tbl[5:6, 1] # {1} because it has been indexed again
tbl[5:6, 1, reindex_refs = FALSE] # {2} -> not reindexed

# Note that order can not be changed with subsetting
tbl[c(4, 3, 1), c(3, 1)] # It preserves order and wanted selection
```

`build_table` *Create a table from a layout and data*

Description

Layouts are used to describe a table pre-data. `build_table` is used to create a table using a layout and a dataset.

Usage

```
build_table(
  lyt,
  df,
  alt_counts_df = NULL,
  col_counts = NULL,
  col_total = if (is.null(alt_counts_df)) nrow(df) else nrow(alt_counts_df),
  topleft = NULL,
  hsep = default_hsep(),
  round_type = if (is(lyt, "PreDataTableLayouts")) obj_round_type(lyt) else
    valid_round_type,
  ...
)
```

Arguments

`lyt`	(`PreDataTableLayouts`) layout object pre-data used for tabulation.
`df`	(`data.frame` or `tibble`) dataset.
`alt_counts_df`	(`data.frame` or `tibble`) alternative full dataset the rtables framework will use *only* when calculating column counts.
`col_counts`	(`numeric` or `NULL`) **[Deprecated]** if non-`NULL`, column counts *for leaf-columns only* which override those calculated automatically during tabulation. Must specify "counts" for *all* leaf-columns if non-`NULL`. `NA` elements will be replaced with the automatically calculated counts. Turns on display of leaf-column counts when non-`NULL`.
`col_total`	(`integer(1)`) the total observations across all columns. Defaults to `nrow(df)`.

topleft	(character) override values for the "top left" material to be displayed during printing.
hsep	(string) set of characters to be repeated as the separator between the header and body of the table when rendered as text. Defaults to a connected horizontal line (unicode 2014) in locals that use a UTF charset, and to - elsewhere (with a once per session warning). See formatters::set_default_hsep() for further information.
round_type	("iec" (default), "iec_mod" or "sas") the type of rounding to perform. See formatters::format_value() for details.
...	ignored.

Details

When alt_counts_df is specified, column counts are calculated by applying the exact column subsetting expressions determined when applying column splitting to the main data (df) to alt_counts_df and counting the observations in each resulting subset.

In particular, this means that in the case of splitting based on cuts of the data, any dynamic cuts will have been calculated based on df and simply re-used for the count calculation.

Value

A TableTree or ElementaryTable object representing the table created by performing the tabulations declared in lyt to the data df.

Note

When overriding the column counts or totals care must be taken that, e.g., length() or nrow() are not called within tabulation functions, because those will NOT give the overridden counts. Writing/using tabulation functions which accept .N_col and .N_total or do not rely on column counts at all (even implicitly) is the only way to ensure overridden counts are fully respected.

Author(s)

Gabriel Becker

Examples

```
lyt <- basic_table() |>
  split_cols_by("Species") |>
  analyze("Sepal.Length", afun = function(x) {
    list(
      "mean (sd)" = rcell(c(mean(x), sd(x)), format = "xx.xx (xx.xx)"),
      "range" = diff(range(x))
    )
  })
lyt
```

```
tbl <- build_table(lyt, iris)
tbl

# analyze multiple variables
lyt2 <- basic_table() |>
  split_cols_by("Species") |>
  analyze(c("Sepal.Length", "Petal.Width"), afun = function(x) {
    list(
      "mean (sd)" = rcell(c(mean(x), sd(x)), format = "xx.xx (xx.xx)"),
      "range" = diff(range(x))
    )
  })

tbl2 <- build_table(lyt2, iris)
tbl2

# an example more relevant for clinical trials with column counts
lyt3 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = function(x) {
    setNames(as.list(fivenum(x)), c(
      "minimum", "lower-hinge", "median",
      "upper-hinge", "maximum"
    ))
  })

tbl3 <- build_table(lyt3, DM)
tbl3

tbl4 <- build_table(lyt3, subset(DM, AGE > 40))
tbl4

# with column counts calculated based on different data
miniDM <- DM[sample(1:NROW(DM), 100), ]
tbl5 <- build_table(lyt3, DM, alt_counts_df = miniDM)
tbl5

tbl6 <- build_table(lyt3, DM, col_counts = 1:3)
tbl6
```

---

c.RowsVerticalSection *Combine* RowsVerticalSection *objects*

Description

Combine two or more RowsVerticalSection objects (as returned by in_rows()) into a single object

Usage

```
## S3 method for class 'RowsVerticalSection'
c(...)
```

Arguments

`...`	`RowsVerticalSection` objects

Value

A single `RowsVerticalSection` object containing all row sections from the objects passed to `...`

`cbind_rtables` *Column-bind two* `TableTree` *objects*

Description

Column-bind two `TableTree` objects

Usage

```
cbind_rtables(x, ..., sync_count_vis = TRUE)
```

Arguments

`x`	(`TableTree` or `TableRow`) a table or row object.
`...`	one or more further objects of the same class as `x`.
`sync_count_vis`	(`logical(1)`) should column count visibility be synced across the new and existing columns. Currently defaults to `TRUE` for backwards compatibility but this may change in future releases.

Value

A formal table object.

Examples

```
x <- rtable(c("A", "B"), rrow("row 1", 1, 2), rrow("row 2", 3, 4))
y <- rtable("C", rrow("row 1", 5), rrow("row 2", 6))
z <- rtable("D", rrow("row 1", 9), rrow("row 2", 10))

t1 <- cbind_rtables(x, y)
t1

t2 <- cbind_rtables(x, y, z)
t2
```

```
col_paths_summary(t1)
col_paths_summary(t2)
```

`cell_values` *Retrieve cell values by row and column path*

Description

Retrieve cell values by row and column path

Usage

```
cell_values(tt, rowpath = NULL, colpath = NULL, omit_labrows = TRUE)

value_at(tt, rowpath = NULL, colpath = NULL)

## S4 method for signature 'VTableTree'
value_at(tt, rowpath = NULL, colpath = NULL)
```

Arguments

`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`rowpath`	(`character`) path in row-split space to the desired row(s). Can include `"@content"`.
`colpath`	(`character`) path in column-split space to the desired column(s). Can include `"*"`.
`omit_labrows`	(`flag`) whether label rows underneath `rowpath` should be omitted (`TRUE`, the default), or return empty lists of cell "values" (`FALSE`).

Value

- `cell_values` returns a `list` (regardless of the type of value the cells hold). If `rowpath` defines a path to a single row, `cell_values` returns the list of cell values for that row, otherwise a list of such lists, one for each row captured underneath `rowpath`. This occurs after subsetting to `colpath` has occurred.
- `value_at` returns the "unwrapped" value of a single cell, or an error, if the combination of `rowpath` and `colpath` do not define the location of a single cell in `tt`.

Note

`cell_values` will return a single cell's value wrapped in a list. Use `value_at` to receive the "bare" cell value.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  split_rows_by("RACE") |>
  summarize_row_groups() |>
  split_rows_by("STRATA1") |>
  analyze("AGE")


library(dplyr) ## for mutate
tbl <- build_table(lyt, DM |>
  mutate(SEX = droplevels(SEX), RACE = droplevels(RACE)))

row_paths_summary(tbl)
col_paths_summary(tbl)

cell_values(
  tbl, c("RACE", "ASIAN", "STRATA1", "B"),
  c("ARM", "A: Drug X", "SEX", "F")
)

# it's also possible to access multiple values by being less specific
cell_values(
  tbl, c("RACE", "ASIAN", "STRATA1"),
  c("ARM", "A: Drug X", "SEX", "F")
)
cell_values(tbl, c("RACE", "ASIAN"), c("ARM", "A: Drug X", "SEX", "M"))

## any arm, male columns from the ASIAN content (i.e. summary) row
cell_values(
  tbl, c("RACE", "ASIAN", "@content"),
  c("ARM", "B: Placebo", "SEX", "M")
)
cell_values(
  tbl, c("RACE", "ASIAN", "@content"),
  c("ARM", "*", "SEX", "M")
)

## all columns
cell_values(tbl, c("RACE", "ASIAN", "STRATA1", "B"))

## all columns for the Combination arm
cell_values(
  tbl, c("RACE", "ASIAN", "STRATA1", "B"),
  c("ARM", "C: Combination")
)

cvlist <- cell_values(
  tbl, c("RACE", "ASIAN", "STRATA1", "B", "AGE", "Mean"),
  c("ARM", "B: Placebo", "SEX", "M")
)
```

```
cvnolist <- value_at(
  tbl, c("RACE", "ASIAN", "STRATA1", "B", "AGE", "Mean"),
  c("ARM", "B: Placebo", "SEX", "M")
)
stopifnot(identical(cvlist[[1]], cvnolist))
```

`CellValue` *Constructor for Cell Value*

Description

Constructor for Cell Value

Usage

```
CellValue(
  val,
  format = NULL,
  colspan = 1L,
  label = NULL,
  indent_mod = NULL,
  footnotes = NULL,
  align = NULL,
  format_na_str = NULL,
  stat_names = NA_character_,
  round_type = valid_round_type
)
```

Arguments

`val`	(ANY) value in the cell exactly as it should be passed to a formatter or returned when extracted.
`format`	(`string`, `function`, or `list`) format associated with this split. Formats can be declared via strings (`"xx.x"`) or function. In cases such as `analyze` calls, they can be character vectors or lists of functions. See `formatters::list_valid_format_labels()` for a list of all available format strings.
`colspan`	(`integer(1)`) column span value.
`label`	(`string`) a label (not to be confused with the name) for the object/structure.
`indent_mod`	(`numeric`) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

footnotes	(list or NULL) referential footnote messages for the cell.
align	(string or NULL) alignment the value should be rendered with. Defaults to "center" if NULL is used. See formatters::list_valid_aligns() for all currently supported alignments.
format_na_str	(string) string which should be displayed when formatted if this cell's value(s) are all NA.
stat_names	(character or NA) names for the statistics in the cell. It can be a vector of strings. If NA, statistic names are not specified.
round_type	("iec" (default), "iec_mod" or "sas") the type of rounding to perform. See formatters::format_value() for details.

Value

An object representing the value within a single cell within a populated table. The underlying structure of this object is an implementation detail and should not be relied upon beyond calling accessors for the class.

---

clayout *Column information/structure accessors*

Description

Column information/structure accessors

Usage

```
clayout(obj)

## S4 method for signature 'VTableNodeInfo'
clayout(obj)

## S4 method for signature 'PreDataTableLayouts'
clayout(obj)

## S4 method for signature 'ANY'
clayout(obj)

clayout(object) <- value

## S4 replacement method for signature 'PreDataTableLayouts'
clayout(object) <- value
```

```
col_info(obj)

## S4 method for signature 'VTableNodeInfo'
col_info(obj)

col_info(obj) <- value

## S4 replacement method for signature 'TableRow'
col_info(obj) <- value

## S4 replacement method for signature 'ElementaryTable'
col_info(obj) <- value

## S4 replacement method for signature 'TableTree'
col_info(obj) <- value

coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'InstantiatedColumnInfo'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'PreDataTableLayouts'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'PreDataColLayout'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
```

```
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'LayoutColTree'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'VTableTree'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

## S4 method for signature 'TableRow'
coltree(
  obj,
  df = NULL,
  rtpos = TreePos(),
  alt_counts_df = df,
  ccount_format = "(N=xx)"
)

col_exprs(obj, df = NULL)

## S4 method for signature 'PreDataTableLayouts'
col_exprs(obj, df = NULL)

## S4 method for signature 'PreDataColLayout'
col_exprs(obj, df = NULL)

## S4 method for signature 'InstantiatedColumnInfo'
col_exprs(obj, df = NULL)

col_counts(obj, path = NULL)

## S4 method for signature 'InstantiatedColumnInfo'
col_counts(obj, path = NULL)

## S4 method for signature 'VTableNodeInfo'
```

```
col_counts(obj, path = NULL)

col_counts(obj, path = NULL) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
col_counts(obj, path = NULL) <- value

## S4 replacement method for signature 'VTableNodeInfo'
col_counts(obj, path = NULL) <- value

col_total(obj)

## S4 method for signature 'InstantiatedColumnInfo'
col_total(obj)

## S4 method for signature 'VTableNodeInfo'
col_total(obj)

col_total(obj) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
col_total(obj) <- value

## S4 replacement method for signature 'VTableNodeInfo'
col_total(obj) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
object	(ANY) the object to modify in place.
value	(ANY) the new value.
df	(data.frame or NULL) data to use if the column information is being generated from a pre-data layout object.
rtpos	(TreePos) root position.
alt_counts_df	(data.frame or tibble) alternative full dataset the rtables framework will use *only* when calculating column counts.
ccount_format	(FormatSpec) The format to be used by default for column counts throughout this column tree (i.e. if not overridden by a more specific format specification).
path	(character or NULL) col_counts accessor and setter only. Path (in column structure).

Value

A LayoutColTree object.

Returns various information about columns, depending on the accessor used.

See Also

facet_colcount()

---

clear_indent_mods *Clear all indent modifiers from a table*

Description

Clear all indent modifiers from a table

Usage

```
clear_indent_mods(tt)

## S4 method for signature 'VTableTree'
clear_indent_mods(tt)

## S4 method for signature 'TableRow'
clear_indent_mods(tt)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.

Value

The same class as tt, with all indent modifiers set to zero.

Examples

```
lyt1 <- basic_table() |>
  summarize_row_groups("STUDYID", label_fstr = "overall summary") |>
  split_rows_by("AEBODSYS", child_labels = "visible") |>
  summarize_row_groups("STUDYID", label_fstr = "subgroup summary") |>
  analyze("AGE", indent_mod = -1L)

tbl1 <- build_table(lyt1, ex_adae)
tbl1
clear_indent_mods(tbl1)
```

colcount_visible *Value and Visibility of specific column counts by path*

Description

Value and Visibility of specific column counts by path

Usage

```
colcount_visible(obj, path)

## S4 method for signature 'VTableTree'
colcount_visible(obj, path)

## S4 method for signature 'InstantiatedColumnInfo'
colcount_visible(obj, path)

## S4 method for signature 'LayoutColTree'
colcount_visible(obj, path)

colcount_visible(obj, path) <- value

## S4 replacement method for signature 'VTableTree'
colcount_visible(obj, path) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
colcount_visible(obj, path) <- value

## S4 replacement method for signature 'LayoutColTree'
colcount_visible(obj, path) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
value	(ANY) the new value.

Value

for colcount_visible a logical scalar indicating whether the specified position in the column hierarchy is set to display its column count; for colcount_visible<-, obj updated with the specified count displaying behavior set.

Note

Users generally should not call `colcount_visible` directly, as setting sibling facets to have differing column count visibility will result in an error when printing or paginating the table.

---

collect_leaves *Collect leaves of a* TableTree

Description

Collect leaves of a `TableTree`

Usage

```
collect_leaves(tt, incl.cont = TRUE, add.labrows = FALSE)
```

Arguments

`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`incl.cont`	(`flag`) whether to include rows from content tables within the tree. Defaults to `TRUE`.
`add.labrows`	(`flag`) whether to include label rows. Defaults to `FALSE`.

Value

A list of `TableRow` objects for all rows in the table.

---

coltree_structure *Display column tree structure*

Description

Displays the tree structure of the columns of a table or column structure object.

Usage

```
coltree_structure(obj)
```

Arguments

`obj`	(`ANY`) the object for the accessor to access or modify.

Value

Nothing, called for its side effect of displaying a summary to the terminal.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("STRATA1") |>
  split_cols_by("SEX", nested = FALSE) |>
  analyze("AGE")

tbl <- build_table(lyt, ex_adsl)
coltree_structure(tbl)
```

---

compare_rtables *Compare two rtables*

Description

Prints a matrix where . means cell matches, X means cell does not match, + cell (row) is missing, and - cell (row) should not be there. If `structure` is set to TRUE, C indicates column-structure mismatch, R indicates row-structure mismatch, and S indicates mismatch in both row and column structure.

Usage

```
compare_rtables(
  object,
  expected,
  tol = 0.1,
  comp.attr = TRUE,
  structure = FALSE
)
```

Arguments

object	(VTableTree) rtable to test.
expected	(VTableTree) expected rtable.
tol	(numeric(1)) tolerance.
comp.attr	(flag) whether to compare cell formats. Other attributes are silently ignored.
structure	(flag) whether structures (in the form of column and row paths to cells) should be compared. Currently defaults to FALSE, but this is subject to change in future versions.

Value

A matrix of class `rtables_diff` representing the differences between `object` and `expected` as described above.

Note

In its current form, `compare_rtables` does not take structure into account, only row and cell position.

Examples

```
t1 <- rtable(header = c("A", "B"), format = "xx", rrow("row 1", 1, 2))
t2 <- rtable(header = c("A", "B", "C"), format = "xx", rrow("row 1", 1, 2, 3))

compare_rtables(object = t1, expected = t2)

if (interactive()) {
  Viewer(t1, t2)
}

expected <- rtable(
  header = c("ARM A\nN=100", "ARM B\nN=200"),
  format = "xx",
  rrow("row 1", 10, 15),
  rrow(),
  rrow("section title"),
  rrow("row colspan", rcell(c(.345543, .4432423), colspan = 2, format = "(xx.xx, xx.xx)"))
)

expected

object <- rtable(
  header = c("ARM A\nN=100", "ARM B\nN=200"),
  format = "xx",
  rrow("row 1", 10, 15),
  rrow("section title"),
  rrow("row colspan", rcell(c(.345543, .4432423), colspan = 2, format = "(xx.xx, xx.xx)"))
)

compare_rtables(object, expected, comp.attr = FALSE)

object <- rtable(
  header = c("ARM A\nN=100", "ARM B\nN=200"),
  format = "xx",
  rrow("row 1", 10, 15),
  rrow(),
  rrow("section title")
)

compare_rtables(object, expected)

object <- rtable(
```

```
  header = c("ARM A\nN=100", "ARM B\nN=200"),
  format = "xx",
  rrow("row 1", 14, 15.03),
  rrow(),
  rrow("section title"),
  rrow("row colspan", rcell(c(.345543, .4432423), colspan = 2, format = "(xx.xx, xx.xx)"))
)

compare_rtables(object, expected)

object <- rtable(
  header = c("ARM A\nN=100", "ARM B\nN=200"),
  format = "xx",
  rrow("row 1", 10, 15),
  rrow(),
  rrow("section title"),
  rrow("row colspan", rcell(c(.345543, .4432423), colspan = 2, format = "(xx.x, xx.x)"))
)

compare_rtables(object, expected)
```

`compat_args` *Compatibility argument conventions*

Description

Compatibility argument conventions

Usage

```
compat_args(.lst, row.name, format, indent, label, inset)
```

Arguments

`.lst`	(`list`) an already-collected list of arguments to be used instead of the elements of `....` Arguments passed via `...` will be ignored if this is specified.
`row.name`	(`string` or `NULL`) row name. If `NULL`, an empty string is used as `row.name` of the `rrow()`.
`format`	(`string`, `function`, or `list`) the format label (string) or formatter function to apply to the cell values passed via `....` See `formatters::list_valid_format_labels()` for currently supported format labels.
`indent`	**[Deprecated]**
`label`	(`string`) a label (not to be confused with the name) for the object/structure.

inset (integer(1))
the table inset for the row or table being constructed. See formatters::table_inset() for details.

Value

No return value.

See Also

Other conventions: constr_args(), gen_args(), lyt_args(), sf_args()

---

cont_n_allcols *Score functions for sorting* TableTrees

Description

Score functions for sorting TableTrees

Usage

```
cont_n_allcols(tt)

cont_n_onecol(j)
```

Arguments

tt (TableTree or related class)
a TableTree object representing a populated table.

j (numeric(1))
index of column used for scoring.

Value

A single numeric value indicating score according to the relevant metric for tt, to be used when sorting.

See Also

For examples and details, please read the documentation for sort_at_path() and the Sorting and Pruning vignette.

content_table *Retrieve or set content table from a* TableTree

Description

Returns the content table of obj if it is a TableTree object, or NULL otherwise.

Usage

```
content_table(obj)

content_table(obj) <- value
```

Arguments

obj	(TableTree) the table object.
value	(ElementaryTable) the new content table for obj.

Value

the ElementaryTable containing the (top level) *content rows* of obj (or NULL if obj is not a formal table object).

counts_wpcts *Analysis function to count levels of a factor with percentage of the column total*

Description

Analysis function to count levels of a factor with percentage of the column total

Usage

```
counts_wpcts(x, .N_col)
```

Arguments

x	(factor) a vector of data, provided by rtables pagination machinery.
.N_col	(integer(1)) total count for the column, provided by rtables pagination machinery.

Value

A RowsVerticalSection object with counts (and percents) for each level of the factor.

Examples

```
counts_wpcts(DM$SEX, 400)
```

---

custom_split_funs *Custom split functions*

Description

Split functions provide the work-horse for rtables's generalized partitioning. These functions accept a (sub)set of incoming data and a split object, and return "splits" of that data.

Custom Splitting Function Details

User-defined custom split functions can perform any type of computation on the incoming data provided that they meet the requirements for generating "splits" of the incoming data based on the split object.

Split functions are functions that accept:

df a data.frame of incoming data to be split.

spl a Split object. This is largely an internal detail custom functions will not need to worry about, but obj_name(spl), for example, will give the name of the split as it will appear in paths in the resulting table.

vals any pre-calculated values. If given non-NULL values, the values returned should match these. Should be NULL in most cases and can usually be ignored.

labels any pre-calculated value labels. Same as above for values.

trim if TRUE, resulting splits that are empty are removed.

(optional) .spl_context a data.frame describing previously performed splits which collectively arrived at df.

The function must then output a named list with the following elements:

values the vector of all values corresponding to the splits of df.

datasplit a list of data.frames representing the groupings of the actual observations from df.

labels a character vector giving a string label for each value listed in the values element above.

(optional) extras if present, extra arguments are to be passed to summary and analysis functions whenever they are executed on the corresponding element of datasplit or a subset thereof.

One way to generate custom splitting functions is to wrap existing split functions and modify either the incoming data before they are called or their outputs.

See Also

make_split_fun() for the API for creating custom split functions, and split_funcs for a variety of pre-defined split functions.

Examples

```
# Example of a picky split function. The number of values in the column variable
# var decrees if we are going to print also the column with all observation
# or not.

picky_splitter <- function(var) {
  # Main layout function
  function(df, spl, vals, labels, trim) {
    orig_vals <- vals

    # Check for number of levels if all are selected
    if (is.null(vals)) {
      vec <- df[[var]]
      vals <- unique(vec)
    }

    # Do a split with or without All obs
    if (length(vals) == 1) {
      do_base_split(spl = spl, df = df, vals = vals, labels = labels, trim = trim)
    } else {
      fnc_tmp <- add_overall_level("Overall", label = "All Obs", first = FALSE)
      fnc_tmp(df = df, spl = spl, vals = orig_vals, trim = trim)
    }
  }
}

# Data sub-set
d1 <- subset(ex_adsl, ARM == "A: Drug X" | (ARM == "B: Placebo" & SEX == "F"))
d1 <- subset(d1, SEX %in% c("M", "F"))
d1$SEX <- factor(d1$SEX)

# This table uses the number of values in the SEX column to add the overall col or not
lyt <- basic_table() |>
  split_cols_by("ARM", split_fun = drop_split_levels) |>
  split_cols_by("SEX", split_fun = picky_splitter("SEX")) |>
  analyze("AGE", show_labels = "visible")
tbl <- build_table(lyt, d1)
tbl
```

---

data.frame_export *Generate a result data frame*

Description

Collection of utilities to extract data.frame objects from TableTree objects.

Usage

```
as_result_df(
  tt,
  spec = NULL,
  data_format = c("full_precision", "strings", "numeric"),
  make_ard = FALSE,
  expand_colnames = FALSE,
  keep_label_rows = FALSE,
  add_tbl_name_split = FALSE,
  simplify = FALSE,
  verbose = FALSE,
  round_type = obj_round_type(tt),
  ...
)

path_enriched_df(tt, path_fun = collapse_path, value_fun = collapse_values)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
spec	(function) function that generates the result data frame from a table (TableTree). It defaults to NULL, for standard processing.
data_format	(string) the format of the data in the result data frame. It can be one value between "full_precision" (default), "strings", and "numeric". The last two values show the numeric data with the visible precision.
make_ard	(flag) when TRUE, the result data frame will have only one statistic per row.
expand_colnames	(flag) when TRUE, the result data frame will have expanded column names above the usual output. This is useful when the result data frame is used for further processing.
keep_label_rows	(flag) when TRUE, the result data frame will have all labels as they appear in the final table.
add_tbl_name_split	(flag) when TRUE and when the table has more than one analyze(table_names = "<diff_names>"), the table names will be present as a group split named "<analysis_spl_tbl_name>".
simplify	(flag) when TRUE, the result data frame will have only visible labels and result columns. Consider showing also label rows with keep_label_rows = TRUE. This output can be used again to create a TableTree object with df_to_tt().

verbose	(flag) when TRUE, the function will print additional information for data_format != "full_precision".
round_type	("iec" (default), "iec_mod" or "sas") the type of rounding to perform. See formatters::format_value() for details.
...	additional arguments passed to spec-specific result data frame function (spec). When using make_ard = TRUE, it is possible to turn off the extraction of the exact string decimals printed by the table with add_tbl_str_decimals = FALSE.
path_fun	(function) function to transform paths into single-string row/column names.
value_fun	(function) function to transform cell values into cells of a data.frame. Defaults to collapse_values, which creates strings where multi-valued cells are collapsed together, separated by |.

Value

- as_result_df returns a result data.frame.
- path_enriched_df() returns a data.frame of tt's cell values (processed by value_fun, with columns named by the full column paths (processed by path_fun and an additional row_path column with the row paths (processed by path_fun).

Functions

- path_enriched_df(): Transform a TableTree object to a path-enriched data.frame.

Note

When parent_name is used when constructing a layout to directly control the name of subtables in a table, that will be reflected in the 'group' values returned in the result dataframe/ard. When automatic de-duplication of sibling names is performed by rtables, that is automatically undone during the result df creation process, so the group values will be as if the relevant siblings had identical names.

See Also

df_to_tt() when using simplify = TRUE and formatters::make_row_df() to have a comprehensive view of the hierarchical structure of the rows.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("STRATA1") |>
  analyze(c("AGE", "BMRKR2"))

tbl <- build_table(lyt, ex_adsl)
```

```
as_result_df(tbl, simplify = TRUE)

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze(c("AGE", "BMRKR2"))

tbl <- build_table(lyt, ex_adsl)
path_enriched_df(tbl)
```

`df_to_tt` *Create an* `ElementaryTable` *from a* `data.frame`

Description

Create an `ElementaryTable` from a `data.frame`

Usage

```
df_to_tt(df)
```

Arguments

`df`	(`data.frame`) a data frame.

Details

If row names are not defined in `df` (or they are simple numbers), then the row names are taken from the column `label_name`, if it exists. If `label_name` exists, then it is also removed from the original data. This behavior is compatible with `as_result_df()`, when `as_is = TRUE` and the row names are not unique.

See Also

`as_result_df()` for the inverse operation.

Examples

```
df_to_tt(mtcars)
```

do_base_split *Apply basic split (for use in custom split functions)*

Description

This function is intended for use inside custom split functions. It applies the current split *as if it had no custom splitting function* so that those default splits can be further manipulated.

Usage

```
do_base_split(spl, df, vals = NULL, labels = NULL, trim = FALSE)
```

Arguments

spl	(Split) a Split object defining a partitioning or analysis/tabulation of the data.
df	(data.frame or tibble) dataset.
vals	(ANY) already calculated/known values of the split. Generally should be left as NULL.
labels	(character) labels associated with vals. Should be NULL whenever vals is, which should almost always be the case.
trim	(flag) whether groups corresponding to empty data subsets should be removed. Defaults to FALSE.

Value

The result of the split being applied as if it had no custom split function. See custom_split_funs.

Examples

```
uneven_splfun <- function(df, spl, vals = NULL, labels = NULL, trim = FALSE) {
  ret <- do_base_split(spl, df, vals, labels, trim)
  if (NROW(df) == 0) {
    ret <- lapply(ret, function(x) x[1])
  }
  ret
}

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_multivar(c("USUBJID", "AESEQ", "BMRKR1"),
    varlabels = c("N", "E", "BMR1"),
    split_fun = uneven_splfun
  ) |>
```

```
  analyze_colvars(list(
    USUBJID = function(x, ...) length(unique(x)),
    AESEQ = max,
    BMRKR1 = mean
  ))

tbl <- build_table(lyt, subset(ex_adae, as.numeric(ARM) <= 2))
tbl
```

`drop_facet_levels` *Pre-processing function for use in* `make_split_fun`

Description

This function is intended for use as a pre-processing component in `make_split_fun`, and should not be called directly by end users.

Usage

```
drop_facet_levels(df, spl, ...)
```

Arguments

`df`	(`data.frame`) the incoming data corresponding with the parent facet.
`spl`	(`VarLevelSplit`) the split.
`...`	additional parameters passed internally.

See Also

`make_split_fun()`

Other make_custom_split: `add_combo_facet()`, `make_split_fun()`, `make_split_result()`, `restrict_facets()`, `trim_levels_in_facets()`

ElementaryTable-class TableTree *classes*

Description

TableTree classes

Table constructors and classes

Usage

```
ElementaryTable(
  kids = list(),
  name = "",
  lev = 1L,
  label = "",
 labelrow = LabelRow(lev = lev, label = label, vis = !isTRUE(iscontent) && !is.na(label)
   && nzchar(label)),
  rspans = data.frame(),
  cinfo = NULL,
  iscontent = NA,
  var = NA_character_,
  format = NULL,
  na_str = NA_character_,
  indent_mod = 0L,
  title = "",
  subtitles = character(),
  main_footer = character(),
  prov_footer = character(),
  header_section_div = NA_character_,
  hsep = default_hsep(),
  trailing_section_div = NA_character_,
  inset = 0L,
  round_type = valid_round_type
)

TableTree(
  kids = list(),
  name = if (!is.na(var)) var else "",
  cont = EmptyElTable,
  lev = 1L,
  label = name,
 labelrow = LabelRow(lev = lev, label = label, vis = nrow(cont) == 0 && !is.na(label) &&
   nzchar(label)),
  rspans = data.frame(),
  iscontent = NA,
  var = NA_character_,
```

```
  cinfo = NULL,
  format = NULL,
  na_str = NA_character_,
  indent_mod = 0L,
  title = "",
  subtitles = character(),
  main_footer = character(),
  prov_footer = character(),
  page_title = NA_character_,
  hsep = default_hsep(),
  header_section_div = NA_character_,
  trailing_section_div = NA_character_,
  inset = 0L,
  round_type = NULL
)
```

Arguments

kids	(list) list of direct children.
name	(string) name of the split/table/row being created. Defaults to the value of the corresponding label, but is not required to be.
lev	(integer(1)) nesting level (roughly, indentation level in practical terms).
label	(string) a label (not to be confused with the name) for the object/structure.
labelrow	(LabelRow) the LabelRow object to assign to the table. Constructed from label by default if not specified.
rspans	(data.frame) currently stored but otherwise ignored.
cinfo	(InstantiatedColumnInfo or NULL) column structure for the object being created.
iscontent	(flag) whether the TableTree/ElementaryTable is being constructed as the content table for another TableTree.
var	(string) variable name.
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".

`indent_mod` (`numeric`)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

`title` (`string`)
single string to use as main title (`formatters::main_title()`). Ignored for subtables.

`subtitles` (`character`)
a vector of strings to use as subtitles (`formatters::subtitles()`), where every element is printed on a separate line. Ignored for subtables.

`main_footer` (`character`)
a vector of strings to use as main global (non-referential) footer materials (`formatters::main_footer()`) where every element is printed on a separate line.

`prov_footer` (`character`)
a vector of strings to use as provenance-related global footer materials (`formatters::prov_footer()`), where every element is printed on a separate line.

`header_section_div` (`string`)
string which will be used to divide the header from the table. See `header_section_div()` for the associated getter and setter. Please consider changing last element of `section_div()` when concatenating tables that require a divider between them.

`hsep` (`string`)
set of characters to be repeated as the separator between the header and body of the table when rendered as text. Defaults to a connected horizontal line (unicode 2014) in locals that use a UTF charset, and to `-` elsewhere (with a once per session warning). See `formatters::set_default_hsep()` for further information.

`trailing_section_div` (`string`)
string which will be used as a section divider after the printing of the last row contained in this (sub)table, unless that row is also the last table row to be printed overall, or `NA_character_` for none (the default). When generated via laytouting, this would correspond to the `section_div` of the split under which this table represents a single facet.

`inset` (`numeric(1)`)
number of spaces to inset the table header, table body, referential footnotes, and main_footer, as compared to alignment of title, subtitle, and provenance footer. Defaults to 0 (no inset).

`round_type` (`"iec"` (default), `"iec_mod"` or `"sas"`)
the type of rounding to perform. See `formatters::format_value()` for details.

`cont` (`ElementaryTable`)
content table.

`page_title` (`character`)
page-specific title(s).

Value

A formal object representing a populated table.

Author(s)

Gabriel Becker

`EmptyColInfo` *Empty table, column, split objects*

Description

Empty objects of various types to compare against efficiently.

`export_as_tsv` *Create enriched flat value table with paths*

Description

This function creates a flat tabular file of cell values and corresponding paths via `path_enriched_df()`. It then writes that data frame out as a `tsv` file.

Usage

```
export_as_tsv(
  tt,
  file = NULL,
  path_fun = collapse_path,
  value_fun = collapse_values,
  sep = "\t",
  ...
)

import_from_tsv(file)
```

Arguments

`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`file`	(`string`) the path of the file to written to or read from.
`path_fun`	(`function`) function to transform paths into single-string row/column names.

value_fun (function)
function to transform cell values into cells of a data.frame. Defaults to collapse_values, which creates strings where multi-valued cells are collapsed together, separated by |.

sep (string)
defaults to \t. See utils::write.table() for more details.

... (any)
additional arguments to be passed to utils::write.table().

Details

By default (i.e. when value_func is not specified, list columns where at least one value has length > 1 are collapsed to character vectors by collapsing the list element with "|".

Value

- export_as_tsv returns NULL silently.
- import_from_tsv returns a data.frame with re-constituted list values.

Note

There is currently no round-trip capability for this type of export. You can read values exported this way back in via import_from_tsv but you will receive only the data.frame version back, NOT a TableTree.

See Also

path_enriched_df() for the underlying function that does the work.

---

facet_colcount *Get or set column count for a facet in column space*

Description

Get or set column count for a facet in column space

Usage

```
facet_colcount(obj, path)

## S4 method for signature 'LayoutColTree'
facet_colcount(obj, path = NULL)

## S4 method for signature 'LayoutColLeaf'
facet_colcount(obj, path = NULL)

## S4 method for signature 'VTableTree'
```

```
facet_colcount(obj, path)

## S4 method for signature 'InstantiatedColumnInfo'
facet_colcount(obj, path)

facet_colcount(obj, path) <- value

## S4 replacement method for signature 'LayoutColTree'
facet_colcount(obj, path) <- value

## S4 replacement method for signature 'LayoutColLeaf'
facet_colcount(obj, path) <- value

## S4 replacement method for signature 'VTableTree'
facet_colcount(obj, path) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
facet_colcount(obj, path) <- value
```

Arguments

`obj`	(ANY) the object for the accessor to access or modify.
`path`	character. This path must end on a split value, e.g., the level of a categorical variable that was split on in column space, but it need not be the path to an individual column.
`value`	(ANY) the new value.

Value

for `facet_colcount` the current count associated with that facet in column space, for `facet_colcount<-`, `obj` modified with the new column count for the specified facet.

Note

Updating a lower-level (more specific) column count manually **will not** update the counts for its parent facets. This cannot be made automatic because the rtables framework does not require sibling facets to be mutually exclusive (e.g., total "arm", faceting into cumulative quantiles, etc) and thus the count of a parent facet will not always be simply the sum of the counts for all of its children.

See Also

`col_counts()`

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM", show_colcounts = TRUE) |>
```

```
  split_cols_by("SEX",
    split_fun = keep_split_levels(c("F", "M")),
    show_colcounts = TRUE
  ) |>
  split_cols_by("STRATA1", show_colcounts = TRUE) |>
  analyze("AGE")

tbl <- build_table(lyt, ex_adsl)

facet_colcount(tbl, c("ARM", "A: Drug X"))
facet_colcount(tbl, c("ARM", "A: Drug X", "SEX", "F"))
facet_colcount(tbl, c("ARM", "A: Drug X", "SEX", "F", "STRATA1", "A"))

## modify specific count after table creation
facet_colcount(tbl, c("ARM", "A: Drug X", "SEX", "F", "STRATA1", "A")) <- 25

## show black space for certain counts by assign NA

facet_colcount(tbl, c("ARM", "A: Drug X", "SEX", "F", "STRATA1", "C")) <- NA
```

`facet_colcounts_visible<-` *Set visibility of column counts for a group of sibling facets*

Description

Set visibility of column counts for a group of sibling facets

Usage

```
facet_colcounts_visible(obj, path) <- value
```

Arguments

`obj`	(ANY) the object for the accessor to access or modify.
`path`	(`character`) the path *to the parent of the desired siblings*. The last element in the path should be a split name.
`value`	(ANY) the new value.

Value

obj, modified with the desired column count. display behavior

See Also

`colcount_visible()`

find_degen_struct *Find degenerate (sub)structures within a table*

Description

[Experimental]

This function returns a list with the row-paths to all structural subtables which contain no data rows (even if they have associated content rows).

Usage

```
find_degen_struct(tt)
```

Arguments

tt	(TableTree) a TableTree object.

Value

A list of character vectors representing the row paths, if any, to degenerate substructures within the table.

See Also

Other table structure validation functions: sanitize_table_struct(), validate_table_struct()

Examples

```
find_degen_struct(rtable("hi"))
```

format_rcell *Format* rcell *objects*

Description

This is a wrapper for formatters::format_value() for use with CellValue objects

Usage

```
format_rcell(
  x,
  format,
  output = c("ascii", "html"),
  na_str = obj_na_str(x) %||% "NA",
  pr_row_format = NULL,
  pr_row_na_str = NULL,
  round_type,
  shell = FALSE
)
```

Arguments

x	(CellValue or ANY) an object of class CellValue, or a raw value.
format	(string or function) the format label or formatter function to apply to x.
output	(string) output type.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".
pr_row_format	(list) list of default formats coming from the general row.
pr_row_na_str	(list) list of default "NA" strings coming from the general row.
round_type	("iec" (default), "iec_mod" or "sas") the type of rounding to perform. See formatters::format_value() for details.
shell	(flag) whether the formats themselves should be returned instead of the values with formats applied. Defaults to FALSE.

Value

Formatted text.

Examples

```
cll <- CellValue(pi, format = "xx.xxx")
format_rcell(cll)

# Cell values precedes the row values
cll <- CellValue(pi, format = "xx.xxx")
format_rcell(cll, pr_row_format = "xx.x")

# Similarly for NA values
```

```
cll <- CellValue(NA, format = "xx.xxx", format_na_str = "This is THE NA")
format_rcell(cll, pr_row_na_str = "This is NA")
```

`get_formatted_cells` *Get formatted cells*

Description

Get formatted cells

Usage

```
get_formatted_cells(obj, shell = FALSE, round_type = obj_round_type(obj))

## S4 method for signature 'TableTree'
get_formatted_cells(obj, shell = FALSE, round_type = obj_round_type(obj))

## S4 method for signature 'ElementaryTable'
get_formatted_cells(obj, shell = FALSE, round_type = obj_round_type(obj))

## S4 method for signature 'TableRow'
get_formatted_cells(obj, shell = FALSE, round_type = obj_round_type(obj))

## S4 method for signature 'LabelRow'
get_formatted_cells(obj, shell = FALSE, round_type = obj_round_type(obj))

get_cell_aligns(obj)

## S4 method for signature 'TableTree'
get_cell_aligns(obj)

## S4 method for signature 'ElementaryTable'
get_cell_aligns(obj)

## S4 method for signature 'TableRow'
get_cell_aligns(obj)

## S4 method for signature 'LabelRow'
get_cell_aligns(obj)
```

Arguments

`obj`	(ANY) the object for the accessor to access or modify.
`shell`	(flag) whether the formats themselves should be returned instead of the values with formats applied. Defaults to FALSE.

round_type ("iec" (default), "iec_mod" or "sas")
the type of rounding to perform. See formatters::format_value() for details.

Value

The formatted print-strings for all (body) cells in obj.

Examples

```
library(dplyr)

iris2 <- iris |>
  group_by(Species) |>
  mutate(group = as.factor(rep_len(c("a", "b"), length.out = n()))) |>
  ungroup()

tbl <- basic_table() |>
  split_cols_by("Species") |>
  split_cols_by("group") |>
 analyze(c("Sepal.Length", "Petal.Width"), afun = list_wrap_x(summary), format = "xx.xx") |>
  build_table(iris2)

get_formatted_cells(tbl)
```

---

get_full_lyt_df *Retrieve Info About Possible Nesting Anchors*

Description

This function scans an existing layout's row structure and lists valid at_sibling anchors for intermediate nesting.

Usage

```
get_full_lyt_df(
  splvec,
  next_node = 1L,
  next_anchor_step = 1L,
  parent,
  depth,
  node_type
)

## S4 method for signature 'PreDataTableLayouts'
get_full_lyt_df(
  splvec,
  next_node = 1L,
```

```
  next_anchor_step = 1,
  parent,
  depth,
  node_type
)

get_layout_dfs(lyt)

## S4 method for signature 'PreDataRowLayout'
get_full_lyt_df(
  splvec,
  next_node = 1,
  next_anchor_step = 1L,
  parent = 0L,
  depth = 1L,
  node_type = "active"
)

## S4 method for signature 'PreDataColLayout'
get_full_lyt_df(
  splvec,
  next_node = 1,
  next_anchor_step = 1L,
  parent = 0L,
  depth = 1L,
  node_type = "active"
)

## S4 method for signature 'SplitVector'
get_full_lyt_df(
  splvec,
  next_node = 1L,
  next_anchor_step = 1L,
  parent,
  depth,
  node_type
)

## S4 method for signature 'SplitVectorTree'
get_full_lyt_df(
  splvec,
  next_node = 1L,
  next_anchor_step = 1L,
  parent,
  depth,
  node_type
)
```

```
## S4 method for signature 'Split'
get_full_lyt_df(
  splvec,
  next_node = 1L,
  next_anchor_step = 1L,
  parent,
  depth,
  node_type
)

## S4 method for signature 'VTableNodeInfo'
get_full_lyt_df(
  splvec,
  next_node = 1L,
  next_anchor_step = 1L,
  parent,
  depth,
  node_type
)

get_anchor_dfs(lyt)

get_row_anchor_df(lyt)

get_row_anchor_list(lyt)
```

Arguments

splvec	(PreDataTableLayouts or internal classes) The layout or partial layout to list anchors for.
next_node	(integer(1)) For internal use
next_anchor_step	(integer(1)) For internal use.
parent	(integer(1)) For internal use.
depth	(integer(1)) For internal use.
node_type	(character(1)) For internal use.
lyt	(PreDataTableLayouts or PreDataRowLayout) A layout or row to identify anchors for.

Details

A layout data.frame is a data.frame describing a single dimension of pre-data layout structure, containing the following columns (most of which are used for internal implementations and will

not be useful to the end-user):

- `name`: name of the element
- `nodeid`: sequential numeric id of the node, for use in constructing graphs (0 is the root node)
- `parentid`: node id of the layout instructions direct parent
- `depth`: length of path from root to the current node through the implicit graph defined by the (`nodeid`, `parentid`) pairings
- `type`: a description of the 'type' of the node, used internally
- `is_toplevel`: whether the node represents a top-level split/analysis.
- `anchor_step`: position *along the path of eligible anchor points*, (`NA` for nodes not along that path).

The core difference between a layout data.frame and an anchor data.frame is that the anchor df has been subset to remove rows for nodes not currently eligible to be anchor points (ie allowed targets for a subsequent instruction's `at_sibling` argument).

Value

for `get_layout_dfs` a list with `rows` and `cols` elements containing layout data.frames (see Details) for each structural dimension; `get_anchor_dfs` returns the same, but with anchor data.frames rather than full layout ones. `get_anchor_row_df` is a convenience function that returns only the `rows` anchor data.frame. `get_row_anchor_list` returns a list, each element of which is a set of the names of one or more layout instructions that will be placed as direct siblings to each-other; i.e., anchored to the first element of the vector when the length of the element is greater than one.

Note

Instructions which are anchored in such a way that they ultimately become top-level instructions in the layout (i.e., by being anchored as a sibling to a top-level instruction) are handled somewhat differently for implementation reasons and may present differently to those anchored to non-top-level instructions.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("STRATA1") |>
  split_rows_by("RACE") |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR1", at_sibling = "RACE") |>
  analyze("AGE")

get_layout_dfs(lyt)
get_anchor_dfs(lyt)
get_row_anchor_df(lyt)
```

head *Head and tail methods*

Description

Head and tail methods

Usage

```
head(x, ...)

## S4 method for signature 'VTableTree'
head(
  x,
  n = 6,
  ...,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  reindex_refs = FALSE
)

tail(x, ...)

## S4 method for signature 'VTableTree'
tail(
  x,
  n = 6,
  ...,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  reindex_refs = FALSE
)
```

Arguments

x	an object
...	arguments to be passed to or from other methods.
n	an integer vector of length up to dim(x) (or 1, for non-dimensioned objects). A logical is silently coerced to integer. Values specify the indices to be selected in the corresponding dimension (or along the length) of the object. A positive value of n[i] includes the first/last n[i] indices in that dimension, while a negative value excludes the last/first abs(n[i]), including all remaining indices. NA or non-specified values (when length(n) < length(dim(x))) select all indices in that dimension. Must contain at least one non-missing value.

keep_topleft	(flag) if TRUE (the default), top_left material for the table will be carried over to the subset.
keep_titles	(flag) if TRUE (the default), all title material for the table will be carried over to the subset.
keep_footers	(flag) if TRUE, all footer material for the table will be carried over to the subset. It defaults to keep_titles.
reindex_refs	(flag) defaults to FALSE. If TRUE, referential footnotes will be reindexed for the subset.

`horizontal_sep` *Access or recursively set header-body separator for tables*

Description

Access or recursively set header-body separator for tables

Usage

```
horizontal_sep(obj)

## S4 method for signature 'VTableTree'
horizontal_sep(obj)

horizontal_sep(obj) <- value

## S4 replacement method for signature 'VTableTree'
horizontal_sep(obj) <- value

## S4 replacement method for signature 'TableRow'
horizontal_sep(obj) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
value	(string) string to use as new header/body separator.

Value

- horizontal_sep returns the string acting as the header separator.
- horizontal_sep<- returns obj, with the new header separator applied recursively to it and all its subtables.

in_rows *Create multiple rows in analysis or summary functions*

Description

Define the cells that get placed into multiple rows in `afun`.

Usage

```
in_rows(
  ...,
  .list = NULL,
  .names = NULL,
  .labels = NULL,
  .formats = NULL,
  .indent_mods = NULL,
  .cell_footnotes = list(NULL),
  .row_footnotes = list(NULL),
  .aligns = NULL,
  .format_na_strs = NULL,
  .stat_names = list(NULL)
)
```

Arguments

`...`	single row defining expressions.
`.list`	(`list`) list cell content (usually `rcells`). The `.list` is concatenated to `....`
`.names`	(`character` or `NULL`) names of the returned list/structure.
`.labels`	(`character` or `NULL`) labels for the defined rows.
`.formats`	(`character` or `NULL`) formats for the values.
`.indent_mods`	(`integer` or `NULL`) indent modifications for the defined rows.
`.cell_footnotes`	(`list`) referential footnote messages to be associated by name with *cells*.
`.row_footnotes`	(`list`) referential footnotes messages to be associated by name with *rows*.
`.aligns`	(`character` or `NULL`) alignments for the cells. Standard for `NULL` is `"center"`. See `formatters::list_valid_aligns()` for currently supported alignments.

`.format_na_strs`
: (`character` or `NULL`)
NA strings for the cells.

`.stat_names`
: (`list`)
names for the statistics in the cells. It can be a vector of values. If `list(NULL)`, statistic names are not specified and will appear as `NA`.

Value

A `RowsVerticalSection` object (or `NULL`). The details of this object should be considered an internal implementation detail.

Note

In post-processing, referential footnotes can also be added using row and column paths with `fnotes_at_path<-`.

See Also

`analyze()`

Examples

```
in_rows(1, 2, 3, .names = c("a", "b", "c"))
in_rows(1, 2, 3, .labels = c("a", "b", "c"))
in_rows(1, 2, 3, .names = c("a", "b", "c"), .labels = c("AAA", "BBB", "CCC"))
in_rows(
  .list = list(a = c(NA, NA)),
  .formats = "xx - xx",
  .format_na_strs = list(c("asda", "lkjklj"))
)
in_rows(.list = list(a = c(NA, NA)), .format_na_strs = c("asda", "lkjklj"))

in_rows(.list = list(a = 1, b = 2, c = 3))
in_rows(1, 2, .list = list(3), .names = c("a", "b", "c"))

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = function(x) {
    in_rows(
      "Mean (sd)" = rcell(c(mean(x), sd(x)), format = "xx.xx (xx.xx)"),
      "Range" = rcell(range(x), format = "xx.xx - xx.xx")
    )
  })

tbl <- build_table(lyt, ex_adsl)
tbl
```

indent *Change indentation of all* rrows *in an* rtable

Description

Change indentation of all rrows in an rtable

Usage

```
indent(x, by = 1)
```

Arguments

x	(VTableTree) an rtable object.
by	(integer) number to increase indentation of rows by. Can be negative. If final indentation is less than 0, the indentation is set to 0.

Value

x with its indent modifier incremented by by.

Examples

```
is_setosa <- iris$Species == "setosa"
m_tbl <- rtable(
  header = rheader(
   rrow(row.name = NULL, rcell("Sepal.Length", colspan = 2), rcell("Petal.Length", colspan = 2)),
    rrow(NULL, "mean", "median", "mean", "median")
  ),
  rrow(
    row.name = "All Species",
    mean(iris$Sepal.Length), median(iris$Sepal.Length),
    mean(iris$Petal.Length), median(iris$Petal.Length),
    format = "xx.xx"
  ),
  rrow(
    row.name = "Setosa",
    mean(iris$Sepal.Length[is_setosa]), median(iris$Sepal.Length[is_setosa]),
    mean(iris$Petal.Length[is_setosa]), median(iris$Petal.Length[is_setosa]),
    format = "xx.xx"
  )
)
indent(m_tbl)
indent(m_tbl, 2)
```

indent_string *Indent strings*

Description

Used in rtables to indent row names for the ASCII output.

Usage

```
indent_string(x, indent = 0, incr = 2, including_newline = TRUE)
```

Arguments

x	(character) a character vector.
indent	(numeric) a vector of non-negative integers of length length(x).
incr	(integer(1)) a non-negative number of spaces per indent level.
including_newline	(flag) whether newlines should also be indented.

Value

x, indented with left-padding with indent * incr white-spaces.

Examples

```
indent_string("a", 0)
indent_string("a", 1)
indent_string(letters[1:3], 0:2)
indent_string(paste0(letters[1:3], "\n", LETTERS[1:3]), 0:2)
```

insert_row_at_path *Insert row at path*

Description

Insert a row into an existing table directly before or directly after an existing data (i.e., non-content and non-label) row, specified by its path.

Usage

```
insert_row_at_path(tt, path, value, after = FALSE)

## S4 method for signature 'VTableTree,DataRow'
insert_row_at_path(tt, path, value, after = FALSE)

## S4 method for signature 'VTableTree,ANY'
insert_row_at_path(tt, path, value)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
value	(ANY) the new value.
after	(flag) whether value should be added as a row directly before (FALSE, the default) or after (TRUE) the row specified by path.

See Also

DataRow(), rrow()

Examples

```
lyt <- basic_table() |>
  split_rows_by("COUNTRY", split_fun = keep_split_levels(c("CHN", "USA"))) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)

tbl2 <- insert_row_at_path(
  tbl, c("COUNTRY", "CHN", "AGE", "Mean"),
  rrow("new row", 555)
)
tbl2

tbl3 <- insert_row_at_path(tbl2, c("COUNTRY", "CHN", "AGE", "Mean"),
  rrow("new row redux", 888),
  after = TRUE
)
tbl3
```

insert_rrow *Insert* rrow*s at (before) a specific location*

Description

[Deprecated]

Usage

```
insert_rrow(tbl, rrow, at = 1, ascontent = FALSE)
```

Arguments

tbl	(VTableTree) a rtable object.
rrow	(TableRow) an rrow to append to tbl.
at	(integer(1)) position into which to put the rrow, defaults to beginning (i.e. row 1).
ascontent	(flag) currently ignored.

Details

This function is deprecated and will be removed in a future release of rtables. Please use insert_row_at_path() or label_at_path() instead.

Value

A TableTree of the same specific class as tbl.

Note

Label rows (i.e. a row with no data values, only a row.name) can only be inserted at positions which do not already contain a label row when there is a non-trivial nested row structure in tbl.

Examples

```
o <- options(warn = 0)
lyt <- basic_table() |>
  split_cols_by("Species") |>
  analyze("Sepal.Length")

tbl <- build_table(lyt, iris)

insert_rrow(tbl, rrow("Hello World"))
insert_rrow(tbl, rrow("Hello World"), at = 2)
```

```
lyt2 <- basic_table() |>
  split_cols_by("Species") |>
  split_rows_by("Species") |>
  analyze("Sepal.Length")

tbl2 <- build_table(lyt2, iris)

insert_rrow(tbl2, rrow("Hello World"))
insert_rrow(tbl2, rrow("Hello World"), at = 2)
insert_rrow(tbl2, rrow("Hello World"), at = 4)

insert_rrow(tbl2, rrow("new row", 5, 6, 7))

insert_rrow(tbl2, rrow("new row", 5, 6, 7), at = 3)

options(o)
```

`InstantiatedColumnInfo-class` *Instantiated column info*

Description

Instantiated column info

Usage

```
InstantiatedColumnInfo(
  treelyt = LayoutColTree(colcount = total_cnt),
  csubs = list(expression(TRUE)),
  extras = list(list()),
  cnts = NA_integer_,
  total_cnt = NA_integer_,
  dispcounts = FALSE,
  countformat = "(N=xx)",
  count_na_str = "",
  topleft = character()
)
```

Arguments

`treelyt`	(`LayoutColTree`) a `LayoutColTree` object.
`csubs`	(`list`) a list of subsetting expressions.
`extras`	(`list`) extra arguments associated with the columns.

cnts	(integer) counts.
total_cnt	(integer(1)) total observations represented across all columns.
dispcounts	(flag) whether the counts should be displayed as header info when the associated table is printed.
countformat	(string) format for the counts if they are displayed.
count_na_str	(character) string to use in place of missing values when formatting counts. Defaults to "".
topleft	(character) override values for the "top left" material to be displayed during printing.

Value

An InstantiateadColumnInfo object.

---

is_rtable *Check if an object is a valid* rtable

Description

Check if an object is a valid rtable

Usage

```
is_rtable(x)
```

Arguments

x	(ANY) an object.

Value

TRUE if x is a formal TableTree object, FALSE otherwise.

Examples

```
is_rtable(build_table(basic_table(), iris))
```

label_at_path *Label at path*

Description

Accesses or sets the label at a path.

Usage

```
label_at_path(tt, path)

label_at_path(tt, path) <- value
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
value	(ANY) the new value.

Details

If path resolves to a single row, the label for that row is retrieved or set. If, instead, path resolves to a subtable, the text for the row-label associated with that path is retrieved or set. In the subtable case, if the label text is set to a non-NA value, the labelrow will be set to visible, even if it was not before. Similarly, if the label row text for a subtable is set to NA, the label row will bet set to non-visible, so the row will not appear at all when the table is printed.

Note

When changing the row labels for content rows, it is important to path all the way to the *row*. Paths ending in "@content" will not exhibit the behavior you want, and are thus an error. See row_paths() for help determining the full paths to content rows.

Examples

```
lyt <- basic_table() |>
  split_rows_by("COUNTRY", split_fun = keep_split_levels(c("CHN", "USA"))) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)

label_at_path(tbl, c("COUNTRY", "CHN"))

label_at_path(tbl, c("COUNTRY", "USA")) <- "United States"
```

```
tbl
```

LabelRow *Row classes and constructors*

Description

Row classes and constructors

Row constructors and classes

Usage

```
LabelRow(
  lev = 1L,
  label = "",
  name = label,
  vis = !is.na(label) && nzchar(label),
  cinfo = EmptyColInfo,
  indent_mod = 0L,
  table_inset = 0L,
  trailing_section_div = NA_character_,
  round_type = valid_round_type
)

.tablerow(
  vals = list(),
  name = "",
  lev = 1L,
  label = name,
  cspan = rep(1L, length(vals)),
  cinfo = EmptyColInfo,
  var = NA_character_,
  format = NULL,
  na_str = NA_character_,
  klass,
  indent_mod = 0L,
  footnotes = list(),
  table_inset = 0L,
  trailing_section_div = NA_character_,
  round_type = valid_round_type
)

DataRow(...)

ContentRow(...)
```

Arguments

lev	(integer(1)) nesting level (roughly, indentation level in practical terms).
label	(string) a label (not to be confused with the name) for the object/structure.
name	(string) name of the split/table/row being created. Defaults to the value of the corresponding label, but is not required to be.
vis	(flag) whether the row should be visible (LabelRow only).
cinfo	(InstantiatedColumnInfo or NULL) column structure for the object being created.
indent_mod	(numeric) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.
table_inset	(numeric(1)) number of spaces to inset the table header, table body, referential footnotes, and main footer, as compared to alignment of title, subtitles, and provenance footer. Defaults to 0 (no inset).
trailing_section_div	(string) string which will be used as a section divider after the printing of the last row contained in this (sub)table, unless that row is also the last table row to be printed overall, or NA_character_ for none (the default). When generated via layouting, this would correspond to the section_div of the split under which this table represents a single facet.
round_type	("iec", "iec_mod" or "sas") the type of rounding to perform. See round_fmt() for details.
vals	(list) cell values for the row.
cspan	(integer) column span. 1 indicates no spanning.
var	(string) variable name.
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".
klass	(character) internal detail.

footnotes	(list or NULL) referential footnotes to be applied at current level. In post-processing, this can be achieved with fnotes_at_path<-.
...	additional parameters passed to shared constructor (.tablerow).

Value

A formal object representing a table row of the constructed type.

Author(s)

Gabriel Becker

---

length,CellValue-method

Length of a Cell value

Description

Length of a Cell value

Usage

```
## S4 method for signature 'CellValue'
length(x)
```

Arguments

x	(CellValue) a CellValue object.

Value

Always returns 1L.

`list_wrap_x` *Returns a function that coerces the return values of a function to a list*

Description

Returns a function that coerces the return values of a function to a list

Usage

```
list_wrap_x(f)

list_wrap_df(f)
```

Arguments

`f`	(`function`) the function to wrap.

Details

`list_wrap_x` generates a wrapper which takes `x` as its first argument, while `list_wrap_df` generates an otherwise identical wrapper function whose first argument is named `df`.

We provide both because when using the functions as tabulation in `analyze()`, functions which take `df` as their first argument are passed the full subset data frame, while those which accept anything else notably including `x` are passed only the relevant subset of the variable being analyzed.

Value

A function that returns a list of `CellValue` objects.

Author(s)

Gabriel Becker

Examples

```
summary(iris$Sepal.Length)

f <- list_wrap_x(summary)
f(x = iris$Sepal.Length)

f2 <- list_wrap_df(summary)
f2(df = iris$Sepal.Length)
```

make_afun *Create a custom analysis function wrapping an existing function*

Description

Create a custom analysis function wrapping an existing function

Usage

```
make_afun(
  fun,
  .stats = NULL,
  .formats = NULL,
  .labels = NULL,
  .indent_mods = NULL,
  .ungroup_stats = NULL,
  .format_na_strs = NULL,
  ...,
  .null_ref_cells = ".in_ref_col" %in% names(formals(fun))
)
```

Arguments

fun	(function) the function to be wrapped in a new customized analysis function. fun should return a named list.
.stats	(character) names of elements to keep from fun's full output.
.formats	(ANY) vector or list of formats to override any defaults applied by fun.
.labels	(character) vector of labels to override defaults returned by fun.
.indent_mods	(integer) named vector of indent modifiers for the generated rows.
.ungroup_stats	(character) vector of names, which must match elements of .stats.
.format_na_strs	(ANY) vector/list of NA strings to override any defaults applied by fun.
...	additional arguments to fun which effectively become new defaults. These can still be overridden by extra_args within a split.
.null_ref_cells	(flag) whether cells for the reference column should be NULL-ed by the returned analysis function. Defaults to TRUE if fun accepts .in_ref_col as a formal argument.

Note this argument occurs after ... so it must be *fully* specified by name when set.

Value

A function suitable for use in `analyze()` with element selection, reformatting, and relabeling performed automatically.

Note

Setting `.ungroup_stats` to non-`NULL` changes the *structure* of the value(s) returned by `fun`, rather than just labeling (`.labels`), formatting (`.formats`), and selecting amongst (`.stats`) them. This means that subsequent `make_afun` calls to customize the output further both can and must operate on the new structure, *not* the original structure returned by `fun`. See the final pair of examples below.

See Also

`analyze()`

Examples

```
s_summary <- function(x) {
  stopifnot(is.numeric(x))

  list(
    n = sum(!is.na(x)),
    mean_sd = c(mean = mean(x), sd = sd(x)),
    min_max = range(x)
  )
}

s_summary(iris$Sepal.Length)

a_summary <- make_afun(
  fun = s_summary,
  .formats = c(n = "xx", mean_sd = "xx.xx (xx.xx)", min_max = "xx.xx - xx.xx"),
  .labels = c(n = "n", mean_sd = "Mean (sd)", min_max = "min - max")
)

a_summary(x = iris$Sepal.Length)

a_summary2 <- make_afun(a_summary, .stats = c("n", "mean_sd"))

a_summary2(x = iris$Sepal.Length)

a_summary3 <- make_afun(a_summary, .formats = c(mean_sd = "(xx.xxx, xx.xxx)"))

s_foo <- function(df, .N_col, a = 1, b = 2) {
  list(
    nrow_df = nrow(df),
    .N_col = .N_col,
```

```
    a = a,
    b = b
  )
}

s_foo(iris, 40)

a_foo <- make_afun(s_foo,
  b = 4,
  .formats = c(nrow_df = "xx.xx", ".N_col" = "xx.", a = "xx", b = "xx.x"),
  .labels = c(
    nrow_df = "Nrow df",
    ".N_col" = "n in cols", a = "a value", b = "b value"
  ),
  .indent_mods = c(nrow_df = 2L, a = 1L)
)

a_foo(iris, .N_col = 40)
a_foo2 <- make_afun(a_foo, .labels = c(nrow_df = "Number of Rows"))
a_foo2(iris, .N_col = 40)

# grouping and further customization
s_grp <- function(df, .N_col, a = 1, b = 2) {
  list(
    nrow_df = nrow(df),
    .N_col = .N_col,
    letters = list(
      a = a,
      b = b
    )
  )
}
a_grp <- make_afun(s_grp,
  b = 3,
  .labels = c(
    nrow_df = "row count",
    .N_col = "count in column"
  ),
  .formats = c(nrow_df = "xx.", .N_col = "xx."),
  .indent_mods = c(letters = 1L),
  .ungroup_stats = "letters"
)
a_grp(iris, 40)
a_aftergrp <- make_afun(a_grp,
  .stats = c("nrow_df", "b"),
  .formats = c(b = "xx.")
)
a_aftergrp(iris, 40)

s_ref <- function(x, .in_ref_col, .ref_group) {
  list(
    mean_diff = mean(x) - mean(.ref_group)
  )
```

```
}

a_ref <- make_afun(s_ref,
  .labels = c(mean_diff = "Mean Difference from Ref")
)
a_ref(iris$Sepal.Length, .in_ref_col = TRUE, 1:10)
a_ref(iris$Sepal.Length, .in_ref_col = FALSE, 1:10)
```

`make_col_df` *Column layout summary*

Description

Used for pagination. Generate a structural summary of the columns of an `rtables` table and return it as a `data.frame`.

Usage

```
make_col_df(
  tt,
  colwidths = NULL,
  visible_only = TRUE,
  na_str = "",
  ccount_format = colcount_format(tt) %||% "(N=xx)"
)
```

Arguments

`tt`	(`ANY`) object representing the table-like object to be summarized.
`colwidths`	(`numeric`) internal detail, do not set manually.
`visible_only`	(`flag`) should only visible aspects of the table structure be reflected in this summary. Defaults to `TRUE`. May not be supported by all methods.
`na_str`	(`character(1)`) The string to display when a column count is NA. Users should not need to set this.
`ccount_format`	(`FormatSpec`) The format to be used by default for column counts if one is not specified for an individual column count.

make_split_fun *Create a custom splitting function*

Description

Create a custom splitting function

Usage

```
make_split_fun(pre = list(), core_split = NULL, post = list())
```

Arguments

pre	(list) zero or more functions which operate on the incoming data and return a new data frame that should split via core_split. They will be called on the data in the order they appear in the list.
core_split	(function or NULL) if non-NULL, a function which accepts the same arguments that do_base_split does, and returns the same type of named list. Custom functions which override this behavior cannot be used in column splits.
post	(list) zero or more functions which should be called on the list output by splitting.

Details

Custom split functions can be thought of as (up to) 3 different types of manipulations of the splitting process:

1. Pre-processing of the incoming data to be split.
2. (Row-splitting only) Customization of the core mapping of incoming data to facets.
3. Post-processing operations on the set of facets (groups) generated by the split.

This function provides an interface to create custom split functions by implementing and specifying sets of operations in each of those classes of customization independently.

Pre-processing functions (1), must accept: df, spl, vals, and labels, and can optionally accept .spl_context. They then manipulate df (the incoming data for the split) and return a modified data frame. This modified data frame *must* contain all columns present in the incoming data frame, but can add columns if necessary (though we note that these new columns cannot be used in the layout as split or analysis variables, because they will not be present when validity checking is done).

The preprocessing component is useful for things such as manipulating factor levels, e.g., to trim unobserved ones or to reorder levels based on observed counts, etc.

Core splitting functions override the fundamental splitting procedure, and are only necessary in rare cases. These must accept spl, df, vals, labels, and can optionally accept .spl_context. They should return a split result object constructed via make_split_result().

In particular, if the custom split function will be used in column space, subsetting expressions (e.g., as returned by `quote()` or `bquote` must be provided, while they are optional (and largely ignored, currently) in row space.

Post-processing functions (3) must accept the result of the core split as their first argument (which can be anything), in addition to `spl`, and `fulldf`, and can optionally accept `.spl_context`. They must each return a modified version of the same structure specified above for core splitting.

In both the pre- and post-processing cases, multiple functions can be specified. When this happens, they are applied sequentially, in the order they appear in the list passed to the relevant argument (`pre` and `post`, respectively).

Value

A custom function that can be used as a split function.

See Also

custom_split_funs for a more detailed discussion on what custom split functions do.

Other make_custom_split: `add_combo_facet()`, `drop_facet_levels()`, `make_split_result()`, `restrict_facets()`, `trim_levels_in_facets()`

Examples

```
mysplitfun <- make_split_fun(
  pre = list(drop_facet_levels),
  post = list(add_overall_facet("ALL", "All Arms"))
)

basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM", split_fun = mysplitfun) |>
  analyze("AGE") |>
  build_table(subset(DM, ARM %in% c("B: Placebo", "C: Combination")))

## post (and pre) arguments can take multiple functions, here
## we add an overall facet and the reorder the facets
reorder_facets <- function(splret, spl, fulldf, ...) {
  ord <- order(names(splret$values))
  make_split_result(
    splret$values[ord],
    splret$datasplit[ord],
    splret$labels[ord]
  )
}

mysplitfun2 <- make_split_fun(
  pre = list(drop_facet_levels),
  post = list(
    add_overall_facet("ALL", "All Arms"),
    reorder_facets
  )
)
basic_table(show_colcounts = TRUE) |>
```

```
  split_cols_by("ARM", split_fun = mysplitfun2) |>
  analyze("AGE") |>
  build_table(subset(DM, ARM %in% c("B: Placebo", "C: Combination")))

very_stupid_core <- function(spl, df, vals, labels, .spl_context) {
  make_split_result(c("stupid", "silly"),
    datasplit = list(df[1:10, ], df[11:30, ]),
    labels = c("first 10", "second 20")
  )
}

dumb_30_facet <- add_combo_facet("dumb",
  label = "thirty patients",
  levels = c("stupid", "silly")
)
nonsense_splfun <- make_split_fun(
  core_split = very_stupid_core,
  post = list(dumb_30_facet)
)

## recall core split overriding is not supported in column space
## currently, but we can see it in action in row space

lyt_silly <- basic_table() |>
  split_rows_by("ARM", split_fun = nonsense_splfun) |>
  summarize_row_groups() |>
  analyze("AGE")
silly_table <- build_table(lyt_silly, DM)
silly_table
```

`make_split_result` *Construct split result object*

Description

These functions can be used to create or add to a split result in functions which implement core splitting or post-processing within a custom split function.

Usage

```
make_split_result(
  values,
  datasplit,
  labels,
  extras = NULL,
  subset_exprs = vector("list", length(values))
)
```

```
add_to_split_result(
  splres,
  values,
  datasplit,
  labels,
  extras = NULL,
  subset_exprs = NULL
)
```

Arguments

values	(character or list(SplitValue)) the values associated with each facet.
datasplit	(list(data.frame)) the facet data for each facet generated in the split.
labels	(character) the labels associated with each facet.
extras	(list or NULL) extra values associated with each of the facets which will be passed to analysis functions applied within the facet.
subset_exprs	(list) A list of subsetting expressions (e.g., created with quote()) to be used during column subsetting.
splres	(list) a list representing the result of splitting.

Details

These functions performs various housekeeping tasks to ensure that the split result list is as the rtables internals expect it, most of which are not relevant to end users.

Value

A named list representing the facets generated by the split with elements values, datasplit, and labels, which are the same length and correspond to each other element-wise.

See Also

Other make_custom_split: add_combo_facet(), drop_facet_levels(), make_split_fun(), restrict_facets(), trim_levels_in_facets()

Examples

```
splres <- make_split_result(
  values = c("hi", "lo"),
  datasplit = list(hi = mtcars, lo = mtcars[1:10, ]),
  labels = c("more data", "less data"),
  subset_exprs = list(expression(TRUE), expression(seq_along(wt) <= 10))
)
```

```
splres2 <- add_to_split_result(splres,
  values = "med",
  datasplit = list(med = mtcars[1:20, ]),
  labels = "kinda some data",
  subset_exprs = quote(seq_along(wt) <= 20)
)
```

---

make_subset_expr *Make subset expression for a split-value pair*

Description

Make subset expression for a split-value pair

Usage

```
make_subset_expr(spl, val)

## S4 method for signature 'VarLevelSplit'
make_subset_expr(spl, val)

## S4 method for signature 'MultiVarSplit'
make_subset_expr(spl, val)

## S4 method for signature 'AnalyzeVarSplit'
make_subset_expr(spl, val)

## S4 method for signature 'AnalyzeColVarSplit'
make_subset_expr(spl, val)

## S4 method for signature 'VarStaticCutSplit'
make_subset_expr(spl, val)

## S4 method for signature 'CumulativeCutSplit'
make_subset_expr(spl, val)

## S4 method for signature 'AllSplit'
make_subset_expr(spl, val)

## S4 method for signature 'expression'
make_subset_expr(spl, val)

## S4 method for signature 'character'
make_subset_expr(spl, val)
```

Arguments

spl	(Split) A split object.
val	(SplitValue or string) The value, either as a SplitValue object or the raw value as a string.

Details

If val is a SplitValue object which already contains a subsetting expression with length >0, that is immediately returned. Otherwise, the appropriate subsetting expression is constructed based on the split type of spl and the value val.

Value

A subseting expression to be used to restrict data to a particular column during tabulation.

Note

this is occasionally useful when constructing custom splitting behavior which may used for column splitting but generally should not be called directly by the end user.

Examples

```
spl <- VarLevelSplit("ARM", split_label = "ARM")
make_subset_expr(spl, "B: Placebo")
```

---

manual_cols *Manual column declaration*

Description

Manual column declaration

Usage

```
manual_cols(..., .lst = list(...), ccount_format = NULL)
```

Arguments

...	one or more vectors of levels to appear in the column space. If more than one set of levels is given, the values of the second are nested within each value of the first, and so on.
.lst	(list) a list of sets of levels, by default populated via list(...).
ccount_format	(FormatSpec) the format to use when counts are displayed.

Value

An InstantiatedColumnInfo object, suitable for declaring the column structure for a manually constructed table.

Author(s)

Gabriel Becker

Examples

```
# simple one level column space
rows <- lapply(1:5, function(i) {
  DataRow(rep(i, times = 3))
})
tbl <- TableTree(kids = rows, cinfo = manual_cols(split = c("a", "b", "c")))
tbl

# manually declared nesting
tbl2 <- TableTree(
  kids = list(DataRow(as.list(1:4))),
  cinfo = manual_cols(
    Arm = c("Arm A", "Arm B"),
    Gender = c("M", "F")
  )
)
tbl2
```

ManualSplit *Manually defined split*

Description

Manually defined split

Usage

```
ManualSplit(
  levels,
  label,
  name = "manual",
  extra_args = list(),
  indent_mod = 0L,
  cindent_mod = 0L,
  cvar = "",
  cextra_args = list(),
  label_pos = "visible",
  page_prefix = NA_character_,
  section_div = NA_character_
)
```

Arguments

levels	(character) levels of the split (i.e. the children of the manual split).
label	(string) a label (not to be confused with the name) for the object/structure.
name	(string) name of the split/table/row being created. Defaults to the value of the corresponding label, but is not required to be.
extra_args	(list) extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.
indent_mod	(numeric) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.
cindent_mod	(numeric(1)) the indent modifier for the content tables generated by this split.
cvar	(string) the variable, if any, that the content function should accept. Defaults to NA.
cextra_args	(list) extra arguments to be passed to the content function when tabulating row group summaries.
label_pos	(string) location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.
page_prefix	(string) prefix to be appended with the split value when forcing pagination between the children of a split/table.
section_div	(string) string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

Value

A ManualSplit object.

Author(s)

Gabriel Becker

`matrix_form,VTableTree-method`

Transform an `rtable` *to a list of matrices which can be used for outputting*

Description

Although `rtables` are represented as a tree data structure when outputting the table to ASCII or HTML it is useful to map the `rtable` to an in-between state with the formatted cells in a matrix form.

Usage

```
## S4 method for signature 'VTableTree'
matrix_form(
  obj,
  indent_rownames = FALSE,
  expand_newlines = TRUE,
  indent_size = 2,
  fontspec = NULL,
  col_gap = 3L,
  round_type = obj_round_type(obj)
)
```

Arguments

`obj`	(`ANY`) the object for the accessor to access or modify.
`indent_rownames`	(`flag`) if `TRUE`, the column with the row names in the `strings` matrix of the output has indented row names (strings pre-fixed).
`expand_newlines`	(`flag`) whether the matrix form generated should expand rows whose values contain newlines into multiple 'physical' rows (as they will appear when rendered into ASCII). Defaults to `TRUE`.
`indent_size`	(`numeric(1)`) number of spaces to use per indent level. Defaults to 2.
`fontspec`	(`font_spec`) The font that should be used by default when rendering this `MatrixPrintForm` object, or NULL (the default).
`col_gap`	(`numeric(1)`)] The number of spaces (in the font specified by `fontspec`) that should be placed between columns when the table is rendered directly to text (e.g., by `toString` or `export_as_txt`). Defaults to `3`.

round_type ("iec" (default), "iec_mod" or "sas")
the type of rounding to perform. See formatters::format_value() for details.

Details

The strings in the return object are defined as follows: row labels are those determined by make_row_df and cell values are determined using get_formatted_cells. (Column labels are calculated using a non-exported internal function.

Value

A list with the following elements:

strings The content, as it should be printed, of the top-left material, column headers, row labels, and cell values of tt.

spans The column-span information for each print-string in the strings matrix.

aligns The text alignment for each print-string in the strings matrix.

display Whether each print-string in the strings matrix should be printed.

row_info The data.frame generated by make_row_df.

With an additional nrow_header attribute indicating the number of pseudo "rows" that the column structure defines.

Examples

```
library(dplyr)

iris2 <- iris |>
  group_by(Species) |>
  mutate(group = as.factor(rep_len(c("a", "b"), length.out = n()))) |>
  ungroup()

lyt <- basic_table() |>
  split_cols_by("Species") |>
  split_cols_by("group") |>
  analyze(c("Sepal.Length", "Petal.Width"),
    afun = list_wrap_x(summary), format = "xx.xx"
  )

lyt

tbl <- build_table(lyt, iris2)

matrix_form(tbl)
```

MultiVarSplit *Split between two or more different variables*

Description

Split between two or more different variables

Usage

```
MultiVarSplit(
  vars,
  split_label = "",
  varlabels = NULL,
  varnames = NULL,
  cfun = NULL,
  cformat = NULL,
  cna_str = NA_character_,
  split_format = NULL,
  split_na_str = NA_character_,
  split_name = "multivars",
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  indent_mod = 0L,
  cindent_mod = 0L,
  cvar = "",
  cextra_args = list(),
  label_pos = "visible",
  split_fun = NULL,
  page_prefix = NA_character_,
  section_div = NA_character_,
  show_colcounts = FALSE,
  colcount_format = NULL
)
```

Arguments

vars	(character) vector of variable names.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
varlabels	(character) vector of labels for vars.
varnames	(character) vector of names for vars which will appear in pathing. When vars are all

unique this will be the variable names. If not, these will be variable names with suffixes as necessary to enforce uniqueness.

`cfun` (`list`, `function`, or `NULL`)
tabulation function(s) for creating content rows. Must accept `x` or `df` as first parameter. Must accept `labelstr` as the second argument. Can optionally accept all optional arguments accepted by analysis functions. See `analyze()`.

`cformat` (`string`, `function`, or `list`)
format for content rows.

`cna_str` (`character`)
NA string for use with `cformat` for content table.

`split_format` (`string`, `function`, or `list`)
default format associated with the split being created.

`split_na_str` (`character`)
NA string vector for use with `split_format`.

`split_name` (`string`)
name associated with the split (for pathing, etc.).

`child_labels` (`string`)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts `"default"`, `"visible"`, and `"hidden"`. Defaults to `"default"` which flags the label row as visible only if the child has 0 content rows.

`extra_args` (`list`)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

`indent_mod` (`numeric`)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

`cindent_mod` (`numeric(1)`)
the indent modifier for the content tables generated by this split.

`cvar` (`string`)
the variable, if any, that the content function should accept. Defaults to `NA`.

`cextra_args` (`list`)
extra arguments to be passed to the content function when tabulating row group summaries.

`label_pos` (`string`)
location where the variable label should be displayed. Accepts `"hidden"` (default for non-analyze row splits), `"visible"`, `"topleft"`, and `"default"` (for analyze splits only). For `analyze` calls, `"default"` indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

`split_fun` (`function` or `NULL`)
custom splitting function. See custom_split_funs.

page_prefix (string)
: prefix to be appended with the split value when forcing pagination between the children of a split/table.

section_div (string)
: string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

show_colcounts (logical(1))
: should column counts be displayed at the level facets created by this split. Defaults to FALSE.

colcount_format (character(1))
: if show_colcounts is TRUE, the format which should be used to display column counts for facets generated by this split. Defaults to "(N=xx)".

Value

A MultiVarSplit object.

Author(s)

Gabriel Becker

---

names,VTableNodeInfo-method

Names of a TableTree

Description

Names of a TableTree

Usage

```
## S4 method for signature 'VTableNodeInfo'
names(x)

## S4 method for signature 'InstantiatedColumnInfo'
names(x)

## S4 method for signature 'LayoutColTree'
names(x)

## S4 method for signature 'VTableTree'
row.names(x)
```

Arguments

x (TableTree)
: the object.

Details

For TableTrees with more than one level of splitting in columns, the names are defined to be the top-level split values repped out across the columns that they span.

Value

The column names of x, as defined in the details above.

---

no_colinfo *Exported for use in* tern

Description

Does the table/row/InstantiatedColumnInfo object contain no column structure information?

Usage

```
no_colinfo(obj)

## S4 method for signature 'VTableNodeInfo'
no_colinfo(obj)

## S4 method for signature 'InstantiatedColumnInfo'
no_colinfo(obj)
```

Arguments

obj	(ANY) the object for the accessor to access or modify.

Value

TRUE if the object has no/empty instantiated column information, FALSE otherwise.

---

nrow,VTableTree-method *Table dimensions*

Description

Table dimensions

Usage

```
## S4 method for signature 'VTableTree'
nrow(x)

## S4 method for signature 'VTableNodeInfo'
ncol(x)

## S4 method for signature 'VTableNodeInfo'
dim(x)
```

Arguments

x	(TableTree or ElementaryTable) a table object.

Value

The number of rows (nrow), columns (ncol), or both (dim) of the object.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze(c("SEX", "AGE"))

tbl <- build_table(lyt, ex_adsl)

dim(tbl)
nrow(tbl)
ncol(tbl)

NROW(tbl)
NCOL(tbl)
```

---

obj_avar *Row attribute accessors*

Description

Row attribute accessors

Usage

```
obj_avar(obj)

## S4 method for signature 'TableRow'
obj_avar(obj)
```

```
## S4 method for signature 'ElementaryTable'
obj_avar(obj)

row_cells(obj)

## S4 method for signature 'TableRow'
row_cells(obj)

## S4 method for signature 'RowsVerticalSection'
row_cells(obj)

row_cells(obj) <- value

## S4 replacement method for signature 'TableRow'
row_cells(obj) <- value

row_values(obj)

## S4 method for signature 'TableRow'
row_values(obj)

row_values(obj) <- value

## S4 replacement method for signature 'TableRow'
row_values(obj) <- value

## S4 replacement method for signature 'LabelRow'
row_values(obj) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
value	(ANY) the new value.

Value

Various return values depending on the accessor called.

`obj_name,VNodeInfo-method`

Methods for generics in the `formatters` *package*

Description

See the `formatters` documentation for descriptions of these generics.

These are internal methods that are documented only to satisfy `R CMD check`. End users should pay no attention to this documentation, except for the few exported methods.

Usage

```
## S4 method for signature 'VNodeInfo'
obj_name(obj)

## S4 method for signature 'Split'
obj_name(obj)

## S4 replacement method for signature 'VNodeInfo'
obj_name(obj) <- value

## S4 replacement method for signature 'Split'
obj_name(obj) <- value

## S4 method for signature 'Split'
obj_label(obj)

## S4 method for signature 'TableRow'
obj_label(obj)

## S4 method for signature 'VTableTree'
obj_label(obj)

## S4 method for signature 'ValueWrapper'
obj_label(obj)

## S4 replacement method for signature 'Split'
obj_label(obj) <- value

## S4 replacement method for signature 'TableRow'
obj_label(obj) <- value

## S4 replacement method for signature 'ValueWrapper'
obj_label(obj) <- value

## S4 replacement method for signature 'VTableTree'
obj_label(obj) <- value

## S4 method for signature 'VTableNodeInfo'
obj_format(obj)

## S4 method for signature 'CellValue'
obj_format(obj)
```

```
## S4 method for signature 'Split'
obj_format(obj)

## S4 method for signature 'RowsVerticalSection'
obj_format(obj)

## S4 replacement method for signature 'VTableNodeInfo'
obj_format(obj) <- value

## S4 replacement method for signature 'Split'
obj_format(obj) <- value

## S4 replacement method for signature 'CellValue'
obj_format(obj) <- value

## S4 replacement method for signature 'RowsVerticalSection'
obj_format(obj) <- value

## S4 method for signature 'Split'
obj_na_str(obj)

## S4 method for signature 'VTitleFooter'
main_title(obj)

## S4 replacement method for signature 'VTitleFooter'
main_title(obj) <- value

## S4 method for signature 'TableRow'
main_title(obj)

## S4 method for signature 'VTitleFooter'
subtitles(obj)

## S4 replacement method for signature 'VTitleFooter'
subtitles(obj) <- value

## S4 method for signature 'TableRow'
subtitles(obj)

## S4 method for signature 'VTitleFooter'
main_footer(obj)

## S4 replacement method for signature 'VTitleFooter'
main_footer(obj) <- value

## S4 method for signature 'TableRow'
main_footer(obj)
```

```
## S4 method for signature 'VTitleFooter'
prov_footer(obj)

## S4 replacement method for signature 'VTitleFooter'
prov_footer(obj) <- value

## S4 method for signature 'TableRow'
prov_footer(obj)

## S4 method for signature 'VTableNodeInfo'
table_inset(obj)

## S4 method for signature 'PreDataTableLayouts'
table_inset(obj)

## S4 replacement method for signature 'VTableNodeInfo'
table_inset(obj) <- value

## S4 replacement method for signature 'PreDataTableLayouts'
table_inset(obj) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
table_inset(obj) <- value

## S4 method for signature 'ANY'
obj_round_type(obj)

## S4 method for signature 'PreDataTableLayouts'
obj_round_type(obj)

## S4 method for signature 'VTableTree'
obj_round_type(obj)

## S4 method for signature 'TableRow'
obj_round_type(obj)

## S4 method for signature 'CellValue'
obj_round_type(obj)

## S4 replacement method for signature 'VTableTree'
obj_round_type(obj) <- value

## S4 replacement method for signature 'TableRow'
obj_round_type(obj) <- value

## S4 replacement method for signature 'LabelRow'
obj_round_type(obj) <- value
```

```
## S4 replacement method for signature 'CellValue'
obj_round_type(obj) <- value

## S4 method for signature 'TableRow'
nlines(x, colwidths = NULL, max_width = NULL, fontspec, col_gap = 3)

## S4 method for signature 'LabelRow'
nlines(
  x,
  colwidths = NULL,
  max_width = NULL,
  fontspec = fontspec,
  col_gap = NULL
)

## S4 method for signature 'RefFootnote'
nlines(x, colwidths = NULL, max_width = NULL, fontspec, col_gap = NULL)

## S4 method for signature 'InstantiatedColumnInfo'
nlines(x, colwidths = NULL, max_width = NULL, fontspec, col_gap = 3)

## S4 method for signature 'VTableTree'
make_row_df(
  tt,
  colwidths = NULL,
  visible_only = TRUE,
  rownum = 0,
  indent = 0L,
  path = character(),
  incontent = FALSE,
  repr_ext = 0L,
  repr_inds = integer(),
  sibpos = NA_integer_,
  nsibs = NA_integer_,
  max_width = NULL,
  fontspec = NULL,
  col_gap = 3
)

## S4 method for signature 'TableRow'
make_row_df(
  tt,
  colwidths = NULL,
  visible_only = TRUE,
  rownum = 0,
  indent = 0L,
  path = "root",
```

```
  incontent = FALSE,
  repr_ext = 0L,
  repr_inds = integer(),
  sibpos = NA_integer_,
  nsibs = NA_integer_,
  max_width = NULL,
  fontspec,
  col_gap = 3
)

## S4 method for signature 'LabelRow'
make_row_df(
  tt,
  colwidths = NULL,
  visible_only = TRUE,
  rownum = 0,
  indent = 0L,
  path = "root",
  incontent = FALSE,
  repr_ext = 0L,
  repr_inds = integer(),
  sibpos = NA_integer_,
  nsibs = NA_integer_,
  max_width = NULL,
  fontspec,
  col_gap = 3
)
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
value	(ANY) the new value.
x	(ANY) an object.
colwidths	(numeric) a vector of column widths for use in vertical pagination.
max_width	(numeric(1)) width that strings should be wrapped to when determining how many lines they require.
fontspec	(font_spec) a font_spec object specifying the font information to use for calculating string widths and heights, as returned by font_spec().
col_gap	(numeric(1)) width of gap between columns in number of spaces. Only used by methods which must calculate span widths after wrapping.

tt	(TableTree or related class) a TableTree object representing a populated table.
visible_only	(flag) should only visible aspects of the table structure be reflected in this summary. Defaults to TRUE. May not be supported by all methods.
rownum	(numeric(1)) internal detail, do not set manually.
indent	(integer(1)) internal detail, do not set manually.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
incontent	(flag) internal detail, do not set manually.
repr_ext	(integer(1)) internal detail, do not set manually.
repr_inds	(integer) internal detail, do not set manually.
sibpos	(integer(1)) internal detail, do not set manually.
nsibs	(integer(1)) internal detail, do not set manually.

Details

When visible_only is TRUE (the default), methods should return a data.frame with exactly one row per visible row in the table-like object. This is useful when reasoning about how a table will print, but does not reflect the full pathing space of the structure (though the paths which are given will all work as is).

If supported, when visible_only is FALSE, every structural element of the table (in row-space) will be reflected in the returned data.frame, meaning the full pathing-space will be represented but some rows in the layout summary will not represent printed rows in the table as it is displayed.

Most arguments beyond tt and visible_only are present so that make_row_df methods can call make_row_df recursively and retain information, and should not be set during a top-level call.

Value

- Accessor functions return the current value of the component being accessed of obj
- Setter functions return a modified copy of obj with the new value.

Note

The technically present root tree node is excluded from the summary returned by both make_row_df and make_col_df (see relevant functions inrtables), as it is the row/column structure of tt and thus not useful for pathing or pagination.

Examples

```
# Expected error with matrix_form. For real case examples consult {rtables} documentation
mf <- basic_matrix_form(iris)
# make_row_df(mf) # Use table obj instead
```

---

pag_tt_indices *Pagination of a* TableTree

Description

Paginate an rtables table in the vertical and/or horizontal direction, as required for the specified page size.

Usage

```
pag_tt_indices(
  tt,
  lpp = 15,
  min_siblings = 2,
  nosplitin = character(),
  colwidths = NULL,
  max_width = NULL,
  fontspec = NULL,
  col_gap = 3,
  verbose = FALSE
)

paginate_table(
  tt,
  page_type = "letter",
  font_family = "Courier",
  font_size = 8,
  lineheight = 1,
  landscape = FALSE,
  pg_width = NULL,
  pg_height = NULL,
  margins = c(top = 0.5, bottom = 0.5, left = 0.75, right = 0.75),
  lpp = NA_integer_,
  cpp = NA_integer_,
  min_siblings = 2,
  nosplitin = character(),
  colwidths = NULL,
  tf_wrap = FALSE,
  max_width = NULL,
  fontspec = font_spec(font_family, font_size, lineheight),
  col_gap = 3,
  verbose = FALSE
)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
lpp	(numeric(1)) maximum lines per page including (re)printed header and context rows.
min_siblings	(numeric(1)) minimum sibling rows which must appear on either side of pagination row for a mid-subtable split to be valid. Defaults to 2.
nosplitin	(character) names of sub-tables where page-breaks are not allowed, regardless of other considerations. Defaults to none.
colwidths	(numeric) a vector of column widths for use in vertical pagination.
max_width	(integer(1), string or NULL) width that title and footer (including footnotes) materials should be word-wrapped to. If NULL, it is set to the current print width of the session (getOption("width")). If set to "auto", the width of the table (plus any table inset) is used. Parameter is ignored if tf_wrap = FALSE.
fontspec	(font_spec) a font_spec object specifying the font information to use for calculating string widths and heights, as returned by font_spec().
col_gap	(numeric(1)) space (in characters) between columns.
verbose	(flag) whether additional information should be displayed to the user. Defaults to FALSE.
page_type	(string) name of a page type. See page_types. Ignored when pg_width and pg_height are set directly.
font_family	(string) name of a font family. An error will be thrown if the family named is not monospaced. Defaults to "Courier".
font_size	(numeric(1)) font size. Defaults to 12.
lineheight	(numeric(1)) line height. Defaults to 1.
landscape	(flag) whether the dimensions of page_type should be inverted for landscape orientation. Defaults to FALSE, ignored when pg_width and pg_height are set directly.
pg_width	(numeric(1)) page width in inches.
pg_height	(numeric(1)) page height in inches.

margins (numeric(4))
named numeric vector containing "bottom", "left", "top", and "right" margins in inches. Defaults to .5 inches for both vertical margins and .75 for both horizontal margins.

cpp (numeric(1) or NULL)
width (in characters) of the pages for horizontal pagination. NA (the default) indicates cpp should be inferred from the page size; NULL indicates no horizontal pagination should be done regardless of page size.

tf_wrap (flag)
whether the text for title, subtitles, and footnotes should be wrapped.

Details

rtables pagination is context aware, meaning that label rows and row-group summaries (content rows) are repeated after (vertical) pagination, as appropriate. This allows the reader to immediately understand where they are in the table after turning to a new page, but does also mean that a rendered, paginated table will take up more lines of text than rendering the table without pagination would.

Pagination also takes into account word-wrapping of title, footer, column-label, and formatted cell value content.

Vertical pagination information (pagination data.frame) is created using (make_row_df).

Horizontal pagination is performed by creating a pagination data frame for the columns, and then applying the same algorithm used for vertical pagination to it.

If physical page size and font information are specified, these are used to derive lines-per-page (lpp) and characters-per-page (cpp) values.

The full multi-direction pagination algorithm then is as follows:

1. Adjust lpp and cpp to account for rendered elements that are not rows (columns):

- titles/footers/column labels, and horizontal dividers in the vertical pagination case
- row-labels, table_inset, and top-left materials in the horizontal case

1. Perform 'forced pagination' representing page-by row splits, generating 1 or more tables.
2. Perform vertical pagination separately on each table generated in (1).
3. Perform horizontal pagination **on the entire table** and apply the results to each table page generated in (1)-(2).
4. Return a list of subtables representing full bi-directional pagination.

Pagination in both directions is done using the *Core Pagination Algorithm* implemented in the formatters package:

Value

- pag_tt_indices returns a list of paginated-groups of row-indices of tt.
- paginate_table returns the subtables defined by subsetting by the indices defined by pag_tt_indices.

Pagination Algorithm

Pagination is performed independently in the vertical and horizontal directions based solely on a *pagination data frame*, which includes the following information for each row/column:

- Number of lines/characters rendering the row will take **after word-wrapping** (`self_extent`)
- The indices (`reprint_inds`) and number of lines (`par_extent`) of the rows which act as **context** for the row
- The row's number of siblings and position within its siblings

Given `lpp` (`cpp`) is already adjusted for rendered elements which are not rows/columns and a data frame of pagination information, pagination is performed via the following algorithm with `start = 1`.

Core Pagination Algorithm:

1. Initial guess for pagination position is `start + lpp` (`start + cpp`)
2. While the guess is not a valid pagination position, and `guess > start`, decrement guess and repeat.
   - An error is thrown if all possible pagination positions between `start` and `start + lpp` (`start + cpp`) would be `< start` after decrementing
3. Retain pagination index
4. If pagination point was less than `NROW(tt)` (`ncol(tt)`), set `start` to `pos + 1`, and repeat steps (1) - (4).

Validating Pagination Position:

Given an (already adjusted) `lpp` or `cpp` value, a pagination is invalid if:

- The rows/columns on the page would take more than (adjusted) `lpp` lines/`cpp` characters to render **including**:
  - word-wrapping
  - (vertical only) context repetition
- (vertical only) footnote messages and/or section divider lines take up too many lines after rendering rows
- (vertical only) row is a label or content (row-group summary) row
- (vertical only) row at the pagination point has siblings, and it has less than `min_siblings` preceding or following siblings
- pagination would occur within a sub-table listed in `nosplitin`

Examples

```
s_summary <- function(x) {
  if (is.numeric(x)) {
    in_rows(
      "n" = rcell(sum(!is.na(x)), format = "xx"),
      "Mean (sd)" = rcell(c(mean(x, na.rm = TRUE), sd(x, na.rm = TRUE)),
        format = "xx.xx (xx.xx)"
      ),
```

```
      "IQR" = rcell(IQR(x, na.rm = TRUE), format = "xx.xx"),
      "min - max" = rcell(range(x, na.rm = TRUE), format = "xx.xx - xx.xx")
    )
  } else if (is.factor(x)) {
    vs <- as.list(table(x))
    do.call(in_rows, lapply(vs, rcell, format = "xx"))
  } else {
    (
      stop("type not supported")
    )
  }
}

lyt <- basic_table() |>
  split_cols_by(var = "ARM") |>
  analyze(c("AGE", "SEX", "BEP01FL", "BMRKR1", "BMRKR2", "COUNTRY"), afun = s_summary)

tbl <- build_table(lyt, ex_adsl)
tbl

nrow(tbl)

row_paths_summary(tbl)

tbls <- paginate_table(tbl, lpp = 15)
mf <- matrix_form(tbl, indent_rownames = TRUE)
w_tbls <- propose_column_widths(mf) # so that we have the same column widths


tmp <- lapply(tbls, function(tbli) {
  cat(toString(tbli, widths = w_tbls))
  cat("\n\n")
  cat("~~~~ PAGE BREAK ~~~~")
  cat("\n\n")
})
```

`prune_table` *Recursively prune a* `TableTree`

Description

Recursively prune a `TableTree`

Usage

```
prune_table(
  tt,
  prune_func = prune_empty_level,
  stop_depth = NA_real_,
```

```
  depth = 0,
  ...
)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
prune_func	(function) a function to be called on each subtree which returns TRUE if the entire subtree should be removed.
stop_depth	(numeric(1)) the depth after which subtrees should not be checked for pruning. Defaults to NA which indicates pruning should happen at all levels.
depth	(numeric(1)) used internally, not intended to be set by the end user.
...	named arguments to optionally be passed down to prune_func if it accepts them (or ...)

Value

A TableTree pruned via recursive application of prune_func.

See Also

prune_empty_level() for details on this and several other basic pruning functions included in the rtables package.

Examples

```
adsl <- ex_adsl
levels(adsl$SEX) <- c(levels(ex_adsl$SEX), "OTHER")

tbl_to_prune <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  summarize_row_groups() |>
  split_rows_by("STRATA1") |>
  summarize_row_groups() |>
  analyze("AGE") |>
  build_table(adsl)

tbl_to_prune |> prune_table()
```

qtable_layout *Generalized frequency table*

Description

This function provides a convenience interface for generating generalizations of a 2-way frequency table. Row and column space can be facetted by variables, and an analysis function can be specified. The function then builds a layout with the specified layout and applies it to the data provided.

Usage

```
qtable_layout(
  data,
  row_vars = character(),
  col_vars = character(),
  avar = NULL,
  row_labels = NULL,
  afun = NULL,
  summarize_groups = FALSE,
  title = "",
  subtitles = character(),
  main_footer = character(),
  prov_footer = character(),
  show_colcounts = TRUE,
  drop_levels = TRUE,
  ...,
  .default_rlabel = NULL
)

qtable(
  data,
  row_vars = character(),
  col_vars = character(),
  avar = NULL,
  row_labels = NULL,
  afun = NULL,
  summarize_groups = FALSE,
  title = "",
  subtitles = character(),
  main_footer = character(),
  prov_footer = character(),
  show_colcounts = TRUE,
  drop_levels = TRUE,
  ...
)
```

Arguments

data	(data.frame) the data to tabulate.
row_vars	(character) the names of variables to be used in row facetting.
col_vars	(character) the names of variables to be used in column facetting.
avar	(string) the variable to be analyzed. Defaults to the first variable in data.
row_labels	(character or NULL) row label(s) which should be applied to the analysis rows. Length must match the number of rows generated by afun.
afun	(function) the function to generate the analysis row cell values. This can be a proper analysis function, or a function which returns a vector or list. Vectors are taken as multi-valued single cells, whereas lists are interpreted as multiple cells.
summarize_groups	(flag) whether each level of nesting should include marginal summary rows. Defaults to FALSE.
title	(string) single string to use as main title (formatters::main_title()). Ignored for subtables.
subtitles	(character) a vector of strings to use as subtitles (formatters::subtitles()), where every element is printed on a separate line. Ignored for subtables.
main_footer	(character) a vector of strings to use as main global (non-referential) footer materials (formatters::main_footer()) where every element is printed on a separate line.
prov_footer	(character) a vector of strings to use as provenance-related global footer materials (formatters::prov_footer()), where every element is printed on a separate line.
show_colcounts	(logical(1)) Indicates whether the lowest level of applied to data. NA, the default, indicates that the show_colcounts argument(s) passed to the relevant calls to split_cols_by* functions. Non-missing values will override the behavior specified in column splitting layout instructions which create the lowest level, or leaf, columns.
drop_levels	(flag) whether unobserved factor levels should be dropped during facetting. Defaults to TRUE.
...	additional arguments passed to afun.
.default_rlabel	(string) this is an implementation detail that should not be set by end users.

Details

This function creates a table with a single top-level structure in both row and column dimensions involving faceting by 0 or more variables in each dimension.

The display of the table depends on certain details of the tabulation. In the case of an `afun` which returns a single cell's contents (either a scalar or a vector of 2 or 3 elements), the label rows for the deepest-nested row facets will be hidden and the labels used there will be used as the analysis row labels. In the case of an `afun` which returns a list (corresponding to multiple cells), the names of the list will be used as the analysis row labels and the deepest-nested facet row labels will be visible.

The table will be annotated in the top-left area with an informative label displaying the analysis variable (`avar`), if set, and the function used (captured via substitute) where possible, or 'count' if not. One exception where the user may directly modify the top-left area (via `row_labels`) is the case of a table with row facets and an `afun` which returns a single row.

Value

- `qtable` returns a built `TableTree` object representing the desired table
- `qtable_layout` returns a `PreDataTableLayouts` object declaring the structure of the desired table, suitable for passing to `build_table()`.

Examples

```
qtable(ex_adsl)
qtable(ex_adsl, row_vars = "ARM")
qtable(ex_adsl, col_vars = "ARM")
qtable(ex_adsl, row_vars = "SEX", col_vars = "ARM")
qtable(ex_adsl, row_vars = c("COUNTRY", "SEX"), col_vars = c("ARM", "STRATA1"))
qtable(ex_adsl,
  row_vars = c("COUNTRY", "SEX"),
  col_vars = c("ARM", "STRATA1"), avar = "AGE", afun = mean
)
summary_list <- function(x, ...) as.list(summary(x))
qtable(ex_adsl, row_vars = "SEX", col_vars = "ARM", avar = "AGE", afun = summary_list)
suppressWarnings(qtable(ex_adsl,
  row_vars = "SEX",
  col_vars = "ARM", avar = "AGE", afun = range
))
```

---

rbindl_rtables *Row-bind* `TableTree` *and related objects*

Description

Row-bind `TableTree` and related objects

Usage

```
rbindl_rtables(
  x,
  gap = lifecycle::deprecated(),
  check_headers = lifecycle::deprecated()
)

## S4 method for signature 'VTableNodeInfo'
rbind(..., deparse.level = 1)

## S4 method for signature 'VTableNodeInfo,ANY'
rbind2(x, y)
```

Arguments

x	(VTableNodeInfo) TableTree, ElementaryTable, or TableRow object.
gap	**[Deprecated]** ignored.
check_headers	**[Deprecated]** ignored.
...	(ANY) elements to be stacked.
deparse.level	(numeric(1)) currently ignored.
y	(VTableNodeInfo) TableTree, ElementaryTable, or TableRow object.

Value

A formal table object.

Note

When objects are row-bound, titles and footer information is retained from the first object (if any exists) if all other objects have no titles/footers or have identical titles/footers. Otherwise, all titles/footers are removed and must be set for the bound table via the formatters::main_title(), formatters::subtitles(), formatters::main_footer(), and formatters::prov_footer() functions.

Examples

```
mtbl <- rtable(
  header = rheader(
   rrow(row.name = NULL, rcell("Sepal.Length", colspan = 2), rcell("Petal.Length", colspan = 2)),
    rrow(NULL, "mean", "median", "mean", "median")
  ),
  rrow(
    row.name = "All Species",
    mean(iris$Sepal.Length), median(iris$Sepal.Length),
```

```
    mean(iris$Petal.Length), median(iris$Petal.Length),
    format = "xx.xx"
  )
)

mtbl2 <- with(subset(iris, Species == "setosa"), rtable(
  header = rheader(
   rrow(row.name = NULL, rcell("Sepal.Length", colspan = 2), rcell("Petal.Length", colspan = 2)),
    rrow(NULL, "mean", "median", "mean", "median")
  ),
  rrow(
    row.name = "Setosa",
    mean(Sepal.Length), median(Sepal.Length),
    mean(Petal.Length), median(Petal.Length),
    format = "xx.xx"
  )
))

rbind(mtbl, mtbl2)
rbind(mtbl, rrow(), mtbl2)
rbind(mtbl, rrow("aaa"), indent(mtbl2))
```

`rcell` *Cell value constructors*

Description

Construct a cell value and associate formatting, labeling, indenting, and column spanning information with it.

Usage

```
rcell(
  x,
  format = NULL,
  colspan = 1L,
  label = NULL,
  indent_mod = NULL,
  footnotes = NULL,
  align = NULL,
  format_na_str = NULL,
  stat_names = NULL,
  round_type = valid_round_type
)

non_ref_rcell(
  x,
  is_ref,
```

```
  format = NULL,
  colspan = 1L,
  label = NULL,
  indent_mod = NULL,
  refval = NULL,
  align = "center",
  format_na_str = NULL
)
```

Arguments

x	(ANY) cell value.
format	(string or function) the format label (string) or formatters function to apply to x. See formatters::list_valid_format_l for currently supported format labels.
colspan	(integer(1)) column span value.
label	(string or NULL) label. If non-NULL, it will be looked at when determining row labels.
indent_mod	(numeric) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.
footnotes	(list or NULL) referential footnote messages for the cell.
align	(string or NULL) alignment the value should be rendered with. Defaults to "center" if NULL is used. See formatters::list_valid_aligns() for all currently supported alignments.
format_na_str	(string) string which should be displayed when formatted if this cell's value(s) are all NA.
stat_names	(character or NA) names for the statistics in the cell. It can be a vector of strings. If NA, statistic names are not specified.
round_type	("iec" (default), "iec_mod" or "sas") the type of rounding to perform. See formatters::format_value() for details.
is_ref	(flag) whether function is being used in the reference column (i.e. .in_ref_col should be passed to this argument).
refval	(ANY) value to use when in the reference column. Defaults to NULL.

Details

non_ref_rcell provides the common *blank for cells in the reference column, this value otherwise*, and should be passed the value of .in_ref_col when it is used.

Value

An object representing the value within a single cell within a populated table. The underlying structure of this object is an implementation detail and should not be relied upon beyond calling accessors for the class.

Note

Currently column spanning is only supported for defining header structure.

Examples

```
rcell(1, format = "xx.x")
rcell(c(1, 2), format = c("xx - xx"))
rcell(c(1, 2), stat_names = c("Rand1", "Rand2"))
```

RefFootnote *Referential Footnote*

Description

Referential Footnote

Usage

```
RefFootnote(note, index = NA_integer_, symbol = NA_character_)
```

Arguments

note	(character(1)) The text of the footnote, not including the symbol or index.
index	(integer(1)) The index (position in the list of footnotes); this should not typically be set by users. NA (the default) indicates automatic counting.
symbol	(character(1)) The symbol to be used instead of the index value to indicate the footnote's anchor and message. NA (the default) will use the footnote's index (after automatic counting, if applicable) as its symbol.

Details

When `symbol` is non-missing, all footnotes with the same symbol will share a single footer entry containing `note`, rather than it being entered repeatedly. `symbol` cannot be `"NA"` or contain `"{"` or `"}"`.

Value

a `RefFootnote` object suitable for use in `in_rows` and `fnotes_at_path<-` and `rcell`, or `NULL` if `note` is of length zero.

Examples

```
afun1 <- function(x, ...) {
  in_rows(
    row1 = 5,
    row2 = c(1, 2),
    .row_footnotes = list(row1 = list(RefFootnote("row 1 rfn"))),
    .cell_footnotes = list(row2 = list(RefFootnote("row 2 cfn")))
  )
}

afun2 <- function(x, ...) {
  in_rows(
    row1 = 5,
    row2 = c(1, 2),
    .row_footnotes = list(row1 = list(RefFootnote("row 1 rfn", symbol = "+"))),
    .cell_footnotes = list(row2 = list(RefFootnote("row 2 cfn", symbol = "^")))
  )
}

lyt1 <- basic_table() |>
  split_cols_by("ARM") |>
  analyze("AGE", afun = afun1)

build_table(lyt1, DM)

lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("STRATA1") |>
  analyze("AGE", afun = afun2)

build_table(lyt2, DM)
```

---

restrict_facets *Postprocessing split function behavior to generally restrict facets*

Description

Postprocessing split function behavior to generally restrict facets

Usage

```
restrict_facets(
  facets,
  op = c("keep", "exclude"),
  reorder = TRUE,
  quiet = FALSE
)
```

Arguments

facets	(character) Vector of facet names
op	("keep", or "exclude") Whether facets names facets to be (exclusively) kept (the default) or removed.
reorder	(flag) For op == "keep", should the resulting facets be reordered to the order they appear in facets. Defaults to TRUE. Ignored if op == "exclude".
quiet	(logical(1)) Whether warnings should be given or not (the default) when facets named in facets are not found in the split result.

Details

This is a function factory which creates a post-process behavioral building block for use in make_split_fun().

This factory provides the equivalent of both keep_split_levels and remove_split_levels in a form suitable for use in make_split_fun().

When op is "keep" (the default), resulting facets are restricted to only those named in facets when the generated function is applied to a split result; in the case of "exclude", facets named in facets are removed so that only those not named remain.

The generated function will throw a warning if any of facets are not found in the split result it receives during splitting, unless it was created with quiet = FALSE.

Value

a function suitable for use within the post argument of make_split_fun().

See Also

make_split_fun()

Other make_custom_split: add_combo_facet(), drop_facet_levels(), make_split_fun(), make_split_result(), trim_levels_in_facets()

Examples

```
keep_spl <- make_split_fun(post = list(restrict_facets(c("M", "F"), op = "keep")))

lyt <- basic_table() |>
```

```
  split_cols_by("SEX", split_fun = keep_spl) |>
  analyze("AGE")

build_table(lyt, ex_adsl)


excl_undiff <- restrict_facets("UNDIFFERENTIATED", op = "exclude")
excl_spl <- make_split_fun(post = list(excl_undiff))

lyt <- basic_table() |>
  split_cols_by("SEX", split_fun = excl_spl) |>
  analyze("AGE")

build_table(lyt, ex_adsl)
```

`rheader` *Create a header*

Description

Create a header

Usage

```
rheader(..., format = "xx", .lst = NULL)
```

Arguments

`...`	row specifications, either as character vectors or the output from `rrow()`, `DataRow()`, `LabelRow()`, etc.
`format`	(`string`, `function`, or `list`) the format label (string) or formatter function to apply to the cell values passed via `....` See `formatters::list_valid_format_labels()` for currently supported format labels.
`.lst`	(`list`) an already-collected list of arguments to be used instead of the elements of `....` Arguments passed via `...` will be ignored if this is specified.

Value

A `InstantiatedColumnInfo` object.

See Also

Other compatibility: `rrow()`, `rrowl()`, `rtable()`

Examples

```
h1 <- rheader(c("A", "B", "C"))
h1

h2 <- rheader(
  rrow(NULL, rcell("group 1", colspan = 2), rcell("group 2", colspan = 2)),
  rrow(NULL, "A", "B", "A", "B")
)
h2
```

---

rm_all_colcounts *Set all column counts at all levels of nesting to NA*

Description

Set all column counts at all levels of nesting to NA

Usage

```
rm_all_colcounts(obj)

## S4 method for signature 'VTableTree'
rm_all_colcounts(obj)

## S4 method for signature 'InstantiatedColumnInfo'
rm_all_colcounts(obj)

## S4 method for signature 'LayoutColTree'
rm_all_colcounts(obj)

## S4 method for signature 'LayoutColLeaf'
rm_all_colcounts(obj)
```

Arguments

obj	(ANY) the object for the accessor to access or modify.

Value

obj with all column counts reset to missing

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  analyze("AGE")
tbl <- build_table(lyt, ex_adsl)

# before
col_counts(tbl)
tbl <- rm_all_colcounts(tbl)
col_counts(tbl)
```

---

row_footnotes *Referential footnote accessors*

Description

Access and set the referential footnotes aspects of a built table.

Usage

```
row_footnotes(obj)

row_footnotes(obj) <- value

cell_footnotes(obj)

cell_footnotes(obj) <- value

col_fnotes_here(obj)

## S4 method for signature 'ANY'
col_fnotes_here(obj)

col_fnotes_here(obj) <- value

col_footnotes(obj)

col_footnotes(obj) <- value

ref_index(obj)

ref_index(obj) <- value

ref_symbol(obj)

ref_symbol(obj) <- value
```

```
ref_msg(obj)

fnotes_at_path(obj, rowpath = NULL, colpath = NULL, reset_idx = TRUE) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
value	(ANY) the new value.
rowpath	(character or NULL) path within row structure. NULL indicates the footnote should go on the column rather than cell.
colpath	(character or NULL) path within column structure. NULL indicates footnote should go on the row rather than cell.
reset_idx	(flag) whether the numbering for referential footnotes should be immediately recalculated. Defaults to TRUE.

See Also

row_paths(), col_paths(), row_paths_summary(), col_paths_summary()

Examples

```
# How to add referencial footnotes after having created a table
lyt <- basic_table() |>
  split_rows_by("SEX", page_by = TRUE) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl <- trim_rows(tbl)
# Check the row and col structure to add precise references
# row_paths(tbl)
# col_paths(t)
# row_paths_summary(tbl)
# col_paths_summary(tbl)

# Add the citation numbers on the table and relative references in the footnotes
fnotes_at_path(tbl, rowpath = c("SEX", "F", "AGE", "Mean")) <- "Famous paper 1"
fnotes_at_path(tbl, rowpath = c("SEX", "UNDIFFERENTIATED")) <- "Unfamous paper 2"
# tbl
```

row_paths *Get a list of table row/column paths*

Description

Get a list of table row/column paths

Usage

```
row_paths(x)

col_paths(x)
```

Arguments

x	(VTableTree) an rtable object.

Value

A list of paths to each row/column within x.

See Also

cell_values(), fnotes_at_path<-, row_paths_summary(), col_paths_summary()

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze(c("SEX", "AGE"))

tbl <- build_table(lyt, ex_adsl)
tbl

row_paths(tbl)
col_paths(tbl)

cell_values(tbl, c("AGE", "Mean"), c("ARM", "B: Placebo"))
```

`row_paths_summary` *Print row/column paths summary*

Description

Print row/column paths summary

Usage

```
row_paths_summary(x)

col_paths_summary(x)
```

Arguments

`x`	(`VTableTree`) an `rtable` object.

Value

A data frame summarizing the row- or column-structure of `x`.

Examples

```
ex_adsl_MF <- ex_adsl |> dplyr::filter(SEX %in% c("M", "F"))

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX", split_fun = drop_split_levels) |>
  analyze(c("AGE", "BMRKR2"))

tbl <- build_table(lyt, ex_adsl_MF)
tbl

df <- row_paths_summary(tbl)
df

col_paths_summary(tbl)

# manually constructed table
tbl2 <- rtable(
  rheader(
    rrow(
      "row 1", rcell("a", colspan = 2),
      rcell("b", colspan = 2)
    ),
    rrow("h2", "a", "b", "c", "d")
  ),
  rrow("r1", 1, 2, 1, 2), rrow("r2", 3, 4, 2, 1)
```

```
)
col_paths_summary(tbl2)
```

---

rrow *Create an* rtable *row*

Description

Create an rtable row

Usage

```
rrow(
  row.name = "",
  ...,
  format = NULL,
  indent = 0,
  inset = 0L,
  round_type = valid_round_type
)
```

Arguments

row.name	(string or NULL) row name. If NULL, an empty string is used as row.name of the rrow().
...	cell values.
format	(string, function, or list) the format label (string) or formatter function to apply to the cell values passed via .... See formatters::list_valid_format_labels() for currently supported format labels.
indent	**[Deprecated]**
inset	(integer(1)) the table inset for the row or table being constructed. See formatters::table_inset() for details.
round_type	("iec", "iec_mod" or "sas") the type of rounding to perform. See round_fmt() for details.

Value

A row object of the context-appropriate type (label or data).

See Also

Other compatibility: rheader(), rrowl(), rtable()

Examples

```
rrow("ABC", c(1, 2), c(3, 2), format = "xx (xx.%)")
rrow("")
```

`rrowl` *Create an* `rtable` *row from a vector or list of values*

Description

Create an `rtable` row from a vector or list of values

Usage

```
rrowl(
  row.name,
  ...,
  format = NULL,
  indent = 0,
  inset = 0L,
  round_type = valid_round_type
)
```

Arguments

`row.name`	(`string` or `NULL`) row name. If `NULL`, an empty string is used as `row.name` of the `rrow()`.
`...`	values in vector/list form.
`format`	(`string`, `function`, or `list`) the format label (string) or formatter function to apply to the cell values passed via `....` See `formatters::list_valid_format_labels()` for currently supported format labels.
`indent`	**[Deprecated]**
`inset`	(`integer(1)`) the table inset for the row or table being constructed. See `formatters::table_inset()` for details.
`round_type`	(`"iec"`, `"iec_mod"` or `"sas"`) the type of rounding to perform. See `round_fmt()` for details.

Value

A row object of the context-appropriate type (label or data).

See Also

Other compatibility: `rheader()`, `rrow()`, `rtable()`

Examples

```
rrowl("a", c(1, 2, 3), format = "xx")
rrowl("a", c(1, 2, 3), c(4, 5, 6), format = "xx")


rrowl("N", table(iris$Species))
rrowl("N", table(iris$Species), format = "xx")

x <- tapply(iris$Sepal.Length, iris$Species, mean, simplify = FALSE)

rrow(row.name = "row 1", x)
rrow("ABC", 2, 3)

rrowl(row.name = "row 1", c(1, 2), c(3, 4))
rrow(row.name = "row 2", c(1, 2), c(3, 4))
```

---

rtable *Create a table*

Description

Create a table

Usage

```
rtable(
  header,
  ...,
  format = NULL,
  hsep = default_hsep(),
  inset = 0L,
  round_type = valid_round_type
)

rtablel(header, ..., format = NULL, hsep = default_hsep(), inset = 0L)
```

Arguments

header	(TableRow, character, or InstantiatedColumnInfo) information defining the header (column structure) of the table. This can be as row objects (legacy), character vectors, or an InstantiatedColumnInfo object.
...	rows to place in the table.
format	(string, function, or list) the format label (string) or formatter function to apply to the cell values passed via .... See formatters::list_valid_format_labels() for currently supported format labels.

hsep	(string) set of characters to be repeated as the separator between the header and body of the table when rendered as text. Defaults to a connected horizontal line (unicode 2014) in locals that use a UTF charset, and to - elsewhere (with a once per session warning). See formatters::set_default_hsep() for further information.
inset	(integer(1)) the table inset for the row or table being constructed. See formatters::table_inset() for details.
round_type	("iec", "iec_mod" or "sas") the type of rounding to perform. See round_fmt() for details.

Value

A formal table object of the appropriate type (ElementaryTable or TableTree).

See Also

Other compatibility: rheader(), rrow(), rrowl()

Examples

```
rtable(
  header = LETTERS[1:3],
  rrow("one to three", 1, 2, 3),
  rrow("more stuff", rcell(pi, format = "xx.xx"), "test", "and more")
)

# Table with multirow header

sel <- iris$Species == "setosa"
mtbl <- rtable(
  header = rheader(
    rrow(
      row.name = NULL, rcell("Sepal.Length", colspan = 2),
      rcell("Petal.Length", colspan = 2)
    ),
    rrow(NULL, "mean", "median", "mean", "median")
  ),
  rrow(
    row.name = "All Species",
    mean(iris$Sepal.Length), median(iris$Sepal.Length),
    mean(iris$Petal.Length), median(iris$Petal.Length),
    format = "xx.xx"
  ),
  rrow(
    row.name = "Setosa",
    mean(iris$Sepal.Length[sel]), median(iris$Sepal.Length[sel]),
    mean(iris$Petal.Length[sel]), median(iris$Petal.Length[sel])
  )
)
```

```
mtbl

names(mtbl) # always first row of header

# Single row header

tbl <- rtable(
  header = c("Treatement\nN=100", "Comparison\nN=300"),
  format = "xx (xx.xx%)",
  rrow("A", c(104, .2), c(100, .4)),
  rrow("B", c(23, .4), c(43, .5)),
  rrow(""),
  rrow("this is a very long section header"),
  rrow("estimate", rcell(55.23, "xx.xx", colspan = 2)),
  rrow("95% CI", indent = 1, rcell(c(44.8, 67.4), format = "(xx.x, xx.x)", colspan = 2))
)
tbl

row.names(tbl)
names(tbl)

# Subsetting

tbl[1, ]
tbl[, 1]

tbl[1, 2]
tbl[2, 1]

tbl[3, 2]
tbl[5, 1]
tbl[5, 2]

# Data Structure methods

dim(tbl)
nrow(tbl)
ncol(tbl)
names(tbl)

# Colspans

tbl2 <- rtable(
  c("A", "B", "C", "D", "E"),
  format = "xx",
  rrow("r1", 1, 2, 3, 4, 5),
  rrow("r2", rcell("sp2", colspan = 2), "sp1", rcell("sp2-2", colspan = 2))
)
tbl2
```

`sanitize_table_struct` *Sanitize degenerate table structures*

Description

[Experimental]

Experimental function to correct structure of degenerate tables by adding messaging rows to empty sub-structures.

Usage

```
sanitize_table_struct(tt, empty_msg = "-- This Section Contains No Data --")
```

Arguments

`tt`	(`TableTree`) a `TableTree` object.
`empty_msg`	(`string`) the string which should be spanned across the inserted empty rows.

Details

This function locates degenerate portions of the table (including the table overall in the case of a table with no data rows) and inserts a row which spans all columns with the message `empty_msg` at each one, generating a table guaranteed to be non-degenerate.

Value

If `tt` is already valid, it is returned unmodified. If `tt` is degenerate, a modified, non-degenerate version of the table is returned.

See Also

Other table structure validation functions: `find_degen_struct()`, `validate_table_struct()`

Examples

```
sanitize_table_struct(rtable("cool beans"))

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  summarize_row_groups()

## Degenerate because it doesn't have any analyze calls -> no data rows
badtab <- build_table(lyt, DM)
sanitize_table_struct(badtab)
```

section_div *Section dividers accessor and setter*

Description

section_div can be used to set or get the section divider for a table object produced by build_table(). When assigned in post-processing (section_div<-) the table can have a section divider after every row, each assigned independently. If assigning during layout creation, only split_rows_by() (and its related row-wise splits) and analyze() have a section_div parameter that will produce separators between split sections and data subgroups, respectively. These two approaches generally should not be mixed (see Details).

Usage

```
section_div(obj)

## S4 method for signature 'VTableTree'
section_div(obj)

## S4 method for signature 'list'
section_div(obj)

## S4 method for signature 'TableRow'
section_div(obj)

section_div(obj, only_sep_sections = FALSE) <- value

## S4 replacement method for signature 'VTableTree'
section_div(obj, only_sep_sections = FALSE) <- value

## S4 replacement method for signature 'TableRow'
section_div(obj, only_sep_sections = FALSE) <- value

header_section_div(obj)

## S4 method for signature 'PreDataTableLayouts'
header_section_div(obj)

## S4 method for signature 'VTableTree'
header_section_div(obj)

header_section_div(obj) <- value

## S4 replacement method for signature 'PreDataTableLayouts'
header_section_div(obj) <- value

## S4 replacement method for signature 'VTableTree'
```

```
header_section_div(obj) <- value

top_level_section_div(obj)

## S4 method for signature 'PreDataTableLayouts'
top_level_section_div(obj)

top_level_section_div(obj) <- value

## S4 replacement method for signature 'PreDataTableLayouts'
top_level_section_div(obj) <- value

section_div_info(obj)

section_div_at_path(obj, path, labelrow = FALSE)

section_div_at_path(
  obj,
  path,
  .prev_path = character(),
  labelrow = FALSE,
  tt_type = c("any", "row", "table", "elemtable")
) <- value
```

Arguments

obj	(VTableTree) table object. This can be of any class that inherits from VTableTree or TableRow/LabelRow.
only_sep_sections	(flag) defaults to FALSE for section_div<-. Allows you to set the section divider only for sections that are splits or analyses if the number of values is less than the number of rows in the table. If TRUE, the section divider will be set for all rows of the table.
value	(character) vector of strings to use as section dividers (a single string for section_div_at_path<-). Each string's character(s) are repeated to the full width of the printed table. Non-NA strings will result in a trailing separator at the associated location (see Details); values of NA_character_ result in no visible divider when the table is printed/exported. For section_div<-, value's length should the number of rows in obj, when only_sep_sections is FALSE and should be less than or equal to the maximum number of nested split/analyze steps anywhere in the layout corresponding to the table when only_sep_sections is TRUE. See the Details section below for more information.
path	(character) The path of the element(s) to set section_div(s) on. Can include '*' wildcards for section_div_at_path<- only.

labelrow (logical(1))
For section_div_at_path, when path leads to a subtable, indicates whether the section div be set/retrieved for the subtable (FALSE, the default) or the subtable's label row (TRUE). Ignored when path resolves to an individual row.

.prev_path (character)
Internal detail, do not manually set.

tt_type (character(1))
One of "any", "row", "table", "elemtable"; when testing existence or resolving a path with "*" wildcards, this indicates a restriction on *the final element the path resolves to*. E.g., for "table", possible paths which match the structure of the wild-card path but resolve to an individual row will not be considered matching. The value "elemtable" indicates an Elementary table, i.e., one representing a single variable within an analyze call.

Details

Section dividers provide visual breaks between structural elements of a table in row space. They are repeated to fill a full line of the table and printed after the element (row, subtable) they are associated with. Use a value of " " to display a blank line section divider in the table. A section divider of NA_character_ indicates no visible divider (i.e., no line at all) should be printed for that row or section when rendering the table.

When multiple section dividers would appear consecutively with no rows between them (e.g., a subtable and its last row both having a section divider set), only the *least specific* section divider (the subtable divider in this example) will be displayed when rendering the table. This is to avoid multiple non-informative lines of consecutive dividers when there is nested splitting in the row structure of a table.
section_div_at_path<- accepts a single path (which can include the '*' wildcard), and a single string in value and sets the section divider on the element(s) of obj that the path resolve to.

For section_div<- value should be a character vector. When you want to only affect sections or splits, please use only_sep_sections or provide a shorter vector than the number of rows. Ideally, the length of the vector should be less than the number of splits with, eventually, the leaf-level, i.e. DataRow where analyze results are. Note that if only one value is inserted, only the first split will be affected. If only_sep_sections = TRUE, which is the default for section_div() produced from the table construction, the section divider will be set for all the splits and eventually analyses, but not for the header or each row of the table. This can be set with header_section_div in basic_table() or, eventually, with hsep in build_table(). If only_sep_sections is FALSE, "section" dividers will be set for each row in the table *including content and label rows*.

In section_div<-, when only_sep_sections is FALSE *all higher order section divs are removed, even when new value for a row that they would apply to is* NA.

A section_div -> modify -> section_div<- workflow will not work to modify section dividers declared in a layout (i.e., with split_rows_by*(., section_div=) or analyze(.,section_div=)) after the table has been built. In that case a row 'inherits' its section divider behavior from the largest subtable that has a section divider set and for which it is the final row. Instead it clears the higher-order section dividers and sets an individual divider on each row (setting NA_character_ for rows that had no divider after them when rendering). This means that if pruning is done after the above process and the last row in a "section" is pruned, the last remaining row *will not inherit the section's divider* the way it would before the modification by section_div<-.

Generally it is advisable to use `section_div_at_path<-` - often with `"*"` wildcards in the path - to modify dividers declared in the layout instead of `section_div<-`. Alternatively, pruning should be done *before* calling `section_div<-` (when passing a a vector of length `nrow(tt)`), when a script or function will do both operations on a table.

Setting section_dividers for rows which do not currently inherit section divider behavior from a containing subtable will work as expected.

`section_div_info` returns a data.frame of section divider info (a subset of the result of `make_row_df` when called on a table tree or row object). This information can be used to reset section dividers at the correct path via `section_div_at_path` for tables which have section dividers deriving from their layout (which will be attached to subtables, rather than rows).

Value

The section divider string. Each line that does not have a trailing separator will have `NA_character_` as section divider.

For `section_div_info`, a dataframe containing `label`, `name`, "node_class", `path`, `trailing_sep` (the effective divider, whether inherited or not), `self_section_div` (the divider set on the row itself), and `sect_div_from_path` (the path to the table element the value in `trailing_sep` is inherited from, or `NA_character_` for label rows, which are not pathable).

Note

Section dividers which would appear after the last row of the table (ie those on the last row or last elementary subtable in the table) are never printed when rendering the table.

when called on an individual row object, `section_div` and `section_div<-` get and set the trialing divider for that row. In generally this is to be avoided; when manually constructing row objects, the `trailing_section_div` argument can set the trailing divider directly during creation.

See Also

`basic_table()` parameter `header_section_div` and `top_level_section_div` for global section dividers.

Examples

```
# Data
df <- data.frame(
  cat = c(
    "really long thing its so ", "long"
  ),
  value = c(6, 3, 10, 1)
)
fast_afun <- function(x) list("m" = rcell(mean(x), format = "xx."), "m/2" = max(x) / 2)

tbl <- basic_table() |>
  split_rows_by("cat", section_div = "~") |>
  analyze("value", afun = fast_afun, section_div = " ") |>
  build_table(df)
```

```
# Getter
section_div(tbl)

# Setter
section_div(tbl) <- letters[seq_len(nrow(tbl))]
tbl

# last letter can appear if there is another table
rbind(tbl, tbl)

# header_section_div
header_section_div(tbl) <- "+"
tbl
```

`sf_args` *Split function argument conventions*

Description

Split function argument conventions

Usage

```
sf_args(trim, label, first)
```

Arguments

`trim`	(`flag`) whether splits corresponding with 0 observations should be kept when tabulating.
`label`	(`string`) a label (not to be confused with the name) for the object/structure.
`first`	(`flag`) whether the created split level should be placed first in the levels (`TRUE`) or last (`FALSE`, the default).

Value

No return value.

See Also

Other conventions: `compat_args()`, `constr_args()`, `gen_args()`, `lyt_args()`

`simple_analysis` *Default tabulation*

Description

This function is used when `analyze()` is invoked.

Usage

```
simple_analysis(x, ...)

## S4 method for signature 'numeric'
simple_analysis(x, ...)

## S4 method for signature 'logical'
simple_analysis(x, ...)

## S4 method for signature 'factor'
simple_analysis(x, ...)

## S4 method for signature 'ANY'
simple_analysis(x, ...)
```

Arguments

`x`	(`vector`) the *already split* data being tabulated for a particular cell/set of cells.
`...`	additional parameters to pass on.

Details

This function has the following behavior given particular types of inputs:

numeric calls `mean()` on `x`.

logical calls `sum()` on `x`.

factor calls `length()` on `x`.

The `in_rows()` function is called on the resulting value(s). All other classes of input currently lead to an error.

Value

A `RowsVerticalSection` object (or `NULL`). The details of this object should be considered an internal implementation detail.

Author(s)

Gabriel Becker and Adrian Waddell

Examples

```
simple_analysis(1:3)
simple_analysis(iris$Species)
simple_analysis(iris$Species == "setosa")
```

`sort_at_path` *Sorting a table at a specific path*

Description

Main sorting function to order the sub-structure of a `TableTree` at a particular path in the table tree.

Usage

```
sort_at_path(
  tt,
  path,
  scorefun,
  decreasing = NA,
  na.pos = c("omit", "last", "first"),
  .prev_path = character(),
  ...
)
```

Arguments

`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`path`	(`character`) a vector path for a position within the structure of a `TableTree`. Each element represents a subsequent choice amongst the children of the previous choice.
`scorefun`	(`function`) scoring function. Should accept the type of children directly under the position at `path` (either `VTableTree`, `VTableRow`, or `VTableNodeInfo`, which covers both) and return a numeric value to be sorted.
`decreasing`	(`flag`) whether the scores generated by `scorefun` should be sorted in decreasing order. If unset (the default of `NA`), it is set to `TRUE` if the generated scores are numeric and `FALSE` if they are characters.
`na.pos`	(`string`) what should be done with children (sub-trees/rows) with `NA` scores. Defaults to `"omit"`, which removes them. Other allowed values are `"last"` and `"first"`, which indicate where `NA` scores should be placed in the order.
`.prev_path`	(`character`) internal detail, do not set manually.

... Additional (named) arguments that will be passed directly down to score_fun *if* it accepts them (or accepts ... itself).

Details

sort_at_path, given a path, locates the (sub)table(s) described by the path (see below for handling of the "*" wildcard). For each such subtable, it then calls scorefun on each direct child of the table, using the resulting scores to determine their sorted order. tt is then modified to reflect each of these one or more sorting operations.

score_fun can optionally accept decreasing, which will be passed the value passed to sort_at_path automatically, and other arguments which can be set via .... The first argument passed to scorefun will always be the table structure (subtable or row) it is scoring.

In path, a leading "root" element will be ignored, regardless of whether this matches the object name (and thus actual root path name) of tt. Including "root" in paths where it does not match the name of tt may mask deeper misunderstandings of how valid paths within a TableTree object correspond to the layout used to originally declare it, which we encourage users to avoid.

path can include the "wildcard" "*" as a step, which translates roughly to *any* node/branching element and means that each child at that step will be *separately* sorted based on scorefun and the remaining path entries. This can occur multiple times in a path.

A list of valid (non-wildcard) paths can be seen in the path column of the data.frame created by formatters::make_row_df() with the visible_only argument set to FALSE. It can also be inferred from the summary given by table_structure().

Note that sorting needs a deeper understanding of table structure in rtables. Please consider reading the related vignette (Sorting and Pruning) and explore table structure with useful functions like table_structure() and row_paths_summary(). It is also very important to understand the difference between "content" rows and "data" rows. The first one analyzes and describes the split variable generally and is generated with summarize_row_groups(), while the second one is commonly produced by calling one of the various analyze() instances.

Built-in score functions are cont_n_allcols() and cont_n_onecol(). They are both working with content rows (coming from summarize_row_groups()) while a custom score function needs to be used on DataRows. Here, some useful descriptor and accessor functions (coming from related vignette):

- cell_values() - Retrieves a named list of a TableRow or TableTree object's values.
- formatters::obj_name() - Retrieves the name of an object. Note this can differ from the label that is displayed (if any is) when printing.
- formatters::obj_label() - Retrieves the display label of an object. Note this can differ from the name that appears in the path.
- content_table() - Retrieves a TableTree object's content table (which contains its summary rows).
- tree_children() - Retrieves a TableTree object's direct children (either subtables, rows or possibly a mix thereof, though that should not happen in practice).

Value

A TableTree with the same structure as tt with the exception that the requested sorting has been done at path.

See Also

- Score functions cont_n_allcols() and cont_n_onecol().
- formatters::make_row_df() and table_structure() for pathing information.
- tt_at_path() to select a table's (sub)structure at a given path.

Examples

```
# Creating a table to sort

# Function that gives two statistics per table-tree "leaf"
more_analysis_fnc <- function(x) {
  in_rows(
    "median" = median(x),
    "mean" = mean(x),
    .formats = "xx.x"
  )
}

# Main layout of the table
raw_lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by(
    "RACE",
    split_fun = drop_and_remove_levels("WHITE") # dropping WHITE levels
  ) |>
  summarize_row_groups() |>
  split_rows_by("STRATA1") |>
  summarize_row_groups() |>
  analyze("AGE", afun = more_analysis_fnc)

# Creating the table and pruning empty and NAs
tbl <- build_table(raw_lyt, DM) |>
  prune_table()

# Peek at the table structure to understand how it is built
table_structure(tbl)

#  Sorting only ASIAN sub-table, or, in other words, sorting STRATA elements for
# the ASIAN group/row-split. This uses content_table() accessor function as it
# is a "ContentRow". In this case, we also base our sorting only on the second column.
sort_at_path(tbl, c("ASIAN", "STRATA1"), cont_n_onecol(2))

# Custom scoring function that is working on "DataRow"s
scorefun <- function(tt) {
  # Here we could use browser()
  sum(unlist(row_values(tt))) # Different accessor function
}
# Sorting mean and median for all the AGE leaves!
sort_at_path(tbl, c("RACE", "*", "STRATA1", "*", "AGE"), scorefun)

last_cat_scorefun <- function(x, decreasing, lastcat) {
```

```
  mycat <- obj_name(x)
  if (mycat == lastcat) {
    ifelse(isTRUE(decreasing), -Inf, Inf)
  } else {
    match(tolower(substr(mycat, 1, 1)), letters)
  }
}

lyt2 <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE")

tbl2 <- build_table(lyt2, DM)
sort_at_path(tbl2, "SEX", last_cat_scorefun, lastcat = "M")
sort_at_path(tbl2, "SEX", last_cat_scorefun, lastcat = "M", decreasing = FALSE)
```

`spl_context` *.spl_context within analysis and split functions*

Description

`.spl_context` is an optional parameter for any of rtables' special functions, i.e. `afun` (analysis function in `analyze()`), `cfun` (content or label function in `summarize_row_groups()`), or `split_fun` (e.g. for `split_rows_by()`).

Details

The `.spl_context` `data.frame` gives information about the subsets of data corresponding to the splits within which the current `analyze` action is nested. Taken together, these correspond to the path that the resulting (set of) rows the analysis function is creating, although the information is in a slightly different form. Each split (which correspond to groups of rows in the resulting table), as well as the initial 'root' "split", is represented via the following columns:

split The name of the split (often the variable being split).

value The string representation of the value at that split (`split`).

full_parent_df A `data.frame` containing the full data (i.e. across all columns) corresponding to the path defined by the combination of `split` and `value` of this row *and all rows above this row*.

all_cols_n The number of observations corresponding to the row grouping (union of all columns).

column for each column in the table structure (*row-split and analyze contexts only*) These list columns (named the same as `names(col_exprs(tab))`) contain logical vectors corresponding to the subset of this row's `full_parent_df` corresponding to the column.

cur_col_id Identifier of the current column. This may be an internal name, constructed by pasting the column path together.

cur_col_subset List column containing logical vectors indicating the subset of this row's `full_parent_df` for the column currently being created by the analysis function.

cur_col_expr List of current column expression. This may be used to filter `.alt_df_row`, or any external data, by column. Filtering `.alt_df_row` by columns produces `.alt_df`.

cur_col_n Integer column containing the observation counts for that split.

cur_col_split Current column split names. This is recovered from the current column path.

cur_col_split_val Current column split values. This is recovered from the current column path.

Note

Within analysis functions that accept `.spl_context`, the `all_cols_n` and `cur_col_n` columns of the data frame will contain the 'true' observation counts corresponding to the row-group and row-group x column subsets of the data. These numbers will not, and currently cannot, reflect alternate column observation counts provided by the `alt_counts_df`, `col_counts` or `col_total` arguments to `build_table()`.

`spl_context_to_disp_path` *Translate spl_context to a path to display in error messages*

Description

Translate spl_context to a path to display in error messages

Usage

```
spl_context_to_disp_path(ctx)
```

Arguments

`ctx`	(`data.frame`) the `spl_context` data frame where the error occurred.

Value

A character string containing a description of the row path corresponding to `ctx`.

spl_variable *Variable associated with a split*

Description

This function is intended for use when writing custom splitting logic. In cases where the split is associated with a single variable, the name of that variable will be returned. At time of writing this includes splits generated via the split_rows_by(), split_cols_by(), split_rows_by_cuts(), split_cols_by_cuts(), split_rows_by_cutfun(), and split_cols_by_cutfun() layout directives.

Usage

```
spl_variable(spl)

## S4 method for signature 'VarLevelSplit'
spl_variable(spl)

## S4 method for signature 'VarDynCutSplit'
spl_variable(spl)

## S4 method for signature 'VarStaticCutSplit'
spl_variable(spl)

## S4 method for signature 'Split'
spl_variable(spl)
```

Arguments

spl	(VarLevelSplit) the split object.

Value

For splits with a single variable associated with them, returns the split. Otherwise, an error is raised.

See Also

make_split_fun

split_cols_by *Declaring a column-split based on levels of a variable*

Description

Will generate children for each subset of a categorical variable.

Usage

```
split_cols_by(
  lyt,
  var,
  labels_var = var,
  split_label = var,
  split_fun = NULL,
  format = NULL,
  nested = TRUE,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  ref_group = NULL,
  show_colcounts = FALSE,
  colcount_format = NULL
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
var	(string) variable name.
labels_var	(string) name of variable containing labels to be displayed for the values of var.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
split_fun	(function or NULL) custom splitting function. See custom_split_funs.
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.

`nested` (`logical`)
whether this layout instruction should be applied within the existing layout structure *if possible* (`TRUE`, the default) or as a new top-level element (`FALSE`). Ignored if it would nest a split underneath analyses, which is not allowed.

`child_labels` (`string`)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts `"default"`, `"visible"`, and `"hidden"`. Defaults to `"default"` which flags the label row as visible only if the child has 0 content rows.

`extra_args` (`list`)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

`ref_group` (`string` or `NULL`)
level of `var` that should be considered `ref_group`/reference.

`show_colcounts` (`logical(1)`)
should column counts be displayed at the level facets created by this split. Defaults to `FALSE`.

`colcount_format`
(`character(1)`)
if `show_colcounts` is `TRUE`, the format which should be used to display column counts for facets generated by this split. Defaults to `"(N=xx)"`.

Value

A `PreDataTableLayouts` object suitable for passing to further layouting functions, and to `build_table()`.

Custom Splitting Function Details

User-defined custom split functions can perform any type of computation on the incoming data provided that they meet the requirements for generating "splits" of the incoming data based on the split object.

Split functions are functions that accept:

df a `data.frame` of incoming data to be split.

spl a Split object. This is largely an internal detail custom functions will not need to worry about, but `obj_name(spl)`, for example, will give the name of the split as it will appear in paths in the resulting table.

vals any pre-calculated values. If given non-`NULL` values, the values returned should match these. Should be `NULL` in most cases and can usually be ignored.

labels any pre-calculated value labels. Same as above for `values`.

trim if `TRUE`, resulting splits that are empty are removed.

(optional) .spl_context a `data.frame` describing previously performed splits which collectively arrived at `df`.

The function must then output a named `list` with the following elements:

values the vector of all values corresponding to the splits of `df`.

datasplit a list of `data.frames` representing the groupings of the actual observations from `df`.

labels a character vector giving a string label for each value listed in the `values` element above.

(optional) extras if present, extra arguments are to be passed to summary and analysis functions whenever they are executed on the corresponding element of `datasplit` or a subset thereof.

One way to generate custom splitting functions is to wrap existing split functions and modify either the incoming data before they are called or their outputs.

Author(s)

Gabriel Becker

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  analyze(c("AGE", "BMRKR2"))

tbl <- build_table(lyt, ex_adsl)
tbl

# Let's look at the splits in more detail

lyt1 <- basic_table() |> split_cols_by("ARM")
lyt1

# add an analysis (summary)
lyt2 <- lyt1 |>
  analyze(c("AGE", "COUNTRY"),
    afun = list_wrap_x(summary),
    format = "xx.xx"
  )
lyt2

tbl2 <- build_table(lyt2, DM)
tbl2


# By default sequentially adding layouts results in nesting
library(dplyr)

DM_MF <- DM |>
  filter(SEX %in% c("M", "F")) |>
  mutate(SEX = droplevels(SEX))

lyt3 <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  analyze(c("AGE", "COUNTRY"),
    afun = list_wrap_x(summary),
```

```
    format = "xx.xx"
  )
lyt3

tbl3 <- build_table(lyt3, DM_MF)
tbl3

# nested=TRUE vs not
lyt4 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX", split_fun = drop_split_levels) |>
  split_rows_by("RACE", split_fun = drop_split_levels) |>
  analyze("AGE")
lyt4

tbl4 <- build_table(lyt4, DM)
tbl4

lyt5 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX", split_fun = drop_split_levels) |>
  analyze("AGE") |>
  split_rows_by("RACE", nested = FALSE, split_fun = drop_split_levels) |>
  analyze("AGE")
lyt5

tbl5 <- build_table(lyt5, DM)
tbl5
```

`split_cols_by_cuts` *Split on static or dynamic cuts of the data*

Description

Create columns (or row splits) based on values (such as quartiles) of `var`.

Usage

```
split_cols_by_cuts(
  lyt,
  var,
  cuts,
  cutlabels = NULL,
  split_label = var,
  nested = TRUE,
  cumulative = FALSE,
  show_colcounts = FALSE,
  colcount_format = NULL
```

```
)

split_rows_by_cuts(
  lyt,
  var,
  cuts,
  cutlabels = NULL,
  split_label = var,
  parent_name = var,
  format = NULL,
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  cumulative = FALSE,
  label_pos = if (!is.null(at_sibling)) "visible" else "default",
  section_div = NA_character_
)

split_cols_by_cutfun(
  lyt,
  var,
  cutfun = qtile_cuts,
  cutlabelfun = function(x) NULL,
  split_label = var,
  nested = TRUE,
  extra_args = list(),
  cumulative = FALSE,
  show_colcounts = FALSE,
  colcount_format = NULL
)

split_cols_by_quartiles(
  lyt,
  var,
  split_label = var,
  nested = TRUE,
  extra_args = list(),
  cumulative = FALSE,
  show_colcounts = FALSE,
  colcount_format = NULL
)

split_rows_by_quartiles(
  lyt,
  var,
  split_label = var,
  parent_name = var,
  format = NULL,
```

```
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  cumulative = FALSE,
  indent_mod = 0L,
  label_pos = if (!is.null(at_sibling)) "visible" else "default",
  section_div = NA_character_
)

split_rows_by_cutfun(
  lyt,
  var,
  cutfun = qtile_cuts,
  cutlabelfun = function(x) NULL,
  split_label = var,
  parent_name = var,
  format = NULL,
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  cumulative = FALSE,
  indent_mod = 0L,
  label_pos = if (!is.null(at_sibling)) "visible" else "default",
  section_div = NA_character_
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
var	(string) variable name.
cuts	(numeric) cuts to use.
cutlabels	(character or NULL) labels for the cuts.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
nested	(logical) whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.

cumulative (flag)
whether the cuts should be treated as cumulative. Defaults to FALSE.

show_colcounts (logical(1))
should column counts be displayed at the level facets created by this split. Defaults to FALSE.

colcount_format
(character(1))
if show_colcounts is TRUE, the format which should be used to display column counts for facets generated by this split. Defaults to "(N=xx)".

parent_name (character(1))
Name to assign to the table corresponding to the *split* or *group of sibling analyses*, for split_rows_by* and analyze* when analyzing more than one variable, respectively. Ignored when analyzing a single variable.

format (string, function, or list)
format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.

na_str (string)
string that should be displayed when the value of x is missing. Defaults to "NA".

at_sibling (character(1) or NULL)
If non-null, a preceding split or analyze to anchor this instruction to as a direct sibling. Cannot select an instruction that is downstream of a point where a previously used anchor (See Nesting Anchor Resolution for details).

label_pos (string)
location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

cutfun (function)
function which accepts the *full vector* of var values and returns cut points to be used (via cut) when splitting data during tabulation.

cutlabelfun (function)
function which returns either labels for the cuts or NULL when passed the return value of cutfun.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

child_labels (string)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

Details

For dynamic cuts, the cut is transformed into a static cut by build_table() *based on the full dataset*, before proceeding. Thus even when nested within another split in column/row space, the resulting split will reflect the overall values (e.g., quartiles) in the dataset, NOT the values for subset it is nested under.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Nesting Anchor Resolution

When nested is TRUE, at_sibling allows you to set a *nesting anchor* that your new split_rows_by* or analyze* directive should be placed as a sibling to. The lookup for this anchor occurs *only in the currently active top-level nesting stack*, meaning the directives that have occurred since the last split or analysis with nested == FALSE.

Furthermore, resolution occurs against the first element of each arm of a branching point caused by any previous uses of at_sibling but *only descends into the last arm*.

So for example if our previous layout was generated via:

```
lyt <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR2", nested = FALSE) |>
  split_rows_by("RACE") |>
  analyze("AGE") |>
  split_rows_by("SEX", at_sibling = "RACE") |>
  analyze("BMRKR1")
```

The eligible anchor points would be "BMRKR2", "RACE", "SEX" and "BMRKR1". "AGE" is masked by the branching caused by anchoring our SEX split on RACE.

Finally, while at_sibling does support de-duplication of "<name>[i]" anchors, it does so **within the set of available anchors**, which can be counter-intuitive. It is strongly suggested that the parent_name and table_names argument(s) of split_rows_by* and analyze be used to prevent the need for this. at_sibling will resolve to table names overridden in this manner.

Author(s)

Gabriel Becker

Examples

```
library(dplyr)

# split_cols_by_cuts
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_cuts("AGE",
    split_label = "Age",
    cuts = c(0, 25, 35, 1000),
    cutlabels = c("young", "medium", "old")
  ) |>
  analyze(c("BMRKR2", "STRATA2")) |>
  append_topleft("counts")

tbl <- build_table(lyt, ex_adsl)
tbl

# split_rows_by_cuts
lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by_cuts("AGE",
    split_label = "Age",
    cuts = c(0, 25, 35, 1000),
    cutlabels = c("young", "medium", "old")
  ) |>
  analyze(c("BMRKR2", "STRATA2")) |>
  append_topleft("counts")


tbl2 <- build_table(lyt2, ex_adsl)
tbl2

# split_cols_by_quartiles

lyt3 <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_quartiles("AGE", split_label = "Age") |>
  analyze(c("BMRKR2", "STRATA2")) |>
  append_topleft("counts")

tbl3 <- build_table(lyt3, ex_adsl)
tbl3

# split_rows_by_quartiles
lyt4 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM") |>
  split_rows_by_quartiles("AGE", split_label = "Age") |>
  analyze("BMRKR2") |>
  append_topleft(c("Age Quartiles", " Counts BMRKR2"))

tbl4 <- build_table(lyt4, ex_adsl)
tbl4
```

```
# split_cols_by_cutfun
cutfun <- function(x) {
  cutpoints <- c(
    min(x),
    mean(x),
    max(x)
  )

  names(cutpoints) <- c("", "Younger", "Older")
  cutpoints
}

lyt5 <- basic_table() |>
  split_cols_by_cutfun("AGE", cutfun = cutfun) |>
  analyze("SEX")

tbl5 <- build_table(lyt5, ex_adsl)
tbl5

# split_rows_by_cutfun
lyt6 <- basic_table() |>
  split_cols_by("SEX") |>
  split_rows_by_cutfun("AGE", cutfun = cutfun) |>
  analyze("BMRKR2")

tbl6 <- build_table(lyt6, ex_adsl)
tbl6
```

`split_cols_by_multivar` *Associate multiple variables with columns*

Description

In some cases, the variable to be ultimately analyzed is most naturally defined on a column, not a row, basis. When we need columns to reflect different variables entirely, rather than different levels of a single variable, we use `split_cols_by_multivar`.

Usage

```
split_cols_by_multivar(
  lyt,
  vars,
  split_fun = NULL,
  varlabels = vars,
  varnames = NULL,
  nested = TRUE,
```

```
  extra_args = list(),
  show_colcounts = FALSE,
  colcount_format = NULL
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
vars	(character) vector of variable names.
split_fun	(function or NULL) custom splitting function. See custom_split_funs.
varlabels	(character) vector of labels for vars.
varnames	(character) vector of names for vars which will appear in pathing. When vars are all unique this will be the variable names. If not, these will be variable names with suffixes as necessary to enforce uniqueness.
nested	(logical) whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.
extra_args	(list) extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.
show_colcounts	(logical(1)) should column counts be displayed at the level facets created by this split. Defaults to FALSE.
colcount_format	(character(1)) if show_colcounts is TRUE, the format which should be used to display column counts for facets generated by this split. Defaults to "(N=xx)".

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Author(s)

Gabriel Becker

See Also

analyze_colvars()

Examples

```
library(dplyr)

ANL <- DM |> mutate(value = rnorm(n()), pctdiff = runif(n()))

## toy example where we take the mean of the first variable and the
## count of >.5 for the second.
colfuns <- list(
  function(x) in_rows(mean = mean(x), .formats = "xx.x"),
  function(x) in_rows("# x > 5" = sum(x > .5), .formats = "xx")
)

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by_multivar(c("value", "pctdiff")) |>
  split_rows_by("RACE",
    split_label = "ethnicity",
    split_fun = drop_split_levels
  ) |>
  summarize_row_groups() |>
  analyze_colvars(afun = colfuns)
lyt

tbl <- build_table(lyt, ANL)
tbl
```

---

split_funcs *Split functions*

Description

This is a collection of useful, default split function that can help you in dividing the data, hence the table rows or columns, into different parts or groups (splits). You can also create your own split function if you need to create a custom division as specific as you need. Please consider reading custom_split_funs if this is the case. Beyond this list of functions, you can also use `add_overall_level()` and `add_combo_levels()` for adding or modifying levels and `trim_levels_to_map()` to provide possible level combinations to filter the split with.

Usage

```
keep_split_levels(only, reorder = TRUE)

remove_split_levels(excl)

drop_split_levels(df, spl, vals = NULL, labels = NULL, trim = FALSE)

drop_and_remove_levels(excl)
```

```
reorder_split_levels(neworder, newlabels = neworder, drlevels = TRUE)

trim_levels_in_group(innervar, drop_outlevs = TRUE)
```

Arguments

only	(character) levels to retain (all others will be dropped). If none of the levels is present an empty table is returned.
reorder	(flag) whether the order of only should be used as the order of the children of the split. Defaults to TRUE.
excl	(character) levels to be excluded (they will not be reflected in the resulting table structure regardless of presence in the data).
df	(data.frame or tibble) dataset.
spl	(Split) a Split object defining a partitioning or analysis/tabulation of the data.
vals	(ANY) for internal use only.
labels	(character) labels to use for the remaining levels instead of the existing ones.
trim	(flag) whether splits corresponding with 0 observations should be kept when tabulating.
neworder	(character) new order of factor levels. All need to be present in the data. To add empty levels, rely on pre-processing or create your custom_split_funs.
newlabels	(character) labels for (new order of) factor levels. If named, the levels are matched. Otherwise, the order of neworder is used.
drlevels	(flag) whether levels that are not in neworder should be dropped. Default is TRUE. Note: drlevels = TRUE does not drop levels that are not originally in the data. Rely on pre-processing or use a combination of split functions with make_split_fun() to also drop unused levels.
innervar	(string) variable whose factor levels should be trimmed (e.g. empty levels dropped) *separately within each grouping defined at this point in the structure*.
drop_outlevs	(flag) whether empty levels in the variable being split on (i.e. the "outer" variable, not innervar) should be dropped. Defaults to TRUE.

Value

A function that can be used to split the data accordingly. The actual function signature is similar to the one you can define when creating a fully custom one. For more details see custom_split_funs.

Functions

- `keep_split_levels()`: keeps only specified levels (`only`) in the split variable. If any of the specified levels is not present, an error is returned. `reorder` = `TRUE` (the default) orders the split levels according to the order of `only`.
- `remove_split_levels()`: Removes specified levels (`excl`) from the split variable. Nothing done if not in data.
- `drop_split_levels()`: Drops levels that have no representation in the data.
- `drop_and_remove_levels()`: Removes specified levels `excl` and drops all levels that are not in the data.
- `reorder_split_levels()`: Reorders split levels following `neworder`, which needs to be of same size as the levels in data.
- `trim_levels_in_group()`: Takes the split groups and removes levels of `innervar` if not present in those split groups. If you want to specify a filter of possible combinations, please consider using `trim_levels_to_map()`.

Note

The following parameters are also documented here but they are only the default signature of a split function: `df` (data to be split), `spl` (split object), and `vals` = `NULL`, `labels` = `NULL`, `trim` = `FALSE` (last three only for internal use). See custom_split_funs for more details and `make_split_fun()` for a more advanced API.

See Also

custom_split_funs, `add_overall_level()`, `add_combo_levels()`, and `trim_levels_to_map()`.

Examples

```
# keep_split_levels keeps specified levels (reorder = TRUE by default)
lyt <- basic_table() |>
  split_rows_by("COUNTRY",
    split_fun = keep_split_levels(c("USA", "CAN", "BRA"))
  ) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# remove_split_levels removes specified split levels
lyt <- basic_table() |>
  split_rows_by("COUNTRY",
    split_fun = remove_split_levels(c(
      "USA", "CAN",
      "CHE", "BRA"
```

```
    ))
  ) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# drop_split_levels drops levels that are not present in the data
lyt <- basic_table() |>
  split_rows_by("SEX", split_fun = drop_split_levels) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# Removing "M" and "U" directly, then "UNDIFFERENTIATED" because not in data
lyt <- basic_table() |>
  split_rows_by("SEX", split_fun = drop_and_remove_levels(c("M", "U"))) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# Reordering levels in split variable
lyt <- basic_table() |>
  split_rows_by(
    "SEX",
    split_fun = reorder_split_levels(
      neworder = c("U", "F"),
      newlabels = c(U = "Uu", `F` = "Female")
    )
  ) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# Reordering levels in split variable but keeping all the levels
lyt <- basic_table() |>
  split_rows_by(
    "SEX",
    split_fun = reorder_split_levels(
      neworder = c("U", "F"),
      newlabels = c("Uu", "Female"),
      drlevels = FALSE
    )
  ) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
tbl

# trim_levels_in_group() trims levels within each group defined by the split variable
```

```
dat <- data.frame(
  col1 = factor(c("A", "B", "C"), levels = c("A", "B", "C", "N")),
  col2 = factor(c("a", "b", "c"), levels = c("a", "b", "c", "x"))
) # N is removed if drop_outlevs = TRUE, x is removed always

tbl <- basic_table() |>
  split_rows_by("col1", split_fun = trim_levels_in_group("col2")) |>
  analyze("col2") |>
  build_table(dat)
tbl
```

---

split_rows_by *Add rows according to levels of a variable*

Description

Add rows according to levels of a variable

Usage

```
split_rows_by(
  lyt,
  var,
  labels_var = var,
  split_label = var,
  split_fun = NULL,
  parent_name = var,
  format = NULL,
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  child_labels = c("default", "visible", "hidden"),
  label_pos = if (!is.null(at_sibling)) "visible" else "default",
  indent_mod = 0L,
  page_by = FALSE,
  page_prefix = split_label,
  section_div = NA_character_
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
var	(string) variable name.
labels_var	(string) name of variable containing labels to be displayed for the values of var.

split_label (string)
label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).

split_fun (function or NULL)
custom splitting function. See custom_split_funs.

parent_name (character(1))
Name to assign to the table corresponding to the *split* or *group of sibling analyses*, for split_rows_by* and analyze* when analyzing more than one variable, respectively. Ignored when analyzing a single variable.

format (string, function, or list)
format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.

na_str (string)
string that should be displayed when the value of x is missing. Defaults to "NA".

nested (logical)
whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.

at_sibling (character(1) or NULL)
If non-null, a preceding split or analyze to anchor this instruction to as a direct sibling. Cannot select an instruction that is downstream of a point where a previously used anchor (See Nesting Anchor Resolution for details).

child_labels (string)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.

label_pos (string)
location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

page_by (flag)
whether pagination should be forced between different children resulting from this split. An error will occur if the selected split does not contain at least one value that is not NA.

page_prefix (string)
prefix to be appended with the split value when forcing pagination between the children of a split/table.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Nesting Anchor Resolution

When nested is TRUE, at_sibling allows you to set a *nesting anchor* that your new split_rows_by* or analyze* directive should be placed as a sibling to. The lookup for this anchor occurs *only in the currently active top-level nesting stack*, meaning the directives that have occurred since the last split or analysis with nested == FALSE.

Furthermore, resolution occurs against the first element of each arm of a branching point caused by any previous uses of at_sibling but *only descends into the last arm*.

So for example if our previous layout was generated via:

```
lyt <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR2", nested = FALSE) |>
  split_rows_by("RACE") |>
  analyze("AGE") |>
  split_rows_by("SEX", at_sibling = "RACE") |>
  analyze("BMRKR1")
```

The eligible anchor points would be "BMRKR2", "RACE", "SEX" and "BMRKR1". "AGE" is masked by the branching caused by anchoring our SEX split on RACE.

Finally, while at_sibling does support de-duplication of "<name>[i]" anchors, it does so **within the set of available anchors**, which can be counter-intuitive. It is strongly suggested that the parent_name and table_names argument(s) of split_rows_by* and analyze be used to prevent the need for this. at_sibling will resolve to table names overridden in this manner.

Custom Splitting Function Details

User-defined custom split functions can perform any type of computation on the incoming data provided that they meet the requirements for generating "splits" of the incoming data based on the split object.

Split functions are functions that accept:

df a data.frame of incoming data to be split.

spl a Split object. This is largely an internal detail custom functions will not need to worry about, but obj_name(spl), for example, will give the name of the split as it will appear in paths in the resulting table.

vals any pre-calculated values. If given non-NULL values, the values returned should match these. Should be NULL in most cases and can usually be ignored.

labels any pre-calculated value labels. Same as above for `values`.

trim if `TRUE`, resulting splits that are empty are removed.

(optional) .spl_context a `data.frame` describing previously performed splits which collectively arrived at `df`.

The function must then output a named `list` with the following elements:

values the vector of all values corresponding to the splits of `df`.

datasplit a list of `data.frames` representing the groupings of the actual observations from `df`.

labels a character vector giving a string label for each value listed in the `values` element above.

(optional) extras if present, extra arguments are to be passed to summary and analysis functions whenever they are executed on the corresponding element of `datasplit` or a subset thereof.

One way to generate custom splitting functions is to wrap existing split functions and modify either the incoming data before they are called or their outputs.

Note

If `var` is a factor with empty unobserved levels and `labels_var` is specified, it must also be a factor with the same number of levels as `var`. Currently the error that occurs when this is not the case is not very informative, but that will change in the future.

Author(s)

Gabriel Becker

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("RACE", split_fun = drop_split_levels) |>
  analyze("AGE", mean, var_labels = "Age", format = "xx.xx")

tbl <- build_table(lyt, DM)
tbl

lyt2 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("RACE") |>
  analyze("AGE", mean, var_labels = "Age", format = "xx.xx")

tbl2 <- build_table(lyt2, DM)
tbl2

lyt3 <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  summarize_row_groups(label_fstr = "Overall (N)") |>
  split_rows_by("RACE",
    split_label = "Ethnicity", labels_var = "ethn_lab",
```

```
    split_fun = drop_split_levels
  ) |>
  summarize_row_groups("RACE", label_fstr = "%s (n)") |>
  analyze("AGE", var_labels = "Age", afun = mean, format = "xx.xx")

lyt3


library(dplyr)

DM2 <- DM |>
  filter(SEX %in% c("M", "F")) |>
  mutate(
    SEX = droplevels(SEX),
    gender_lab = c(
      "F" = "Female", "M" = "Male",
      "U" = "Unknown",
      "UNDIFFERENTIATED" = "Undifferentiated"
    )[SEX],
    ethn_lab = c(
      "ASIAN" = "Asian",
      "BLACK OR AFRICAN AMERICAN" = "Black or African American",
      "WHITE" = "White",
      "AMERICAN INDIAN OR ALASKA NATIVE" = "American Indian or Alaska Native",
      "MULTIPLE" = "Multiple",
      "NATIVE HAWAIIAN OR OTHER PACIFIC ISLANDER" =
        "Native Hawaiian or Other Pacific Islander",
      "OTHER" = "Other", "UNKNOWN" = "Unknown"
    )[RACE]
  )

tbl3 <- build_table(lyt3, DM2)
tbl3
```

`split_rows_by_multivar` *Associate multiple variables with rows*

Description

When we need rows to reflect different variables rather than different levels of a single variable, we use `split_rows_by_multivar`.

Usage

```
split_rows_by_multivar(
  lyt,
  vars,
  split_fun = NULL,
```

```
  split_label = "",
  varlabels = vars,
  parent_name = "multivars",
  format = NULL,
  na_str = NA_character_,
  nested = TRUE,
  at_sibling = NULL,
  child_labels = c("default", "visible", "hidden"),
  indent_mod = 0L,
  section_div = NA_character_,
  extra_args = list()
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
vars	(character) vector of variable names.
split_fun	(function or NULL) custom splitting function. See custom_split_funs.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
varlabels	(character) vector of labels for vars.
parent_name	(character(1)) Name to assign to the table corresponding to the *split* or *group of sibling analyses*, for split_rows_by* and analyze* when analyzing more than one variable, respectively. Ignored when analyzing a single variable.
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".
nested	(logical) whether this layout instruction should be applied within the existing layout structure *if possible* (TRUE, the default) or as a new top-level element (FALSE). Ignored if it would nest a split underneath analyses, which is not allowed.
at_sibling	(character(1) or NULL) If non-null, a preceding split or analyze to anchor this instruction to as a direct sibling. Cannot select an instruction that is downstream of a point where a previously used anchor (See Nesting Anchor Resolution for details).

child_labels (string)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

Value

A PreDataTableLayouts object suitable for passing to further layouting functions, and to build_table().

Nesting Anchor Resolution

When nested is TRUE, at_sibling allows you to set a *nesting anchor* that your new split_rows_by* or analyze* directive should be placed as a sibling to. The lookup for this anchor occurs *only in the currently active top-level nesting stack*, meaning the directives that have occurred since the last split or analysis with nested == FALSE.

Furthermore, resolution occurs against the first element of each arm of a branching point caused by any previous uses of at_sibling but *only descends into the last arm*.

So for example if our previous layout was generated via:

```
lyt <- basic_table() |>
  split_rows_by("SEX") |>
  analyze("AGE") |>
  split_rows_by("BMRKR2", nested = FALSE) |>
  split_rows_by("RACE") |>
  analyze("AGE") |>
  split_rows_by("SEX", at_sibling = "RACE") |>
  analyze("BMRKR1")
```

The eligible anchor points would be "BMRKR2", "RACE", "SEX" and "BMRKR1". "AGE" is masked by the branching caused by anchoring our SEX split on RACE.

Finally, while at_sibling does support de-duplication of "<name>[i]" anchors, it does so **within the set of available anchors**, which can be counter-intuitive. It is strongly suggested that the parent_name and table_names argument(s) of split_rows_by* and analyze be used to prevent the need for this. at_sibling will resolve to table names overridden in this manner.

See Also

split_rows_by() for typical row splitting, and split_cols_by_multivar() to perform the same type of split on a column basis.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by_multivar(c("SEX", "STRATA1")) |>
  summarize_row_groups() |>
  analyze(c("AGE", "SEX"))

tbl <- build_table(lyt, DM)
tbl
```

SplitValue *Construct a* SplitValue *object*

Description

Creates a SplitValue object representing a single facet value produced by a splitting operation, optionally carrying a custom subsetting expression and child-specific extra arguments.

Usage

```
SplitValue(val, extr = list(), label = val, sub_expr = NULL)
```

Arguments

val	(ANY) the raw value for this split facet.
extr	(list) named list of child-specific extra arguments to forward to the analysis or content function for this facet.
label	(character(1)) display label. Defaults to val.
sub_expr	(expression or NULL) optional subsetting expression. When NULL (default) the expression is derived automatically from val during tabulation.

Value

A SplitValue object.

See Also

splv_extra(), value_expr()

Examples

```
sv <- SplitValue("A", sub_expr = expression(ARM == "A"))
value_expr(sv)
splv_extra(sv)
```

`splv_extra` *Access or set child-specific extra arguments on a split value*

Description

`splv_extra` retrieves the named list of *child-specific* extra arguments stored on a `SplitValue` object. These arguments are forwarded to the analysis or content function only for the facet represented by that particular split value, making them distinct from `split_exargs()` which applies to *all* children of a split.

Usage

```
splv_extra(obj)

## S4 method for signature 'SplitValue'
splv_extra(obj)

splv_extra(obj) <- value

## S4 replacement method for signature 'SplitValue'
splv_extra(obj) <- value
```

Arguments

`obj`	(`SplitValue`) a split value object, typically produced by `SplitValue()` or as a result of a splitting operation.
`value`	(`list`) named list of extra arguments to store on `obj`.

Value

- `splv_extra` returns the current `list` of child-specific extra args.
- `splv_extra<-` returns `obj` with the extra arguments replaced.

See Also

`split_exargs()` for split-level (all-children) extra arguments.

Examples

```
sv <- SplitValue("A", extr = list(my_arg = 1))
splv_extra(sv)

splv_extra(sv) <- list(my_arg = 99)
splv_extra(sv)
```

---

subset_cols *Subset a table or row to particular columns*

Description

Subset a table or row to particular columns

Usage

```
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'TableTree,numeric'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'ElementaryTable,numeric'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
```

```
)

## S4 method for signature 'ANY,character'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'TableRow,numeric'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'LabelRow,numeric'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'InstantiatedColumnInfo,numeric'
subset_cols(
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)

## S4 method for signature 'LayoutColTree,numeric'
subset_cols(
```

```
  tt,
  j,
  newcinfo = NULL,
  keep_topleft = TRUE,
  keep_titles = TRUE,
  keep_footers = keep_titles,
  ...
)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
j	(integer, logical or character) The column(s) to subset tt down to. Character vectors are interpreted as a *column path*, not as names. Path can include "*" wildcards.
newcinfo	(NULL or InstantiatedColumnInfo) The new column info, if precomputed. Generally should not be manually set by users.
keep_topleft	(flag) if TRUE (the default), top_left material for the table will be carried over to the subset.
keep_titles	(flag) if TRUE (the default), all title material for the table will be carried over to the subset.
keep_footers	(flag) if TRUE, all footer material for the table will be carried over to the subset. It defaults to keep_titles.
...	Ignored.

Examples

```
lyt <- basic_table(
  title = "Title",
  subtitles = c("Sub", "titles"),
  prov_footer = "prov footer",
  main_footer = "main footer"
) |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  analyze(c("AGE"))

tbl <- build_table(lyt, DM)

subset_cols(tbl, c(1, 3))
subset_cols(tbl, c("ARM", "*", "SEX", "F"))
```

summarize_row_groups *Add a content row of summary counts*

Description

Add a content row of summary counts

Usage

```
summarize_row_groups(
  lyt,
  var = "",
  label_fstr = "%s",
  format = "xx (xx.x%)",
  na_str = "-",
  cfun = NULL,
  indent_mod = 0L,
  extra_args = list()
)
```

Arguments

lyt	(PreDataTableLayouts) layout object pre-data used for tabulation.
var	(string) variable name.
label_fstr	(string) a sprintf style format string. For non-comparison splits, it can contain up to one "\%s" which takes the current split value and generates the row/column label. For comparison-based splits it can contain up to two "\%s".
format	(string, function, or list) format associated with this split. Formats can be declared via strings ("xx.x") or function. In cases such as analyze calls, they can be character vectors or lists of functions. See formatters::list_valid_format_labels() for a list of all available format strings.
na_str	(string) string that should be displayed when the value of x is missing. Defaults to "NA".
cfun	(list, function, or NULL) tabulation function(s) for creating content rows. Must accept x or df as first parameter. Must accept labelstr as the second argument. Can optionally accept all optional arguments accepted by analysis functions. See analyze().
indent_mod	(numeric) modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

Details

If `format` expects 1 value (i.e. it is specified as a format string and `xx` appears for two values (i.e. `xx` appears twice in the format string) or is specified as a function, then both raw and percent of column total counts are calculated. If `format` is a format string where `xx` appears only one time, only raw counts are used.

`cfun` must accept `x` or `df` as its first argument. For the `df` argument `cfun` will receive the subset `data.frame` corresponding with the row- and column-splitting for the cell being calculated. Must accept `labelstr` as the second parameter, which accepts the `label` of the level of the parent split currently being summarized. Can additionally take any optional argument supported by analysis functions. (see `analyze()`).

In addition, if complex custom functions are needed, we suggest checking the available additional_fun_params that can be used in `cfun`.

Value

A `PreDataTableLayouts` object suitable for passing to further layouting functions, and to `build_table()`.

Author(s)

Gabriel Becker

Examples

```
DM2 <- subset(DM, COUNTRY %in% c("USA", "CAN", "CHN"))

lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("COUNTRY", split_fun = drop_split_levels) |>
  summarize_row_groups(label_fstr = "%s (n)") |>
  analyze("AGE", afun = list_wrap_x(summary), format = "xx.xx")
lyt

tbl <- build_table(lyt, DM2)
tbl

row_paths_summary(tbl) # summary count is a content table

## use a cfun and extra_args to customize summarization
## behavior
sfun <- function(x, labelstr, trim) {
  in_rows(
    c(mean(x, trim = trim), trim),
    .formats = "xx.x (xx.x%)",
```

```
    .labels = sprintf(
      "%s (Trimmed mean and trim %%)",
      labelstr
    )
  )
}

lyt2 <- basic_table(show_colcounts = TRUE) |>
  split_cols_by("ARM") |>
  split_rows_by("COUNTRY", split_fun = drop_split_levels) |>
  summarize_row_groups("AGE",
    cfun = sfun,
    extra_args = list(trim = .2)
  ) |>
  analyze("AGE", afun = list_wrap_x(summary), format = "xx.xx") |>
  append_topleft(c("Country", "  Age"))

tbl2 <- build_table(lyt2, DM2)
tbl2
```

---

table_shell *Table shells*

Description

A table shell is a rendering of the table which maintains the structure, but does not display the values, rather displaying the formatting instructions for each cell.

Usage

```
table_shell(
  tt,
  widths = NULL,
  col_gap = 3,
  hsep = default_hsep(),
  tf_wrap = FALSE,
  max_width = NULL
)

table_shell_str(
  tt,
  widths = NULL,
  col_gap = 3,
  hsep = default_hsep(),
  tf_wrap = FALSE,
  max_width = NULL
)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
widths	(numeric or NULL) Proposed widths for the columns of x. The expected length of this numeric vector can be retrieved with ncol(x) + 1 as the column of row names must also be considered.
col_gap	(numeric(1)) space (in characters) between columns.
hsep	(string) character to repeat to create header/body separator line. If NULL, the object value will be used. If " ", an empty separator will be printed. See default_hsep() for more information.
tf_wrap	(flag) whether the text for title, subtitles, and footnotes should be wrapped.
max_width	(integer(1), string or NULL) width that title and footer (including footnotes) materials should be word-wrapped to. If NULL, it is set to the current print width of the session (getOption("width")). If set to "auto", the width of the table (plus any table inset) is used. Parameter is ignored if tf_wrap = FALSE.

Value

- table_shell returns NULL, as the function is called for the side effect of printing the shell to the console.
- table_shell_str returns the string representing the table shell.

See Also

value_formats() for a matrix of formats for each cell in a table.

Examples

```
library(dplyr)

iris2 <- iris |>
  group_by(Species) |>
  mutate(group = as.factor(rep_len(c("a", "b"), length.out = n()))) |>
  ungroup()

lyt <- basic_table() |>
  split_cols_by("Species") |>
  split_cols_by("group") |>
 analyze(c("Sepal.Length", "Petal.Width"), afun = list_wrap_x(summary), format = "xx.xx")

tbl <- build_table(lyt, iris2)
table_shell(tbl)
```

table_structure *Summarize table*

Description

Summarize table

Usage

```
table_structure(x, detail = c("subtable", "row"))
```

Arguments

x	(VTableTree) a table object.
detail	(string) either row or subtable.

Value

No return value. Called for the side-effect of printing a row- or subtable-structure summary of x.

Examples

```
library(dplyr)

iris2 <- iris |>
  group_by(Species) |>
  mutate(group = as.factor(rep_len(c("a", "b"), length.out = n()))) |>
  ungroup()

lyt <- basic_table() |>
  split_cols_by("Species") |>
  split_cols_by("group") |>
  analyze(c("Sepal.Length", "Petal.Width"),
    afun = list_wrap_x(summary),
    format = "xx.xx"
  )

tbl <- build_table(lyt, iris2)
tbl

row_paths(tbl)

table_structure(tbl)

table_structure(tbl, detail = "row")
```

top_left *Top left material*

Description

A TableTree object can have *top left material* which is a sequence of strings which are printed in the area of the table between the column header display and the label of the first row. These functions access and modify that material.

Usage

```
top_left(obj)

## S4 method for signature 'VTableTree'
top_left(obj)

## S4 method for signature 'InstantiatedColumnInfo'
top_left(obj)

## S4 method for signature 'PreDataTableLayouts'
top_left(obj)

top_left(obj) <- value

## S4 replacement method for signature 'VTableTree'
top_left(obj) <- value

## S4 replacement method for signature 'InstantiatedColumnInfo'
top_left(obj) <- value

## S4 replacement method for signature 'PreDataTableLayouts'
top_left(obj) <- value
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
value	(ANY) the new value.

Value

A character vector representing the top-left material of obj (or obj after modification, in the case of the setter).

toString,VTableTree-method

Convert an rtable *object to a string*

Description

Transform a complex object into a string representation ready to be printed or written to a plain-text file.

All objects that are printed to console pass via toString. This function allows fundamental formatting specifications to be applied to final output, like column widths and relative wrapping (width), title and footer wrapping (tf_wrap = TRUE and max_width), and horizontal separator character (e.g. hsep = "+").

Usage

```
## S4 method for signature 'VTableTree'
toString(
  x,
  widths = NULL,
  col_gap = 3,
  hsep = horizontal_sep(x),
  indent_size = 2,
  tf_wrap = FALSE,
  max_width = NULL,
  fontspec = font_spec(),
  ttype_ok = FALSE,
  round_type = obj_round_type(x)
)
```

Arguments

x	(ANY) object to be prepared for rendering.
widths	(numeric or NULL) Proposed widths for the columns of x. The expected length of this numeric vector can be retrieved with ncol(x) + 1 as the column of row names must also be considered.
col_gap	(numeric(1)) space (in characters) between columns.
hsep	(string) character to repeat to create header/body separator line. If NULL, the object value will be used. If " ", an empty separator will be printed. See default_hsep() for more information.
indent_size	(numeric(1)) number of spaces to use per indent level. Defaults to 2.

tf_wrap	(flag) whether the text for title, subtitles, and footnotes should be wrapped.
max_width	(integer(1), string or NULL) width that title and footer (including footnotes) materials should be word-wrapped to. If NULL, it is set to the current print width of the session (getOption("width")). If set to "auto", the width of the table (plus any table inset) is used. Parameter is ignored if tf_wrap = FALSE.
fontspec	(font_spec) a font_spec object specifying the font information to use for calculating string widths and heights, as returned by font_spec().
ttype_ok	(logical(1)) should truetype (non-monospace) fonts be allowed via fontspec. Defaults to FALSE. This parameter is primarily for internal testing and generally should not be set by end users.
round_type	(string) The type of rounding to perform. Allowed values: ("iec", "iec_mod" or "sas") See round_fmt() for details.

Details

Manual insertion of newlines is not supported when tf_wrap = TRUE and will result in a warning and undefined wrapping behavior. Passing vectors of already split strings remains supported, however in this case each string is word-wrapped separately with the behavior described above.

Value

A string representation of x as it appears when printed.

See Also

wrap_string()

Examples

```
library(dplyr)

iris2 <- iris |>
  group_by(Species) |>
  mutate(group = as.factor(rep_len(c("a", "b"), length.out = n()))) |>
  ungroup()

lyt <- basic_table() |>
  split_cols_by("Species") |>
  split_cols_by("group") |>
  analyze(c("Sepal.Length", "Petal.Width"), afun = list_wrap_x(summary), format = "xx.xx")

tbl <- build_table(lyt, iris2)

cat(toString(tbl, col_gap = 3))
```

tree_children *Retrieve or set the direct children of a tree-style object*

Description

Retrieve or set the direct children of a tree-style object

Usage

```
tree_children(x)

tree_children(x) <- value
```

Arguments

x	(TableTree or ElementaryTable) an object with a tree structure.
value	(list) new list of children.

Value

A list of direct children of x.

trim_levels_in_facets *Trim levels of another variable from each facet (post-processing split step)*

Description

Trim levels of another variable from each facet (post-processing split step)

Usage

```
trim_levels_in_facets(innervar)
```

Arguments

innervar	(character) the variable(s) to trim (remove unobserved levels) independently within each facet.

Value

A function suitable for use in the post (list) argument of make_split_fun.

See Also

make_split_fun()

Other make_custom_split: add_combo_facet(), drop_facet_levels(), make_split_fun(), make_split_result(), restrict_facets()

---

trim_levels_to_map *Trim levels to map*

Description

This split function constructor creates a split function which trims levels of a variable to reflect restrictions on the possible combinations of two or more variables which the data is split by (along the same axis) within a layout.

Usage

```
trim_levels_to_map(map = NULL)
```

Arguments

map	data.frame. A data.frame defining allowed combinations of variables. Any combination at the level of this split not present in the map will be removed from the data, both for the variable being split and those present in the data but not associated with this split or any parents of it.

Details

When splitting occurs, the map is subset to the values of all previously performed splits. The levels of the variable being split are then pruned to only those still present within this subset of the map representing the current hierarchical splitting context.

Splitting is then performed via the keep_split_levels() split function.

Each resulting element of the partition is then further trimmed by pruning values of any remaining variables specified in the map to those values allowed under the combination of the previous and current split.

Value

A function that can be used as a split function.

See Also

trim_levels_in_group().

Examples

```
map <- data.frame(
  LBCAT = c("CHEMISTRY", "CHEMISTRY", "CHEMISTRY", "IMMUNOLOGY"),
  PARAMCD = c("ALT", "CRP", "CRP", "IGA"),
  ANRIND = c("LOW", "LOW", "HIGH", "HIGH"),
  stringsAsFactors = FALSE
)

lyt <- basic_table() |>
  split_rows_by("LBCAT") |>
  split_rows_by("PARAMCD", split_fun = trim_levels_to_map(map = map)) |>
  analyze("ANRIND")
tbl <- build_table(lyt, ex_adlb)
```

`trim_rows` *Trim rows from a populated table without regard for table structure*

Description

Trim rows from a populated table without regard for table structure

Usage

```
trim_rows(tt, criteria = all_zero_or_na)
```

Arguments

`tt`	(`TableTree` or related class) a `TableTree` object representing a populated table.
`criteria`	(`function`) function which takes a `TableRow` object and returns `TRUE` if that row should be removed. Defaults to `all_zero_or_na()`.

Details

This function will be deprecated in the future in favor of the more elegant and versatile `prune_table()` function which can perform the same function as `trim_rows()` but is more powerful as it takes table structure into account.

Value

The table with rows that have only `NA` or 0 cell values removed.

Note

Visible `LabelRows` are including in this trimming, which can lead to either all label rows being trimmed or label rows remaining when all data rows have been trimmed, depending on what `criteria` returns when called on a `LabelRow` object. To avoid this, use the structurally-aware `prune_table()` machinery instead.

See Also

prune_table()

Examples

```
adsl <- ex_adsl
levels(adsl$SEX) <- c(levels(ex_adsl$SEX), "OTHER")

tbl_to_trim <- basic_table() |>
  analyze("BMRKR1") |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  summarize_row_groups() |>
  split_rows_by("STRATA1") |>
  summarize_row_groups() |>
  analyze("AGE") |>
  build_table(adsl)

tbl_to_trim |> trim_rows()

tbl_to_trim |> trim_rows(all_zero)
```

---

tt_at_path *Access or set table elements at specified path*

Description

Access or set table elements at specified path

Usage

```
tt_at_path(tt, path, ...)

tt_at_path(tt, path, ...) <- value
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
...	unused.
value	(ANY) the new value.

Note

Setting NULL at a defined path removes the corresponding sub-table.

Examples

```
# Accessing sub table.
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  split_rows_by("BMRKR2") |>
  analyze("AGE")

tbl <- build_table(lyt, ex_adsl) |> prune_table()
sub_tbl <- tt_at_path(tbl, path = c("SEX", "F", "BMRKR2"))

# Removing sub table.
tbl2 <- tbl
tt_at_path(tbl2, path = c("SEX", "F")) <- NULL
tbl2

# Setting sub table.
lyt3 <- basic_table() |>
  split_cols_by("ARM") |>
  split_rows_by("SEX") |>
  analyze("BMRKR2")

tbl3 <- build_table(lyt3, ex_adsl) |> prune_table()

tt_at_path(tbl3, path = c("SEX", "F", "BMRKR2")) <- sub_tbl
tbl3
```

---

tt_row_path_exists *Pathing*

Description

for tt_row_path_exists, tests whether a single path (potentially including "*" wildcards) resolves to at least one element satisfying tt_type (if specified).

Given a path with at least one wildcard ("*") in it, tt_normalize_path walks the tree and generates the complete set of fully specified (ie no wildcards) paths which exist in the row structure of obj

Usage

```
tt_row_path_exists(obj, path, tt_type = c("any", "row", "table", "elemtable"))

tt_normalize_row_path(
  obj,
```

```
  path,
  .prev_path = character(),
  tt_type = c("any", "row", "table", "elemtable")
)
```

Arguments

obj	(ANY) the object for the accessor to access or modify.
path	(character) a vector path for a position within the structure of a TableTree. Each element represents a subsequent choice amongst the children of the previous choice.
tt_type	(character(1)) One of "any", "row", "table", "elemtable"; when testing existence or resolving a path with "*" wildcards, this indicates a restriction on *the final element the path resolves to*. E.g., for "table", possible paths which match the structure of the wild-card path but resolve to an individual row will not be considered matching. The value "elemtable" indicates an Elementary table, i.e., one representing a single variable within an analyze call.
.prev_path	(character) Internal implementation detail. Do not set manually.

Details

Pathing is a method of using known structure within a table to specify elements within it in a self-describing, semantically meaningful way.

A Path consists of a character vector of one or more elements which will be used to descend the tree structure of a table's row or column space.

Existing paths will match the layout used to make the table in the form of split, split-value pairs corresponding to facets generated by split_rows_by* and, elementary subtables generated by analyze, and rows generated by the afun used. Groups summaries generated by summarize_row_groups are represented by the 'content table' attached to a subtable representing a facet generated by a split_rows_by instruction, and are addressed via @content instead of their name.

For example, given the code

```
lyt <- basic_table() |>
  split_rows_by("ARM") |>
  split_rows_by("RACE") |>
  summarize_row_groups() |>
  analyze("SEX") |>
  analyze("AGE", nested = FALSE)

tbl <- build_table(lyt, DM)
```

We know that there will be two top-level subtables, one representing (and generated via) the split on the ARM variable, and one generated from the non-nested analyze on AGE. These can be be 'pathed to' at "ARM" and "AGE", respectively. Furthermore each value for ARM can be pathed to via, e.g., c("ARM", "A: Drug X") or more generally using the pathing wildcard "*" at c("ARM", "*").

A particular SEX analysis subtable, then, would be pathed to via the (row) path c("ARM", "*", "RACE", "*", "SEX"), e.g. c("ARM", "B: Placebo", "RACE", "ASIAN", "SEX"). The group-summary for Asians within the placebo group would be pathed to via c("ARM", "B: Placebo", "RACE", "ASIAN", "@content") for the table, and c("ARM", "B: Placebo", "RACE", "ASIAN", "@content", "ASIAN") for the row.

Value

For tt_row_path_exists: TRUE if the path resolves to at least one substructure (subtable or row) that satisfies tt_type, or if the path is length 0; FALSE otherwise

for tt_normalize_row_path: a list of 0 or more fully specified paths which exist in the row structure of obj that match the original wildcard path, and which lead to an element of type tt_type (if specified other than "any").

Note

some pathing-based functionality supports the "*" wildcard (typically 'setters'/functionality which alters a table and returns it) while some does not (typically 'getters' which retrieve a subtable/row from a table or some attribute of that subtable/row).

The "*" wildcard will never act as "@content" to step into a subtable's content table; that must be specified in the path, via e.g., c("*", "*", "@content") instead of c("*", "*", "*").

Examples

```
lyt <- basic_table() |>
  split_rows_by("ARM") |>
  split_rows_by("STRATA1") |>
  analyze("SEX") |>
  analyze("SEX", nested = FALSE)
tbl <- build_table(lyt, DM)
tt_row_path_exists(tbl, c("root", "ARM", "*", "*", "*", "SEX")) # TRUE
tt_row_path_exists(tbl, c("ARM", "*", "*", "*", "SEX")) # TRUE
tt_row_path_exists(tbl, c("ARM", "*", "*", "SEX")) # FALSE
tt_row_path_exists(tbl, "FAKE") # FALSE
tt_row_path_exists(tbl, c("ARM", "*", "STRATA1", "*", "SEX")) # TRUE
tt_row_path_exists(tbl, c("ARM", "*", "STRATA", "*", "SEX")) # FALSE
tt_row_path_exists(tbl, "SEX") # TRUE
tt_row_path_exists(tbl, "SEX", tt_type = "table") # TRUE
tt_row_path_exists(tbl, "SEX", tt_type = "elemtable") # TRUE
tt_row_path_exists(tbl, "SEX", tt_type = "row") # FALSE
tt_row_path_exists(tbl, c("SEX", "*")) # TRUE
tt_normalize_row_path(tbl, c("root", "ARM", "*", "*", "*", "SEX"))
tt_normalize_row_path(tbl, "SEX", tt_type = "row") # empty list
```

update_ref_indexing *Update footnote indices on a built table*

Description

Re-indexes footnotes within a built table.

Usage

```
update_ref_indexing(tt)
```

Arguments

tt	(TableTree or related class) a TableTree object representing a populated table.

Details

After adding or removing referential footnotes manually, or after subsetting a table, the reference indexes (i.e. the number associated with specific footnotes) may be incorrect. This function recalculates these based on the full table.

Note

In the future this should not generally need to be called manually.

validate_table_struct *Validate and assert valid table structure*

Description

[Experimental]

A TableTree (rtables-built table) is considered degenerate if:

1. It contains no subtables or data rows (content rows do not count).
2. It contains a subtable which is degenerate by the criterion above.

validate_table_struct assesses whether tt has a valid (non-degenerate) structure.

assert_valid_table asserts a table must have a valid structure, and throws an informative error (the default) or warning (if warn_only is TRUE) if the table is degenerate (has invalid structure or contains one or more invalid substructures.

Usage

```
validate_table_struct(tt)

assert_valid_table(tt, warn_only = FALSE)
```

Arguments

tt	(TableTree) a TableTree object.
warn_only	(flag) whether a warning should be thrown instead of an error. Defaults to FALSE.

Value

- validate_table_struct returns a logical value indicating valid structure.
- assert_valid_table is called for its side-effect of throwing an error or warning for degenerate tables.

Note

This function is experimental and the exact text of the warning/error is subject to change in future releases.

See Also

Other table structure validation functions: find_degen_struct(), sanitize_table_struct()

Examples

```
validate_table_struct(rtable("hahaha"))
## Not run:
assert_valid_table(rtable("oops"))

## End(Not run)
```

---

value_expr *Retrieve the subset expression from a split value*

Description

Returns the subsetting expression associated with a SplitValue (or ValueWrapper) object, or NULL for objects without one. This expression is used internally to subset data when tabulating.

Usage

```
value_expr(obj)

## S4 method for signature 'ValueWrapper'
value_expr(obj)

## S4 method for signature 'ANY'
value_expr(obj)
```

Arguments

obj	(ValueWrapper or ANY) a split value object, typically a SplitValue constructed by SplitValue(). Any other object returns NULL.

Value

An expression object, or NULL.

Examples

```
sv <- SplitValue("A", sub_expr = expression(ARM == "A"))
value_expr(sv)

value_expr("not a SplitValue") # NULL
```

---

value_formats *Value formats*

Description

Returns a matrix of formats for the cells in a table.

Usage

```
value_formats(obj, default = obj_format(obj))

## S4 method for signature 'ANY'
value_formats(obj, default = obj_format(obj))

## S4 method for signature 'TableRow'
value_formats(obj, default = obj_format(obj))

## S4 method for signature 'LabelRow'
value_formats(obj, default = obj_format(obj))

## S4 method for signature 'VTableTree'
value_formats(obj, default = obj_format(obj))
```

Arguments

obj	(VTableTree or TableRow) a table or row object.
default	(string, function, or list) default format.

Value

Matrix (storage mode list) containing the effective format for each cell position in the table (including 'virtual' cells implied by label rows, whose formats are always NULL).

See Also

table_shell() and table_shell_str() for information on the table format structure.

Examples

```
lyt <- basic_table() |>
  split_rows_by("RACE", split_fun = keep_split_levels(c("ASIAN", "WHITE"))) |>
  analyze("AGE")

tbl <- build_table(lyt, DM)
value_formats(tbl)
```

VarLevelSplit-class *Split on levels within a variable*

Description

Split on levels within a variable

Usage

```
VarLevelSplit(
  var,
  split_label,
  labels_var = NULL,
  cfun = NULL,
  cformat = NULL,
  cna_str = NA_character_,
  split_fun = NULL,
  split_format = NULL,
  split_na_str = NA_character_,
  valorder = NULL,
  split_name = var,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  indent_mod = 0L,
  label_pos = c("topleft", "hidden", "visible"),
  cindent_mod = 0L,
  cvar = "",
  cextra_args = list(),
  page_prefix = NA_character_,
```

```
  section_div = NA_character_,
  show_colcounts = FALSE,
  colcount_format = NULL
)

VarLevWBaselineSplit(
  var,
  ref_group,
  labels_var = var,
  split_label,
  split_fun = NULL,
  label_fstr = "%s - %s",
  cfun = NULL,
  cformat = NULL,
  cna_str = NA_character_,
  cvar = "",
  split_format = NULL,
  split_na_str = NA_character_,
  valorder = NULL,
  split_name = var,
  extra_args = list(),
  show_colcounts = FALSE,
  colcount_format = NULL
)
```

Arguments

var	(string) variable name.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
labels_var	(string) name of variable containing labels to be displayed for the values of var.
cfun	(list, function, or NULL) tabulation function(s) for creating content rows. Must accept x or df as first parameter. Must accept labelstr as the second argument. Can optionally accept all optional arguments accepted by analysis functions. See analyze().
cformat	(string, function, or list) format for content rows.
cna_str	(character) NA string for use with cformat for content table.
split_fun	(function or NULL) custom splitting function. See custom_split_funs.
split_format	(string, function, or list) default format associated with the split being created.

split_na_str (character)
NA string vector for use with split_format.

valorder (character)
the order that the split children should appear in resulting table.

split_name (string)
name associated with the split (for pathing, etc.).

child_labels (string)
the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

label_pos (string)
location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

cindent_mod (numeric(1))
the indent modifier for the content tables generated by this split.

cvar (string)
the variable, if any, that the content function should accept. Defaults to NA.

cextra_args (list)
extra arguments to be passed to the content function when tabulating row group summaries.

page_prefix (string)
prefix to be appended with the split value when forcing pagination between the children of a split/table.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

show_colcounts (logical(1))
should column counts be displayed at the level facets created by this split. Defaults to FALSE.

colcount_format
(character(1))
if show_colcounts is TRUE, the format which should be used to display column counts for facets generated by this split. Defaults to "(N=xx)".

ref_group (character)
value of var to be taken as the ref_group/control to be compared against.

label_fstr (string)
a sprintf style format string. For non-comparison splits, it can contain up to one "\%s" which takes the current split value and generates the row/column label. For comparison-based splits it can contain up to two "\%s".

Value

a VarLevelSplit object.

Author(s)

Gabriel Becker

---

vars_in_layout *List variables required by a pre-data table layout*

Description

List variables required by a pre-data table layout

Usage

```
vars_in_layout(lyt)

## S4 method for signature 'PreDataTableLayouts'
vars_in_layout(lyt)

## S4 method for signature 'PreDataAxisLayout'
vars_in_layout(lyt)

## S4 method for signature 'SplitVectorTree'
vars_in_layout(lyt)

## S4 method for signature 'SplitVector'
vars_in_layout(lyt)

## S4 method for signature 'Split'
vars_in_layout(lyt)

## S4 method for signature 'CompoundSplit'
vars_in_layout(lyt)

## S4 method for signature 'ManualSplit'
vars_in_layout(lyt)
```

Arguments

lyt	(PreDataTableLayouts) the layout (or a component thereof).

Details

This will walk the layout declaration and return a vector of the names of the unique variables that are used in any of the following ways:

- Variable being split on (directly or via cuts)
- Element of a Multi-variable column split
- Content variable
- Value-label variable

Value

A character vector containing the unique variables explicitly used in the layout (see the notes below).

Note

- This function will not detect dependencies implicit in analysis or summary functions which accept x or df and then rely on the existence of particular variables not being split on/analyzed.
- The order these variable names appear within the return vector is undefined and should not be relied upon.

Examples

```
lyt <- basic_table() |>
  split_cols_by("ARM") |>
  split_cols_by("SEX") |>
  summarize_row_groups(label_fstr = "Overall (N)") |>
  split_rows_by("RACE",
    split_label = "Ethnicity", labels_var = "ethn_lab",
    split_fun = drop_split_levels
  ) |>
  summarize_row_groups("RACE", label_fstr = "%s (n)") |>
  analyze("AGE", var_labels = "Age", afun = mean, format = "xx.xx")

vars_in_layout(lyt)
```

VarStaticCutSplit-class

Splits for cutting by values of a numeric variable

Description

Splits for cutting by values of a numeric variable

Create static cut or static cumulative cut split

Usage

```
make_static_cut_split(
  var,
  split_label,
  cuts,
  cutlabels = NULL,
  cfun = NULL,
  cformat = NULL,
  cna_str = NA_character_,
  split_format = NULL,
  split_na_str = NA_character_,
  split_name = var,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  indent_mod = 0L,
  cindent_mod = 0L,
  cvar = "",
  cextra_args = list(),
  label_pos = "visible",
  cumulative = FALSE,
  page_prefix = NA_character_,
  section_div = NA_character_,
  show_colcounts = FALSE,
  colcount_format = NULL
)

VarDynCutSplit(
  var,
  split_label,
  cutfun,
  cutlabelfun = function(x) NULL,
  cfun = NULL,
  cformat = NULL,
  cna_str = NA_character_,
  split_format = NULL,
  split_na_str = NA_character_,
```

```
  split_name = var,
  child_labels = c("default", "visible", "hidden"),
  extra_args = list(),
  cumulative = FALSE,
  indent_mod = 0L,
  cindent_mod = 0L,
  cvar = "",
  cextra_args = list(),
  label_pos = "visible",
  page_prefix = NA_character_,
  section_div = NA_character_,
  show_colcounts = FALSE,
  colcount_format = NULL
)
```

Arguments

var	(string) variable name.
split_label	(string) label to be associated with the table generated by the split. Not to be confused with labels assigned to each child (which are based on the data and type of split during tabulation).
cuts	(numeric) cuts to use.
cutlabels	(character or NULL) labels for the cuts.
cfun	(list, function, or NULL) tabulation function(s) for creating content rows. Must accept x or df as first parameter. Must accept labelstr as the second argument. Can optionally accept all optional arguments accepted by analysis functions. See analyze().
cformat	(string, function, or list) format for content rows.
cna_str	(character) NA string for use with cformat for content table.
split_format	(string, function, or list) default format associated with the split being created.
split_na_str	(character) NA string vector for use with split_format.
split_name	(string) name associated with the split (for pathing, etc.).
child_labels	(string) the display behavior for the labels (i.e. label rows) of the children of this split. Accepts "default", "visible", and "hidden". Defaults to "default" which flags the label row as visible only if the child has 0 content rows.

extra_args (list)
extra arguments to be passed to the tabulation function. Element position in the list corresponds to the children of this split. Named elements in the child-specific lists are ignored if they do not match a formal argument of the tabulation function.

indent_mod (numeric)
modifier for the default indent position for the structure created by this function (subtable, content table, or row) *and all of that structure's children*. Defaults to 0, which corresponds to the unmodified default behavior.

cindent_mod (numeric(1))
the indent modifier for the content tables generated by this split.

cvar (string)
the variable, if any, that the content function should accept. Defaults to NA.

cextra_args (list)
extra arguments to be passed to the content function when tabulating row group summaries.

label_pos (string)
location where the variable label should be displayed. Accepts "hidden" (default for non-analyze row splits), "visible", "topleft", and "default" (for analyze splits only). For analyze calls, "default" indicates that the variable should be visible if and only if multiple variables are analyzed at the same level of nesting.

cumulative (flag)
whether the cuts should be treated as cumulative. Defaults to FALSE.

page_prefix (string)
prefix to be appended with the split value when forcing pagination between the children of a split/table.

section_div (string)
string which should be repeated as a section divider after each group defined by this split instruction, or NA_character_ (the default) for no section divider.

show_colcounts (logical(1))
should column counts be displayed at the level facets created by this split. Defaults to FALSE.

colcount_format
(character(1))
if show_colcounts is TRUE, the format which should be used to display column counts for facets generated by this split. Defaults to "(N=xx)".

cutfun (function)
function which accepts the *full vector* of var values and returns cut points to be used (via cut) when splitting data during tabulation.

cutlabelfun (function)
function which returns either labels for the cuts or NULL when passed the return value of cutfun.

Value

A VarStaticCutSplit, CumulativeCutSplit object for make_static_cut_split, or a VarDynCutSplit object for VarDynCutSplit().

Viewer *Display an* rtable *object in the Viewer pane in RStudio or in a browser*

Description

The table will be displayed using bootstrap styling.

Usage

```
Viewer(x, y = NULL, ...)
```

Arguments

x	(rtable or shiny.tag) an object of class rtable or shiny.tag (defined in htmltools package).
y	(rtable or shiny.tag) optional second argument of same type as x.
...	arguments passed to as_html().

Value

Not meaningful. Called for the side effect of opening a browser or viewer pane.

Examples

```
if (interactive()) {
  sl5 <- factor(iris$Sepal.Length > 5,
    levels = c(TRUE, FALSE),
    labels = c("S.L > 5", "S.L <= 5")
  )

  df <- cbind(iris, sl5 = sl5)

  lyt <- basic_table() |>
    split_cols_by("sl5") |>
    analyze("Sepal.Length")

  tbl <- build_table(lyt, df)

  Viewer(tbl)
  Viewer(tbl, tbl)
```

```
  tbl2 <- htmltools::tags$div(
    class = "table-responsive",
    as_html(tbl, class_table = "table")
  )

  Viewer(tbl, tbl2)
}
```

Index

∗ **compatibility**
  rheader, 131
  rrow, 137
  rrowl, 138
  rtable, 139
∗ **conventions**
  compat_args, 51
  sf_args, 147
∗ **make_custom_split**
  add_combo_facet, 6
  drop_facet_levels, 60
  make_split_fun, 94
  make_split_result, 96
  restrict_facets, 129
  trim_levels_in_facets, 190
∗ **table structure validation functions**
  find_degen_struct, 68
  sanitize_table_struct, 142
  validate_table_struct, 197
.tablerow *(*LabelRow*)*, 86
[,VTableTree,logical,logical-method *(*brackets*)*, 32
[<-,VTableTree,ANY,ANY,list-method *(*brackets*)*, 32

add_colcounts, 5
add_combo_facet, 6
add_combo_facet(), *60*, *95*, *97*, *130*, *191*
add_combo_levels *(*add_overall_level*)*, 9
add_combo_levels(), *166*, *168*
add_existing_table, 7
add_overall_col, 8
add_overall_col(), *9*
add_overall_facet *(*add_combo_facet*)*, 6
add_overall_level, 9
add_overall_level(), *8*, *9*, *166*, *168*
add_to_split_result *(*make_split_result*)*, 96
additional_fun_params, 12, *18–20*, *183*
all_zero *(*all_zero_or_na*)*, 13
all_zero_or_na, 13
all_zero_or_na(), *13*, *192*
analyze, 15
analyze(), *12*, *16*, *20*, *24*, *25*, *78*, *89*, *91*, *105*, *143*, *148*, *150*, *152*, *182*, *183*, *201*, *206*
analyze_colvars, 20
analyze_colvars(), *15*, *165*
AnalyzeColVarSplit *(*AnalyzeVarSplit*)*, 23
AnalyzeMultiVars *(*AnalyzeVarSplit*)*, 23
AnalyzeVarSplit, 23
append_topleft, 26
as.vector(), *29*
as.vector,VTableTree-method *(*asvec*)*, 29
as_html, 27
as_html(), *208*
as_result_df *(*data.frame_export*)*, 55
as_result_df(), *58*
assert_valid_table *(*validate_table_struct*)*, 197
asvec, 29

basic_table, 30
basic_table(), *145*, *146*
brackets, 32
build_table, 35
build_table(), *5*, *7*, *8*, *13*, *17*, *19*, *21*, *26*, *31*, *124*, *143*, *145*, *153*, *156*, *162*, *165*, *172*, *176*, *183*

c.RowsVerticalSection, 37
cbind_rtables, 38
cell_footnotes *(*row_footnotes*)*, 133
cell_footnotes<- *(*row_footnotes*)*, 133
cell_values, 39
cell_values(), *33*, *135*, *150*
CellValue, 41
clayout, 42
clayout,ANY-method *(*clayout*)*, 42

clayout,PreDataTableLayouts-method
(clayout), 42
clayout,VTableNodeInfo-method
(clayout), 42
clayout<- (clayout), 42
clayout<-,PreDataTableLayouts-method
(clayout), 42
clear_indent_mods, 46
clear_indent_mods,TableRow-method
(clear_indent_mods), 46
clear_indent_mods,VTableTree-method
(clear_indent_mods), 46
col_counts (clayout), 42
col_counts(), *66*
col_counts,InstantiatedColumnInfo-method
(clayout), 42
col_counts,VTableNodeInfo-method
(clayout), 42
col_counts<- (clayout), 42
col_counts<-,InstantiatedColumnInfo-method
(clayout), 42
col_counts<-,VTableNodeInfo-method
(clayout), 42
col_exprs (clayout), 42
col_exprs,InstantiatedColumnInfo-method
(clayout), 42
col_exprs,PreDataColLayout-method
(clayout), 42
col_exprs,PreDataTableLayouts-method
(clayout), 42
col_fnotes_here (row_footnotes), 133
col_fnotes_here,ANY-method
(row_footnotes), 133
col_fnotes_here<- (row_footnotes), 133
col_footnotes (row_footnotes), 133
col_footnotes<- (row_footnotes), 133
col_info (clayout), 42
col_info,VTableNodeInfo-method
(clayout), 42
col_info<- (clayout), 42
col_info<-,ElementaryTable-method
(clayout), 42
col_info<-,TableRow-method (clayout), 42
col_info<-,TableTree-method (clayout),
42
col_paths (row_paths), 135
col_paths(), *134*
col_paths_summary (row_paths_summary),
136
col_paths_summary(), *134, 135*
col_total (clayout), 42
col_total,InstantiatedColumnInfo-method
(clayout), 42
col_total,VTableNodeInfo-method
(clayout), 42
col_total<- (clayout), 42
col_total<-,InstantiatedColumnInfo-method
(clayout), 42
col_total<-,VTableNodeInfo-method
(clayout), 42
colcount_visible, 47
colcount_visible(), *67*
colcount_visible,InstantiatedColumnInfo-method
(colcount_visible), 47
colcount_visible,LayoutColTree-method
(colcount_visible), 47
colcount_visible,VTableTree-method
(colcount_visible), 47
colcount_visible<- (colcount_visible),
47
colcount_visible<-,InstantiatedColumnInfo-method
(colcount_visible), 47
colcount_visible<-,LayoutColTree-method
(colcount_visible), 47
colcount_visible<-,VTableTree-method
(colcount_visible), 47
collect_leaves, 48
coltree (clayout), 42
coltree,InstantiatedColumnInfo-method
(clayout), 42
coltree,LayoutColTree-method (clayout),
42
coltree,PreDataColLayout-method
(clayout), 42
coltree,PreDataTableLayouts-method
(clayout), 42
coltree,TableRow-method (clayout), 42
coltree,VTableTree-method (clayout), 42
coltree_structure, 48
compare_rtables, 49
compat_args, 51
compat_args(), *147*
constr_args(), *52*, *147*
cont_n_allcols, 52
cont_n_allcols(), *150, 151*
cont_n_onecol (cont_n_allcols), 52

cont_n_onecol(), *150, 151*
content_all_zeros_nas *(all_zero_or_na)*, 13
content_table, 53
content_table(), *150*
content_table<- *(content_table)*, 53
ContentRow *(LabelRow)*, 86
ContentRow-class *(LabelRow)*, 86
counts_wpcts, 53
CumulativeCutSplit-class *(VarStaticCutSplit-class)*, 205
custom_split_funs, *9, 10*, 54, *59*, *95*, *105*, *155*, *165–168*, *171*, *175*, *201*

data.frame_export, 55
DataRow *(LabelRow)*, 86
DataRow(), *81*, *131*
DataRow-class *(LabelRow)*, 86
default_hsep(), *185*, *188*
df_to_tt, 58
df_to_tt(), *56, 57*
dim,VTableNodeInfo-method *(nrow,VTableTree-method)*, 107
do_base_split, 59
drop_and_remove_levels *(split_funcs)*, 166
drop_facet_levels, 60
drop_facet_levels(), *7*, *95*, *97*, *130*, *191*
drop_split_levels *(split_funcs)*, 166

ElementaryTable *(ElementaryTable-class)*, 61
ElementaryTable-class, 61
EmptyAllSplit *(EmptyColInfo)*, 64
EmptyColInfo, 64
EmptyElTable *(EmptyColInfo)*, 64
EmptyRootSplit *(EmptyColInfo)*, 64
export_as_tsv, 64

facet_colcount, 65
facet_colcount(), *46*
facet_colcount,InstantiatedColumnInfo-method *(facet_colcount)*, 65
facet_colcount,LayoutColLeaf-method *(facet_colcount)*, 65
facet_colcount,LayoutColTree-method *(facet_colcount)*, 65
facet_colcount,VTableTree-method *(facet_colcount)*, 65
facet_colcount<- *(facet_colcount)*, 65
facet_colcount<-,InstantiatedColumnInfo-method *(facet_colcount)*, 65
facet_colcount<-,LayoutColLeaf-method *(facet_colcount)*, 65
facet_colcount<-,LayoutColTree-method *(facet_colcount)*, 65
facet_colcount<-,VTableTree-method *(facet_colcount)*, 65
facet_colcounts_visible<-, 67
find_degen_struct, 68
find_degen_struct(), *142*, *198*
fnotes_at_path<- *(row_footnotes)*, 133
font_spec(), *114*, *117*, *189*
format_rcell, 68
formatters::format_value(), *31*, *36*, *42*, *57*, *63*, *68, 69*, *71*, *103*, *127*
formatters::list_valid_aligns(), *42*, *77*, *127*
formatters::list_valid_format_labels(), *5*, *16, 17*, *21*, *31*, *41*, *51*, *62*, *87*, *127*, *131*, *137–139*, *155*, *161*, *171*, *175*, *182*
formatters::main_footer(), *30, 31*, *63*, *123*, *125*
formatters::main_title(), *30*, *63*, *123*, *125*
formatters::make_row_df(), *57*, *150, 151*
formatters::obj_label(), *150*
formatters::obj_name(), *150*
formatters::prov_footer(), *30, 31*, *63*, *123*, *125*
formatters::set_default_hsep(), *36*, *63*, *140*
formatters::subtitles(), *30, 31*, *63*, *123*, *125*
formatters::table_inset(), *52*, *137, 138*, *140*
formatters_methods *(obj_name,VNodeInfo-method)*, 109

gen_args(), *52*, *147*
get_anchor_dfs *(get_full_lyt_df)*, 71
get_cell_aligns *(get_formatted_cells)*, 70
get_cell_aligns,ElementaryTable-method *(get_formatted_cells)*, 70

get_cell_aligns,LabelRow-method
(get_formatted_cells), 70
get_cell_aligns,TableRow-method
(get_formatted_cells), 70
get_cell_aligns,TableTree-method
(get_formatted_cells), 70
get_formatted_cells, 70
get_formatted_cells,ElementaryTable-method
(get_formatted_cells), 70
get_formatted_cells,LabelRow-method
(get_formatted_cells), 70
get_formatted_cells,TableRow-method
(get_formatted_cells), 70
get_formatted_cells,TableTree-method
(get_formatted_cells), 70
get_full_lyt_df, 71
get_full_lyt_df,PreDataColLayout-method
(get_full_lyt_df), 71
get_full_lyt_df,PreDataRowLayout-method
(get_full_lyt_df), 71
get_full_lyt_df,PreDataTableLayouts-method
(get_full_lyt_df), 71
get_full_lyt_df,Split-method
(get_full_lyt_df), 71
get_full_lyt_df,SplitVector-method
(get_full_lyt_df), 71
get_full_lyt_df,SplitVectorTree-method
(get_full_lyt_df), 71
get_full_lyt_df,VTableNodeInfo-method
(get_full_lyt_df), 71
get_layout_dfs (get_full_lyt_df), 71
get_row_anchor_df (get_full_lyt_df), 71
get_row_anchor_list (get_full_lyt_df),
71

head, 75
head,VTableTree-method (head), 75
header_section_div (section_div), 143
header_section_div(), *31*, *63*
header_section_div,PreDataTableLayouts-method
(section_div), 143
header_section_div,VTableTree-method
(section_div), 143
header_section_div<- (section_div), 143
header_section_div<-,PreDataTableLayouts-method
(section_div), 143
header_section_div<-,VTableTree-method
(section_div), 143
horizontal_sep, 76
horizontal_sep,VTableTree-method
(horizontal_sep), 76
horizontal_sep<- (horizontal_sep), 76
horizontal_sep<-,TableRow-method
(horizontal_sep), 76
horizontal_sep<-,VTableTree-method
(horizontal_sep), 76

import_from_tsv (export_as_tsv), 64
in_rows, 77
in_rows(), *37*, *148*
indent, 79
indent_string, 80
insert_row_at_path, 80
insert_row_at_path(), *82*
insert_row_at_path,VTableTree,ANY-method
(insert_row_at_path), 80
insert_row_at_path,VTableTree,DataRow-method
(insert_row_at_path), 80
insert_rrow, 82
InstantiatedColumnInfo
(InstantiatedColumnInfo-class),
83
InstantiatedColumnInfo-class, 83
is_rtable, 84

keep_split_levels (split_funcs), 166
keep_split_levels(), *191*

label_at_path, 85
label_at_path(), *82*
label_at_path<- (label_at_path), 85
LabelRow, 86
LabelRow(), *131*
LabelRow-class (LabelRow), 86
length(), *148*
length,CellValue-method, 88
list_wrap_df (list_wrap_x), 89
list_wrap_x, 89
low_obs_pruner (all_zero_or_na), 13
lyt_args(), *52*, *147*

main_footer,TableRow-method
(obj_name,VNodeInfo-method),
109
main_footer,VTitleFooter-method
(obj_name,VNodeInfo-method),
109

main_footer<-,VTitleFooter-method
(obj_name,VNodeInfo-method), 109
main_title,TableRow-method
(obj_name,VNodeInfo-method), 109
main_title,VTitleFooter-method
(obj_name,VNodeInfo-method), 109
main_title<-,VTitleFooter-method
(obj_name,VNodeInfo-method), 109
make_afun, 90
make_afun(), *19*
make_col_df, 93
make_row_df,LabelRow-method
(obj_name,VNodeInfo-method), 109
make_row_df,TableRow-method
(obj_name,VNodeInfo-method), 109
make_row_df,VTableTree-method
(obj_name,VNodeInfo-method), 109
make_split_fun, 94, *154*
make_split_fun(), *6*, *7*, *55*, *60*, *97*, *130*, *167*, *168*, *191*
make_split_result, 96
make_split_result(), *7*, *60*, *95*, *130*, *191*
make_static_cut_split
(VarStaticCutSplit-class), 205
make_subset_expr, 98
make_subset_expr,AllSplit-method
(make_subset_expr), 98
make_subset_expr,AnalyzeColVarSplit-method
(make_subset_expr), 98
make_subset_expr,AnalyzeVarSplit-method
(make_subset_expr), 98
make_subset_expr,character-method
(make_subset_expr), 98
make_subset_expr,CumulativeCutSplit-method
(make_subset_expr), 98
make_subset_expr,expression-method
(make_subset_expr), 98
make_subset_expr,MultiVarSplit-method
(make_subset_expr), 98
make_subset_expr,VarLevelSplit-method
(make_subset_expr), 98
make_subset_expr,VarStaticCutSplit-method
(make_subset_expr), 98
manual_cols, 99
ManualSplit, 100
matrix_form,VTableTree-method, 102
mean(), *148*
MultiVarSplit, 104

names,InstantiatedColumnInfo-method
(names,VTableNodeInfo-method), 106
names,LayoutColTree-method
(names,VTableNodeInfo-method), 106
names,VTableNodeInfo-method, 106
ncol,VTableNodeInfo-method
(nrow,VTableTree-method), 107
nlines,InstantiatedColumnInfo-method
(obj_name,VNodeInfo-method), 109
nlines,LabelRow-method
(obj_name,VNodeInfo-method), 109
nlines,RefFootnote-method
(obj_name,VNodeInfo-method), 109
nlines,TableRow-method
(obj_name,VNodeInfo-method), 109
no_colinfo, 107
no_colinfo,InstantiatedColumnInfo-method
(no_colinfo), 107
no_colinfo,VTableNodeInfo-method
(no_colinfo), 107
non_ref_rcell (rcell), 126
nrow,VTableTree-method, 107

obj_avar, 108
obj_avar,ElementaryTable-method
(obj_avar), 108
obj_avar,TableRow-method (obj_avar), 108
obj_format,CellValue-method
(obj_name,VNodeInfo-method), 109
obj_format,RowsVerticalSection-method
(obj_name,VNodeInfo-method), 109
obj_format,Split-method
(obj_name,VNodeInfo-method),

109
obj_format,VTableNodeInfo-method
(obj_name,VNodeInfo-method), 109
obj_format<-,CellValue-method
(obj_name,VNodeInfo-method), 109
obj_format<-,RowsVerticalSection-method
(obj_name,VNodeInfo-method), 109
obj_format<-,Split-method
(obj_name,VNodeInfo-method), 109
obj_format<-,VTableNodeInfo-method
(obj_name,VNodeInfo-method), 109
obj_label,Split-method
(obj_name,VNodeInfo-method), 109
obj_label,TableRow-method
(obj_name,VNodeInfo-method), 109
obj_label,ValueWrapper-method
(obj_name,VNodeInfo-method), 109
obj_label,VTableTree-method
(obj_name,VNodeInfo-method), 109
obj_label<-,Split-method
(obj_name,VNodeInfo-method), 109
obj_label<-,TableRow-method
(obj_name,VNodeInfo-method), 109
obj_label<-,ValueWrapper-method
(obj_name,VNodeInfo-method), 109
obj_label<-,VTableTree-method
(obj_name,VNodeInfo-method), 109
obj_na_str,Split-method
(obj_name,VNodeInfo-method), 109
obj_name,Split-method
(obj_name,VNodeInfo-method), 109
obj_name,VNodeInfo-method, 109
obj_name<-,Split-method
(obj_name,VNodeInfo-method), 109
obj_name<-,VNodeInfo-method
(obj_name,VNodeInfo-method), 109
obj_round_type,ANY-method
(obj_name,VNodeInfo-method), 109
obj_round_type,CellValue-method
(obj_name,VNodeInfo-method), 109
obj_round_type,PreDataTableLayouts-method
(obj_name,VNodeInfo-method), 109
obj_round_type,TableRow-method
(obj_name,VNodeInfo-method), 109
obj_round_type,VTableTree-method
(obj_name,VNodeInfo-method), 109
obj_round_type<-,CellValue-method
(obj_name,VNodeInfo-method), 109
obj_round_type<-,LabelRow-method
(obj_name,VNodeInfo-method), 109
obj_round_type<-,TableRow-method
(obj_name,VNodeInfo-method), 109
obj_round_type<-,VTableTree-method
(obj_name,VNodeInfo-method), 109

pag_tt_indices, 116
page_types, *117*
paginate_table *(*pag_tt_indices*)*, 116
path_enriched_df *(*data.frame_export*)*, 55
path_enriched_df(), *64*, *65*
pathing *(*tt_row_path_exists*)*, 194
prov_footer,TableRow-method
(obj_name,VNodeInfo-method), 109
prov_footer,VTitleFooter-method
(obj_name,VNodeInfo-method), 109
prov_footer<-,VTitleFooter-method
(obj_name,VNodeInfo-method), 109
prune_empty_level *(*all_zero_or_na*)*, 13

prune_empty_level(), *121*
prune_table, 120
prune_table(), *14*, *192*, *193*
prune_zeros_only *(*all_zero_or_na*)*, 13

qtable *(*qtable_layout*)*, 122
qtable_layout, 122

rbind *(*rbindl_rtables*)*, 124
rbind,VTableNodeInfo-method *(*rbindl_rtables*)*, 124
rbind2,VTableNodeInfo,ANY-method *(*rbindl_rtables*)*, 124
rbindl_rtables, 124
rcell, 126
ref_index *(*row_footnotes*)*, 133
ref_index<- *(*row_footnotes*)*, 133
ref_msg *(*row_footnotes*)*, 133
ref_symbol *(*row_footnotes*)*, 133
ref_symbol<- *(*row_footnotes*)*, 133
RefFootnote, 128
remove_split_levels *(*split_funcs*)*, 166
reorder_split_levels *(*split_funcs*)*, 166
restrict_facets, 129
restrict_facets(), *7*, *60*, *95*, *97*, *191*
rheader, 131
rheader(), *137*, *138*, *140*
rm_all_colcounts, 132
rm_all_colcounts,InstantiatedColumnInfo-method *(*rm_all_colcounts*)*, 132
rm_all_colcounts,LayoutColLeaf-method *(*rm_all_colcounts*)*, 132
rm_all_colcounts,LayoutColTree-method *(*rm_all_colcounts*)*, 132
rm_all_colcounts,VTableTree-method *(*rm_all_colcounts*)*, 132
round_fmt(), *28*, *87*, *137*, *138*, *140*, *189*
row.names,VTableTree-method *(*names,VTableNodeInfo-method*)*, 106
row_cells *(*obj_avar*)*, 108
row_cells,RowsVerticalSection-method *(*obj_avar*)*, 108
row_cells,TableRow-method *(*obj_avar*)*, 108
row_cells<- *(*obj_avar*)*, 108
row_cells<-,TableRow-method *(*obj_avar*)*, 108
row_footnotes, 133
row_footnotes<- *(*row_footnotes*)*, 133
row_paths, 135
row_paths(), *85*, *134*
row_paths_summary, 136
row_paths_summary(), *134*, *135*, *150*
row_values *(*obj_avar*)*, 108
row_values,TableRow-method *(*obj_avar*)*, 108
row_values<- *(*obj_avar*)*, 108
row_values<-,LabelRow-method *(*obj_avar*)*, 108
row_values<-,TableRow-method *(*obj_avar*)*, 108
rrow, 137
rrow(), *51*, *81*, *131*, *137*, *138*, *140*
rrowl, 138
rrowl(), *131*, *137*, *140*
rtable, 139
rtable(), *131*, *137*, *138*
rtablel *(*rtable*)*, 139

sanitize_table_struct, 142
sanitize_table_struct(), *68*, *198*
section_div, *31*, 143
section_div(), *31*, *63*
section_div,list-method *(*section_div*)*, 143
section_div,TableRow-method *(*section_div*)*, 143
section_div,VTableTree-method *(*section_div*)*, 143
section_div<- *(*section_div*)*, 143
section_div<-,TableRow-method *(*section_div*)*, 143
section_div<-,VTableTree-method *(*section_div*)*, 143
section_div_at_path *(*section_div*)*, 143
section_div_at_path<- *(*section_div*)*, 143
section_div_info *(*section_div*)*, 143
select_all_levels *(*add_overall_level*)*, 9
sf_args, 147
sf_args(), *52*
simple_analysis, 148
simple_analysis,ANY-method *(*simple_analysis*)*, 148
simple_analysis,factor-method *(*simple_analysis*)*, 148
simple_analysis,logical-method *(*simple_analysis*)*, 148

simple_analysis,numeric-method
(simple_analysis), 148
sort_at_path, 149
sort_at_path(), *33*, *52*
spl_context, *12*, 152
spl_context_to_disp_path, 153
spl_variable, 154
spl_variable,Split-method
(spl_variable), 154
spl_variable,VarDynCutSplit-method
(spl_variable), 154
spl_variable,VarLevelSplit-method
(spl_variable), 154
spl_variable,VarStaticCutSplit-method
(spl_variable), 154
split_cols_by, 155
split_cols_by(), *154*
split_cols_by_cutfun
(split_cols_by_cuts), 158
split_cols_by_cutfun(), *154*
split_cols_by_cuts, 158
split_cols_by_cuts(), *154*
split_cols_by_multivar, 164
split_cols_by_multivar(), *22*, *177*
split_cols_by_quartiles
(split_cols_by_cuts), 158
split_exargs(), *178*
split_funcs, *10*, *55*, 166
split_rows_by, 170
split_rows_by(), *13*, *14*, *143*, *152*, *154*, *177*
split_rows_by_cutfun
(split_cols_by_cuts), 158
split_rows_by_cutfun(), *154*
split_rows_by_cuts
(split_cols_by_cuts), 158
split_rows_by_cuts(), *154*
split_rows_by_multivar, 174
split_rows_by_quartiles
(split_cols_by_cuts), 158
SplitValue, 177
SplitValue(), *178*, *199*
splv_extra, 178
splv_extra(), *177*
splv_extra,SplitValue-method
(splv_extra), 178
splv_extra<- (splv_extra), 178
splv_extra<-,SplitValue-method
(splv_extra), 178
subset_cols, 179
subset_cols,ANY,character-method
(subset_cols), 179
subset_cols,ElementaryTable,numeric-method
(subset_cols), 179
subset_cols,InstantiatedColumnInfo,numeric-method
(subset_cols), 179
subset_cols,LabelRow,numeric-method
(subset_cols), 179
subset_cols,LayoutColTree,numeric-method
(subset_cols), 179
subset_cols,TableRow,numeric-method
(subset_cols), 179
subset_cols,TableTree,numeric-method
(subset_cols), 179
subtitles,TableRow-method
(obj_name,VNodeInfo-method),
109
subtitles,VTitleFooter-method
(obj_name,VNodeInfo-method),
109
subtitles<-,VTitleFooter-method
(obj_name,VNodeInfo-method),
109
sum(), *148*
summarize_row_groups, 182
summarize_row_groups(), *12*, *33*, *150*, *152*

table_inset,PreDataTableLayouts-method
(obj_name,VNodeInfo-method),
109
table_inset,VTableNodeInfo-method
(obj_name,VNodeInfo-method),
109
table_inset<-,InstantiatedColumnInfo-method
(obj_name,VNodeInfo-method),
109
table_inset<-,PreDataTableLayouts-method
(obj_name,VNodeInfo-method),
109
table_inset<-,VTableNodeInfo-method
(obj_name,VNodeInfo-method),
109
table_shell, 184
table_shell(), *200*
table_shell_str (table_shell), 184
table_shell_str(), *200*
table_structure, 186
table_structure(), *150*, *151*

TableTree *(ElementaryTable-class)*, 61
TableTree-class *(ElementaryTable-class)*, 61
tail *(head)*, 75
tail,VTableTree-method *(head)*, 75
top_left, 187
top_left(), *27*
top_left,InstantiatedColumnInfo-method *(top_left)*, 187
top_left,PreDataTableLayouts-method *(top_left)*, 187
top_left,VTableTree-method *(top_left)*, 187
top_left<- *(top_left)*, 187
top_left<-,InstantiatedColumnInfo-method *(top_left)*, 187
top_left<-,PreDataTableLayouts-method *(top_left)*, 187
top_left<-,VTableTree-method *(top_left)*, 187
top_level_section_div *(section_div)*, 143
top_level_section_div,PreDataTableLayouts-method *(section_div)*, 143
top_level_section_div<- *(section_div)*, 143
top_level_section_div<-,PreDataTableLayouts-method *(section_div)*, 143
tostring *(toString,VTableTree-method)*, 188
toString,VTableTree-method, 188
tree_children, 190
tree_children(), *150*
tree_children<- *(tree_children)*, 190
trim_levels_in_facets, 190
trim_levels_in_facets(), *7*, *60*, *95*, *97*, *130*
trim_levels_in_group *(split_funcs)*, 166
trim_levels_in_group(), *191*
trim_levels_to_map, 191
trim_levels_to_map(), *166*, *168*
trim_rows, 192
trim_rows(), *14*
tt_at_path, 193
tt_at_path(), *151*
tt_at_path<- *(tt_at_path)*, 193
tt_normalize_row_path *(tt_row_path_exists)*, 194
tt_row_path_exists, 194
update_ref_indexing, 197
utils::write.table(), *65*

validate_table_struct, 197
validate_table_struct(), *68*, *142*
value_at *(cell_values)*, 39
value_at,VTableTree-method *(cell_values)*, 39
value_expr, 198
value_expr(), *177*
value_expr,ANY-method *(value_expr)*, 198
value_expr,ValueWrapper-method *(value_expr)*, 198
value_formats, 199
value_formats(), *185*
value_formats,ANY-method *(value_formats)*, 199
value_formats,LabelRow-method *(value_formats)*, 199
value_formats,TableRow-method *(value_formats)*, 199
value_formats,VTableTree-method *(value_formats)*, 199
VarDynCutSplit *(VarStaticCutSplit-class)*, 205
VarDynCutSplit(), *208*
VarDynCutSplit-class *(VarStaticCutSplit-class)*, 205
VarLevelSplit *(VarLevelSplit-class)*, 200
VarLevelSplit-class, 200
VarLevWBaselineSplit *(VarLevelSplit-class)*, 200
vars_in_layout, 203
vars_in_layout,CompoundSplit-method *(vars_in_layout)*, 203
vars_in_layout,ManualSplit-method *(vars_in_layout)*, 203
vars_in_layout,PreDataAxisLayout-method *(vars_in_layout)*, 203
vars_in_layout,PreDataTableLayouts-method *(vars_in_layout)*, 203
vars_in_layout,Split-method *(vars_in_layout)*, 203
vars_in_layout,SplitVector-method *(vars_in_layout)*, 203
vars_in_layout,SplitVectorTree-method *(vars_in_layout)*, 203
VarStaticCutSplit-class, 205
Viewer, 208

wrap_string(), *189*