Package: teal.transform (via r-universe)

October 28, 2026

Title Functions for Extracting and Merging Data in the 'teal' Framework

Version 0.7.2.9001

Date 2026-06-26

Description A standardized user interface for column selection, that facilitates dataset merging in 'teal' framework.

License Apache License 2.0

URL https://pharmaverse.github.io/teal.transform/, https://github.com/pharmaverse/teal.transform/

BugReports https://github.com/pharmaverse/teal.transform/issues

Depends R (>= 3.6)

Imports checkmate (>= 2.1.0), dplyr (>= 1.1.0), htmltools, logger (>= 0.2.0), methods, rlang (>= 1.0.0), shiny (>= 1.6.0), shinyjs (>= 2.1.0), shinyvalidate (>= 0.1.3), stats, teal.data (>= 0.8.0), teal.logger (>= 0.4.0), teal.widgets (>= 0.5.0), tidyr (>= 1.0.0), tidyselect (>= 1.2.1), utils

Suggests bslib (>= 0.8.0), knitr (>= 1.42), rmarkdown (>= 2.23), roxy.shinylive (>= 1.0.0), testthat (>= 3.1.5), withr (>= 2.0.0)

VignetteBuilder knitr, rmarkdown

Config/Needs/verdepcheck mllg/checkmate, tidyverse/dplyr, daroczig/logger, r-lib/rlang, rstudio/shiny, daattali/shinyjs, rstudio/shinyvalidate, pharmaverse/teal.data, pharmaverse/teal.logger, pharmaverse/teal.widgets, tidyverse/tidyr, r-lib/tidyselect, yihui/knitr, rstudio/rmarkdown, r-lib/testthat, r-lib/withr

Config/Needs/website insightsengineering/nesttemplate

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE)

Config/roxygen2/version 8.1.1

Config/pak/sysreqs cmake make libicu-dev libuv1-dev libxml2-dev libssl-dev libnode-dev zlib1g-dev

Repository https://pharmaverse.r-universe.dev

Date/Publication 2026-10-28 08:39:49 UTC

RemoteUrl https://github.com/insightsengineering/teal.transform

RemoteRef HEAD

RemoteSha 1ef30de92dc2f8af1fcd6894d07b91c514bad0ee

Contents

add_no_selected_choices . . . 3
check_no_multiple_selection . . . 3
choices_labeled . . . 4
choices_selected . . . 5
compose_and_enable_validators . . . 8
data_extract_multiple_srv . . . 10
data_extract_spec . . . 14
data_extract_srv . . . 16
data_extract_ui . . . 19
datanames_input . . . 21
delayed_choices . . . 21
filter_spec . . . 23
format_data_extract . . . 25
get_anl_relabel_call . . . 26
get_dataset_prefixed_col_names . . . 27
get_extract_datanames . . . 27
get_merge_call . . . 28
get_relabel_call . . . 29
is_single_dataset . . . 29
list_extract_spec . . . 30
merge_datasets . . . 30
merge_expression_module . . . 32
merge_expression_srv . . . 36
no_selected_as_NULL . . . 39
resolve_delayed . . . 40
select_spec . . . 42
split_by_sep . . . 44
value_choices . . . 45
variable_choices . . . 46

Index **48**

add_no_selected_choices *Add empty choice to choices selected*

Description

Add empty choice to choices selected

Usage

```
add_no_selected_choices(x, multiple = FALSE)
```

Arguments

x	(choices_selected) object.
multiple	(logical(1)) whether multiple selections are allowed or not.

Value

choices_selected object with an empty option added to the choices.

check_no_multiple_selection *Checks that the* extract_input *specification does not allow multiple selection*

Description

Stops if condition not met.

Usage

```
check_no_multiple_selection(extract_input)
```

Arguments

extract_input	(list or NULL) a list of data_extract_spec

Value

Raises an error when check fails, otherwise, it returns NULL, invisibly.

choices_labeled *Set "<choice>:<label>" type of names*

Description

This is often useful for `choices_selected()` as it marks up the drop-down boxes for `shiny::selectInput()`.

Usage

```
choices_labeled(choices, labels, subset = NULL, types = NULL)

## S3 method for class 'choices_labeled'
print(x, ...)
```

Arguments

choices	(character or factor or numeric or logical) vector.
labels	(character) vector containing labels to be applied to choices. If NA then "Label Missing" will be used.
subset	(character or factor or numeric or logical) vector that is a subset of choices. This is useful if only a few variables need to be named. If this argument is used, the returned vector will match its order.
types	(character) vector containing the types of the columns to be used for applying the appropriate icons to the choices_selected drop down box (e.g. "numeric").
x	an object used to select a method.
...	further arguments passed to or from other methods.

Details

If either choices or labels are factors, they are coerced to character. Duplicated elements from choices get removed.

Value

Named character vector.

Methods (by generic)

- print(choices_labeled): Print choices_labeled object

Examples

```
library(teal.data)
library(shiny)

ADSL <- rADSL
ADTTE <- rADTTE

choices1 <- choices_labeled(names(ADSL), col_labels(ADSL, fill = FALSE))
choices2 <- choices_labeled(ADTTE$PARAMCD, ADTTE$PARAM)

# if only a subset of variables are needed, use subset argument
choices3 <- choices_labeled(
  names(ADSL),
  col_labels(ADSL, fill = FALSE),
  subset = c("ARMCD", "ARM")
)

ui <- bslib::page_fluid(
  selectInput("c1",
    label = "Choices from ADSL",
    choices = choices1,
    selected = choices1[1]
  ),
  selectInput("c2",
    label = "Choices from ADTTE",
    choices = choices2,
    selected = choices2[1]
  ),
  selectInput("c3",
    label = "Arm choices from ADSL",
    choices = choices3,
    selected = choices3[1]
  )
)
server <- function(input, output) {}

if (interactive()) {
  shinyApp(ui, server)
}
```

---

choices_selected *Choices selected*

Description

Construct a single list containing available choices, the default selected value, and additional settings such as to order the choices with the selected elements appearing first or whether to block the user from making selections.

Can be used in UI input elements such as `teal.widgets::optionalSelectInput()`.

Usage

```
choices_selected(
  choices,
  selected = if (inherits(choices, "delayed_data")) NULL else choices[1],
  keep_order = FALSE,
  fixed = FALSE
)

is.choices_selected(x)
```

Arguments

choices	(character) vector of possible choices or delayed_data object. See variable_choices() and value_choices().
selected	(character) vector of preselected options, (delayed_choices) object or (delayed_data) object. If delayed_data object then choices must also be delayed_data object. If not supplied it will default to the first element of choices if choices is a vector, or NULL if choices is a delayed_data object.
keep_order	(logical) In case of FALSE the selected variables will be on top of the drop-down field.
fixed	(logical) optional, whether to block user to select choices.
x	(choices_selected) object to check.

Details

Please note that the order of selected will always follow the order of choices. The keep_order argument is set to false which will run the following code inside:

```
choices <- c(selected, setdiff(choices, selected))
```

In case you want to keep your specific order of choices, set keep_order to TRUE.

Value

choices_selected returns list of choices_selected, encapsulating the specified choices, selected, keep_order and fixed.

is.choices_selected returns TRUE if x inherits from a choices_selected object, FALSE otherwise.

Functions

- is.choices_selected(): Check if an object is a choices_selected class

Examples

```
library(shiny)
library(teal.widgets)

ADSL <- teal.data::rADSL
choices_selected(variable_choices(ADSL), "SEX")

# How to select nothing
# use an empty character
choices_selected(
  choices = c("", "A", "B", "C"),
  selected = ""
)

# How to allow the user to select nothing
# use an empty character
choices_selected(
  choices = c("A", "", "B", "C"),
  selected = "A"
)


# How to make Nothing the Xth choice
# just use keep_order
choices_selected(
  choices = c("A", "", "B", "C"),
  selected = "A",
  keep_order = TRUE
)


# How to give labels to selections
# by adding names - choices will be replaced by "name" in UI, not in code
choices_selected(
 choices = c("name for A" = "A", "Name for nothing" = "", "name for b" = "B", "name for C" = "C"),
  selected = "A"
)

# by using choices_labeled
# labels will be shown behind the choice
choices_selected(
  choices = choices_labeled(
    c("A", "", "B", "C"),
    c("name for A", "nothing", "name for B", "name for C")
  ),
  selected = "A"
)

# Passing a `delayed_data` object to `selected`
choices_selected(
  choices = variable_choices("ADSL"),
  selected = variable_choices("ADSL", subset = c("STUDYID"))
```

```
)

# Passing `delayed_choices` object - semantically identical objects:
choices_selected(choices = letters, selected = letters)
choices_selected(choices = letters, selected = all_choices())

choices_selected(
  choices = setNames(LETTERS[1:5], paste("Letter", LETTERS[1:5])),
  selected = "E"
)
choices_selected(
  choices = setNames(LETTERS[1:5], paste("Letter", LETTERS[1:5])),
  selected = last_choice()
)

# functional form (subsetting for factor variables only) of choices_selected
# with delayed data loading
choices_selected(variable_choices("ADSL", subset = function(data) {
  idx <- vapply(data, is.factor, logical(1))
  names(data)[idx]
}))

cs <- choices_selected(
  choices = c("A", "B", "C"),
  selected = "A"
)

ui <- bslib::page_fluid(
  optionalSelectInput(
    inputId = "id",
    choices = cs$choices,
    selected = cs$selected
  )
)

server <- function(input, output, session) {}
if (interactive()) {
  shinyApp(ui, server)
}
```

`compose_and_enable_validators` *Function to compose* `validators` *from* `data_extract_multiple_srv`

Description

This function takes the output from `data_extract_multiple_srv` and collates the `shinyvalidate::InputValidators` returned into a single `validator` and enables this.

Usage

```
compose_and_enable_validators(iv, selector_list, validator_names = NULL)
```

Arguments

iv	(shinyvalidate::InputValidator) A validator.
selector_list	(reactive named list of reactives). Typically this is the output from data_extract_multiple_srv. The validators in this list (specifically selector_list()[[validator_names]]()iv) will be added into iv.
validator_names	(character or NULL). If character then only validators in the elements of selector_list() whose name is in this list will be added. If NULL all validators will be added

Value

(shinyvalidate::InputValidator) enabled iv with appropriate validators added into it.

Examples

```
library(shiny)
library(shinyvalidate)
library(shinyjs)
library(teal.widgets)

iris_extract <- data_extract_spec(
  dataname = "iris",
  select = select_spec(
    label = "Select variable:",
    choices = variable_choices(iris, colnames(iris)),
    selected = "Sepal.Length",
    multiple = TRUE,
    fixed = FALSE
  )
)

data_list <- list(iris = reactive(iris))

ui <- bslib::page_fluid(
  useShinyjs(),
  bslib::layout_sidebar(
    verbatimTextOutput("out1"),
    sidebar = tagList(
      data_extract_ui(
        id = "x_var",
        label = "Please select an X column",
        data_extract_spec = iris_extract
      ),
      data_extract_ui(
        id = "y_var",
        label = "Please select a Y column",
```

```
        data_extract_spec = iris_extract
      ),
      data_extract_ui(
        id = "col_var",
        label = "Please select a color column",
        data_extract_spec = iris_extract
      )
    )
  )
)

server <- function(input, output, session) {
  selector_list <- data_extract_multiple_srv(
    list(x_var = iris_extract, y_var = iris_extract, col_var = iris_extract),
    datasets = data_list,
    select_validation_rule = list(
      x_var = sv_required("Please select an X column"),
      y_var = compose_rules(
        sv_required("Exactly 2 'Y' column variables must be chosen"),
        function(x) if (length(x) != 2) "Exactly 2 'Y' column variables must be chosen"
      )
    )
  )
  iv_r <- reactive({
    iv <- InputValidator$new()
    compose_and_enable_validators(
      iv,
      selector_list,
      # if validator_names = NULL then all validators are used
      # to turn on only "x_var" then set this argument to "x_var"
      validator_names = NULL
    )
  })

  output$out1 <- renderPrint({
    if (iv_r()$is_valid()) {
      ans <- lapply(selector_list(), function(x) {
        cat(format_data_extract(x()), "\n\n")
      })
    } else {
      "Check that you have made a valid selection"
    }
  })
}

if (interactive()) {
  shinyApp(ui, server)
}
```

data_extract_multiple_srv *Creates a named list of* data_extract_srv *output*

Description

data_extract_multiple_srv loops over the list of data_extract given and runs data_extract_srv for each one returning a list of reactive objects.

Usage

```
data_extract_multiple_srv(data_extract, datasets, ...)

## S3 method for class 'reactive'
data_extract_multiple_srv(data_extract, datasets, ...)

## S3 method for class 'FilteredData'
data_extract_multiple_srv(data_extract, datasets, ...)

## S3 method for class 'list'
data_extract_multiple_srv(
  data_extract,
  datasets,
  join_keys = NULL,
  select_validation_rule = NULL,
  filter_validation_rule = NULL,
  dataset_validation_rule = if (is.null(select_validation_rule) &&
    is.null(filter_validation_rule)) {
     NULL
 } else {

    shinyvalidate::sv_required("Please select a dataset")
 },
  ...
)
```

Arguments

data_extract	(named list of data_extract_spec objects) the list data_extract_spec objects. The names of the elements in the list need to correspond to the ids passed to data_extract_ui. See example for details.
datasets	(FilteredData or list of reactive or non-reactive data.frame) object containing data either in the form of FilteredData or as a list of data.frame. When passing a list of non-reactive data.frame objects, they are converted to reactive data.frames internally. When passing a list of reactive or non-reactive data.frame objects, the argument join_keys is required also.

`...` An additional argument `join_keys` is required when `datasets` is a list of `data.frame`. It shall contain the keys per dataset in `datasets`.

`join_keys` (`join_keys` or `NULL`) of join keys per dataset in `datasets`.

`select_validation_rule`
(`NULL` or `function` or named `list` of `function`) Should there be any `shinyvalidate` input validation of the select parts of the `data_extract_ui`. If all `data_extract` require the same validation function then this can be used directly (i.e. `select_validation_rule = shinyvalidate::sv_required()`).

For more fine-grained control use a list:

`select_validation_rule = list(extract_1 = sv_required(), extract2 = ~ if (length(.) > 2) "Error")`

If `NULL` then no validation will be added.

See example for more details.

`filter_validation_rule`
(`NULL` or `function` or named `list` of `function`) Same as `select_validation_rule` but for the filter (values) part of the `data_extract_ui`.

`dataset_validation_rule`
(`NULL` or `function` or named `list` of `function`) Same as `select_validation_rule` but for the choose dataset part of the `data_extract_ui`

Value

reactive named `list` containing outputs from `data_extract_srv()`. Output list names are the same as `data_extract` input argument.

Examples

```
library(shiny)
library(shinyvalidate)
library(shinyjs)
library(teal.widgets)

iris_select <- data_extract_spec(
  dataname = "iris",
  select = select_spec(
    label = "Select variable:",
    choices = variable_choices(iris, colnames(iris)),
    selected = "Sepal.Length",
    multiple = TRUE,
    fixed = FALSE
  )
)

iris_filter <- data_extract_spec(
  dataname = "iris",
  filter = filter_spec(
    vars = "Species",
    choices = c("setosa", "versicolor", "virginica"),
    selected = "setosa",
```

```
    multiple = TRUE
  )
)

data_list <- list(iris = reactive(iris))

ui <- bslib::page_fluid(
  useShinyjs(),
  bslib::layout_sidebar(
    verbatimTextOutput("out1"),
    sidebar = tagList(
      data_extract_ui(
        id = "x_var",
        label = "Please select an X column",
        data_extract_spec = iris_select
      ),
      data_extract_ui(
        id = "species_var",
        label = "Please select 2 Species",
        data_extract_spec = iris_filter
      )
    )
  )
)

server <- function(input, output, session) {
  selector_list <- data_extract_multiple_srv(
    list(x_var = iris_select, species_var = iris_filter),
    datasets = data_list,
    select_validation_rule = list(
      x_var = sv_required("Please select an X column")
    ),
    filter_validation_rule = list(
      species_var = compose_rules(
        sv_required("Exactly 2 Species must be chosen"),
        function(x) if (length(x) != 2) "Exactly 2 Species must be chosen"
      )
    )
  )
  iv_r <- reactive({
    iv <- InputValidator$new()
    compose_and_enable_validators(
      iv,
      selector_list,
      validator_names = NULL
    )
  })

  output$out1 <- renderPrint({
    if (iv_r()$is_valid()) {
      ans <- lapply(selector_list(), function(x) {
        cat(format_data_extract(x()), "\n\n")
      })
```

```
    } else {
      "Please fix errors in your selection"
    }
  })
}

if (interactive()) {
  shinyApp(ui, server)
}
```

`data_extract_spec` *Data extract input for* `teal` *modules*

Description

The Data extract input can be used to filter and select columns from a data set. This function enables such an input in `teal`. Please use the constructor function data_extract_spec to set it up.

Usage

```
data_extract_spec(dataname, select = NULL, filter = NULL, reshape = FALSE)
```

Arguments

`dataname`	(`character`) The name of the dataset to be extracted.
`select`	(`NULL` or `select_spec`-S3 class or `delayed_select_spec`) Columns to be selected from the input dataset mentioned in `dataname`. The setup can be created using select_spec function.
`filter`	(`NULL` or `filter_spec` or its respective delayed version) Setup of the filtering of key columns inside the dataset. This setup can be created using the filter_spec function. Please note that if both select and filter are set to `NULL`, then the result will be a filter spec UI with all variables as possible choices and a select spec with multiple set to `TRUE`.
`reshape`	(`logical`) whether reshape long to wide. Note that it will be used only in case of long dataset with multiple keys selected in filter part.

Value

`data_extract_spec` object.

Module Development

`teal.transform` uses this object to construct a UI element in a module.

Note

No checks based on columns can be done because the data is only referred to by name.

References

select_spec filter_spec

Examples

```
adtte_filters <- filter_spec(
  vars = c("PARAMCD", "CNSR"),
  sep = "-",
  choices = c("OS-1" = "OS-1", "OS-0" = "OS-0", "PFS-1" = "PFS-1"),
  selected = "OS-1",
  multiple = FALSE,
  label = "Choose endpoint and Censor"
)

data_extract_spec(
  dataname = "ADTTE",
  filter = adtte_filters,
  select = select_spec(
    choices = c("AVAL", "BMRKR1", "AGE"),
    selected = c("AVAL", "BMRKR1"),
    multiple = TRUE,
    fixed = FALSE,
    label = "Column"
  )
)

data_extract_spec(
  dataname = "ADSL",
  filter = NULL,
  select = select_spec(
    choices = c("AGE", "SEX", "USUBJID"),
    selected = c("SEX"),
    multiple = FALSE,
    fixed = FALSE
  )
)
data_extract_spec(
  dataname = "ADSL",
  filter = filter_spec(
    vars = variable_choices("ADSL", subset = c("AGE"))
  )
)

dynamic_filter <- filter_spec(
  vars = choices_selected(variable_choices("ADSL"), "COUNTRY"),
  multiple = TRUE
)
data_extract_spec(
  dataname = "ADSL",
  filter = dynamic_filter
)
```

`data_extract_srv` *Extraction of the selector(s) details*

Description

Extracting details of the selection(s) in data_extract_ui elements.

Usage

```
data_extract_srv(id, datasets, data_extract_spec, ...)

## S3 method for class 'FilteredData'
data_extract_srv(id, datasets, data_extract_spec, ...)

## S3 method for class 'list'
data_extract_srv(
  id,
  datasets,
  data_extract_spec,
  join_keys = NULL,
  select_validation_rule = NULL,
  filter_validation_rule = NULL,
  dataset_validation_rule = if (is.null(select_validation_rule) &&
    is.null(filter_validation_rule)) {
     NULL
 } else {

    shinyvalidate::sv_required("Please select a dataset")
 },
  ...
)
```

Arguments

`id`	An ID string that corresponds with the ID used to call the module's UI function.
`datasets`	(`FilteredData` or `list` of `reactive` or non-`reactive` `data.frame`) object containing data either in the form of `FilteredData` or as a list of `data.frame`. When passing a list of non-reactive `data.frame` objects, they are converted to reactive `data.frames` internally. When passing a list of reactive or non-reactive `data.frame` objects, the argument `join_keys` is required also.
`data_extract_spec`	(`data_extract_spec` or a list of `data_extract_spec`) A list of data filter and select information constructed by data_extract_spec.
`...`	An additional argument `join_keys` is required when `datasets` is a list of `data.frame`. It shall contain the keys per dataset in `datasets`.
`join_keys`	(`join_keys` or `NULL`) of keys per dataset in `datasets`.

`select_validation_rule`
: (`NULL` or `function`) Should there be any `shinyvalidate` input validation of the select parts of the `data_extract_ui`.

  You can use a validation function directly (i.e. `select_validation_rule = shinyvalidate::sv_required()`) or for more fine-grained control use a function:

  `select_validation_rule = ~ if (length(.) > 2) "Error".`

  If `NULL` then no validation will be added. See example for more details.

`filter_validation_rule`
: (`NULL` or `function`) Same as `select_validation_rule` but for the filter (values) part of the `data_extract_ui`.

`dataset_validation_rule`
: (`NULL` or `function`) Same as `select_validation_rule` but for the choose dataset part of the `data_extract_ui`

Value

A reactive `list` containing following fields:

- `filters`: A list with the information on the filters that are applied to the data set.
- `select`: The variables that are selected from the dataset.
- `always_selected`: The column names from the data set that should always be selected.
- `reshape`: Whether reshape long to wide should be applied or not.
- `dataname`: The name of the data set.
- `internal_id`: The `id` of the corresponding shiny input element.
- `keys`: The names of the columns that can be used to merge the data set.
- `iv`: A `shinyvalidate::InputValidator` containing `validator` for this `data_extract`.

References

data_extract_srv

Examples

```
library(shiny)
library(shinyvalidate)
library(teal.data)
library(teal.widgets)

# Sample ADSL dataset
ADSL <- data.frame(
  STUDYID = "A",
  USUBJID = LETTERS[1:10],
  SEX = rep(c("F", "M"), 5),
  AGE = rpois(10, 30),
  BMRKR1 = rlnorm(10)
)
```

```
# Specification for data extraction
adsl_extract <- data_extract_spec(
  dataname = "ADSL",
  filter = filter_spec(vars = "SEX", choices = c("F", "M"), selected = "F"),
  select = select_spec(
    label = "Select variable:",
    choices = variable_choices(ADSL, c("AGE", "BMRKR1")),
    selected = "AGE",
    multiple = TRUE,
    fixed = FALSE
  )
)

# Using reactive list of data.frames
data_list <- list(ADSL = reactive(ADSL))

join_keys <- join_keys(join_key("ADSL", "ADSL", c("STUDYID", "USUBJID")))

# App: data extraction with validation
ui <- bslib::page_fluid(
  bslib::layout_sidebar(
    verbatimTextOutput("out1"),
    encoding = tagList(
      data_extract_ui(
        id = "adsl_var",
        label = "ADSL selection",
        data_extract_spec = adsl_extract
      )
    )
  )
)
server <- function(input, output, session) {
  adsl_reactive_input <- data_extract_srv(
    id = "adsl_var",
    datasets = data_list,
    data_extract_spec = adsl_extract,
    join_keys = join_keys,
    select_validation_rule = sv_required("Please select a variable.")
  )

  iv_r <- reactive({
    iv <- InputValidator$new()
    iv$add_validator(adsl_reactive_input()$iv)
    iv$enable()
    iv
  })

  output$out1 <- renderPrint({
    if (iv_r()$is_valid()) {
      cat(format_data_extract(adsl_reactive_input()))
    } else {
      "Please fix errors in your selection"
    }
```

```
  })
}

if (interactive()) {
  shinyApp(ui, server)
}

# App: simplified data extraction
ui <- bslib::page_fluid(
  bslib::layout_sidebar(
    verbatimTextOutput("out1"),
    sidebar = tagList(
      data_extract_ui(
        id = "adsl_var",
        label = "ADSL selection",
        data_extract_spec = adsl_extract
      )
    )
  )
)

server <- function(input, output, session) {
  adsl_reactive_input <- data_extract_srv(
    id = "adsl_var",
    datasets = data_list,
    data_extract_spec = adsl_extract
  )

  output$out1 <- renderPrint(adsl_reactive_input())
}

if (interactive()) {
  shinyApp(ui, server)
}
```

`data_extract_ui` `teal` *data extraction module user-interface*

Description

Data extraction module.

Usage

```
data_extract_ui(id, label, data_extract_spec, is_single_dataset = FALSE)
```

Arguments

`id`	(`character`) shiny input unique identifier.
`label`	(`character`) Label above the data extract input.

data_extract_spec
: (list of data_extract_spec) This is the outcome of listing data_extract_spec() constructor calls.

is_single_dataset
: (logical) FALSE to display the dataset widget.

Details

There are three inputs that will be rendered

1. Dataset select Optional. If more than one data_extract_spec is handed over to the function, a shiny shiny::selectInput will be rendered. Else just the name of the dataset is given.
2. Filter Panel Optional. If the data_extract_spec contains a filter element a shiny shiny::selectInput will be rendered with the options to filter the dataset.
3. Select panel A shiny shiny::selectInput to select columns from the dataset to go into the analysis.

The output can be analyzed using data_extract_srv(...).

This functionality should be used in the encoding panel of your teal app. It will allow app-developers to specify a data_extract_spec() object. This object should be used to teal module variables being filtered data from CDISC datasets.

You can use this function in the same way as any shiny module UI. The corresponding server module can be found in data_extract_srv().

Value

Shiny shiny::selectInputs that allow to define how to extract data from a specific dataset. The input elements will be returned inside a shiny::div container.

Examples

```
library(shiny)
library(teal.widgets)

adtte_filters <- filter_spec(
  vars = c("PARAMCD", "CNSR"),
  sep = "-",
  choices = c("OS-1" = "OS-1", "OS-0" = "OS-0", "PFS-1" = "PFS-1"),
  selected = "OS-1",
  multiple = FALSE,
  label = "Choose endpoint and Censor"
)

response_spec <- data_extract_spec(
  dataname = "ADTTE",
  filter = adtte_filters,
  select = select_spec(
    choices = c("AVAL", "BMRKR1", "AGE"),
    selected = c("AVAL", "BMRKR1"),
    multiple = TRUE,
```

```
    fixed = FALSE,
    label = "Column"
  )
)
# Call to use inside your teal module UI function
bslib::layout_sidebar(
  tableOutput("table"),
  sidebar = tags$div(
    data_extract_ui(
      id = "regressor",
      label = "Regressor Variable",
      data_extract_spec = response_spec
    )
  )
)
```

`datanames_input` *Help text with available datasets input*

Description

Creates `shiny::helpText()` with the names of available datasets for the current module.

Usage

```
datanames_input(data_extracts)
```

Arguments

`data_extracts`	(`list`) of data extracts for single variable.

Value

`shiny.tag` defining help-text element that can be added to a UI element.

`delayed_choices` *Bare constructor for* `delayed_choices` *object*

Description

Special S3 structures that delay selection of possible choices in a `filter_spec`, `select_spec` or `choices_selected` object.

Usage

```
all_choices()

first_choice()

last_choice()

first_choices(n)

last_choices(n)
```

Arguments

n	positive (integer-like) number of first/last items to subset to

Value

Object of class `delayed_data, delayed_choices`, which is a function that returns the appropriate subset of its argument. `all_choices`, `first_choices`, and `last_choices` structures also have an additional class for internal use.

Examples

```
# These pairs of structures represent semantically identical specifications:
choices_selected(choices = letters, selected = letters)
choices_selected(choices = letters, selected = all_choices())

choices_selected(choices = letters, selected = letters[1])
choices_selected(choices = letters, selected = first_choice())

choices_selected(choices = letters, selected = letters[length(letters)])
choices_selected(choices = letters, selected = last_choice())

choices_selected(choices = letters, selected = head(letters, 4))
choices_selected(choices = letters, selected = first_choices(4))

choices_selected(choices = letters, selected = tail(letters, 4))
choices_selected(choices = letters, selected = last_choices(4))

filter_spec(
  vars = c("selected_variable"),
  choices = c("value1", "value2", "value3"),
  selected = "value3"
)
filter_spec(
  vars = c("selected_variable"),
  choices = c("value1", "value2", "value3"),
  selected = last_choice()
)
```

filter_spec *Data extract filter specification*

Description

It consists in choices and additionally the variable names for the choices.

Usage

```
filter_spec(
  vars,
  choices = NULL,
  selected = if (inherits(choices, "delayed_data")) NULL else choices[1],
  multiple = length(selected) > 1 || inherits(selected, "multiple_choices"),
  label = "Filter by",
  sep = attr(choices, "sep"),
  drop_keys = FALSE
)
```

Arguments

vars	(character or delayed_data) object. Character vector giving the columns to be filtered. These should be key variables of the data set to be filtered. delayed_data objects can be created via variable_choices(), value_choices(), or choices_selected().
choices	(character or numeric or logical or (delayed_data) object. Named character vector to define the choices of a shiny shiny::selectInput(). These choices will be used to filter the dataset. These shall be filter values of the vars input separated by the separator(sep). Please watch out that the filter values have to follow the order of the vars input. In the following example we will show how to filter two columns: vars = c("PARAMCD","AVISIT") and choices = c("CRP - BASELINE", "ALT - BASELINE") will lead to a filtering of (PARAMCD == "CRP" & AVISIT == "BASELINE") | (PARAMCD == "ALT" & AVISIT == "BASELINE"). The sep input has to be " - " in this case. delayed_data objects can be created via variable_choices() or value_choices().
selected	(character or numeric or logical or (delayed_data or delayed_choices) object. Named character vector to define the selected values of a shiny shiny::selectInput() (default values). This value will be displayed inside the shiny app upon start. delayed_choices objects resolve selection when choices become available.
multiple	(logical) Whether multiple values shall be allowed in the shiny shiny::selectInput().
label	(character) optional, defines a label on top of this specific shiny shiny::selectInput(). The default value is "Filter by".
sep	(character) A separator string to split the choices or selected inputs into the values of the different columns.

drop_keys (logical) optional, whether to drop filter column from the dataset keys, TRUE on default.

Details

The filter_spec is used inside teal apps to allow filtering datasets for their key variables. Imagine having an adverse events table. It has the columns PARAMCD and CNSR. PARAMCD contains the levels "OS", "PFS", "EFS". CNSR contains the levels "0" and "1". The first example should show how a filter_spec setup will influence the drop-down menu the app user will see.

Value

filter_spec-S3-class object or delayed_filter_spec-S3-class object.

Examples

```
# for Adverse Events table
filter_spec(
  vars = c("PARAMCD", "CNSR"),
  sep = "-",
  choices = c("OS-1" = "OS-1", "OS-0" = "OS-0", "PFS-1" = "PFS-1"),
  selected = "OS-1",
  multiple = FALSE,
  label = "Choose endpoint and Censor"
)

# filtering a single variable
filter_spec(
  vars = c("PARAMCD"),
  sep = "-",
  choices = c("OS", "PFS", "EFS"),
  selected = "OS",
  multiple = FALSE,
  label = "Choose endpoint"
)

# filtering a single variable by multiple levels of the variable
filter_spec(
  vars = c("PARAMCD"),
  sep = "-",
  choices = c("OS", "PFS", "EFS"),
  selected = c("OS", "PFS"),
  multiple = TRUE,
  label = "Choose endpoint"
)

# delayed version
filter_spec(
  vars = variable_choices("ADSL", "SEX"),
  sep = "-",
  choices = value_choices("ADSL", "SEX", "SEX"),
  selected = "F",
```

```
  multiple = FALSE,
  label = "Choose endpoint and Censor"
)
# using `choices_selected()`
filter_spec(
 vars = choices_selected(variable_choices("ADSL", subset = c("SEX", "AGE")), "SEX", fixed = FALSE),
  multiple = TRUE
)

filter_spec(
  vars = choices_selected(variable_choices("ADSL"), "SEX", fixed = TRUE),
  multiple = TRUE
)

# choose all choices
adsl_filter <- filter_spec(
  vars = choices_selected(variable_choices("ADSL"), "SEX", fixed = FALSE),
  choices = value_choices("ADSL", "SEX"),
  selected = all_choices()
)
```

`format_data_extract` *Formatting data extracts*

Description

Returns a human-readable string representation of an extracted `data_extract_spec` object.

Usage

```
format_data_extract(data_extract)
```

Arguments

`data_extract`	`list` the list output of `data_extract_srv`.

Details

This function formats the output of `data_extract_srv`. See the example for more information.

Value

`character(1)` representation of the `data_extract` object.

Examples

```
library(shiny)

simple_des <- data_extract_spec(
  dataname = "iris",
  filter = filter_spec(vars = "Petal.Length", choices = c("1.4", "1.5")),
  select = select_spec(choices = c("Petal.Length", "Species"))
)

ui <- bslib::page_fluid(
  data_extract_ui(
    id = "extract",
    label = "data extract ui",
    data_extract_spec = simple_des,
    is_single_dataset = TRUE
  ),
  verbatimTextOutput("formatted_extract")
)
server <- function(input, output, session) {
  extracted_input <- data_extract_srv(
    id = "extract",
    datasets = list(iris = iris),
    data_extract_spec = simple_des
  )
  output$formatted_extract <- renderPrint({
    cat(format_data_extract(extracted_input()))
  })
}

if (interactive()) {
  shinyApp(ui, server)
}
```

---

get_anl_relabel_call *Gets the relabel call*

Description

Gets the relabel call

Usage

```
get_anl_relabel_call(columns_source, datasets, anl_name = "ANL")
```

Arguments

columns_source	(named list) where names are column names, values are labels + additional attribute dataname

datasets	(named list of reactive or non-reactive data.frame) object containing data as a list of data.frame. When passing a list of non-reactive data.frame objects, they are converted to reactive data.frame objects internally.
anl_name	(character(1)) Name of the analysis dataset.

Value

(call) to relabel dataset and assign to anl_name.

`get_dataset_prefixed_col_names` *Returns non-key column names from data*

Description

Returns non-key column names from data.

Usage

```
get_dataset_prefixed_col_names(data)
```

Arguments

data	(data.frame) Data with attribute filter_and_columns. This can only be created by data_extract_srv(), which returns a shiny shiny::reactive().

Value

A named character vector with the non-key columns of the data.

References

data_extract_srv()

`get_extract_datanames` *Gets names of the datasets from a list of* `data_extract_spec` *objects*

Description

Fetches dataname slot per data_extract_spec from a list of data_extract_spec.

Usage

```
get_extract_datanames(data_extracts)
```

Arguments

data_extracts	(data_extract_spec(1)) object or a list (of lists) of data_extract_spec.

Value

character vector with the unique dataname set.

---

get_merge_call *Get merge call from a list of selectors*

Description

Creates list of calls depending on selector(s) and type of the merge. The merge order is the same as in selectors passed to the function.

Usage

```
get_merge_call(
  selector_list,
  join_keys = teal.data::join_keys(),
  dplyr_call_data = get_dplyr_call_data(selector_list, join_keys = join_keys),
  merge_function = "dplyr::full_join",
  anl_name = "ANL"
)
```

Arguments

selector_list	(reactive) output from data_extract_multiple_srv() or a reactive named list of outputs from data_extract_srv(). When using a reactive named list, the names must be identical to the shiny ids of the respective data_extract_ui().
join_keys	(join_keys) nested list of keys used for joining.
dplyr_call_data	(list) simplified selectors with aggregated set of filters.
merge_function	(character(1) or reactive) A character string of a function that accepts the arguments x, y and by to perform the merging of datasets.
anl_name	(character(1)) Name of the analysis dataset.

Value

List with merge call elements.

get_relabel_call *Create relabel call from named character*

Description

Function creates relabel call from named character.

Usage

```
get_relabel_call(labels)
```

Arguments

labels	(named character) where name is name is function argument name and value is a function argument value.

Value

call object with relabel step.

Examples

```
get_relabel_call(
  labels = c(
    x = as.name("ANL"),
    AGE = "Age",
    AVAL = "Continuous variable"
  )
)

get_relabel_call(
  labels = c(
    AGE = "Age",
    AVAL = "Continuous variable"
  )
)
```

is_single_dataset *Verify uniform dataset source across data extract specification*

Description

Checks if the input data_extract_spec objects all come from the same dataset.

Usage

```
is_single_dataset(...)
```

Arguments

...	either data_extract_spec objects or lists of data_extract_spec objects that do not contain NULL

Value

TRUE if all data_extract_spec objects come from the same dataset, FALSE otherwise.

---

list_extract_spec *Make sure that the extract specification is in list format*

Description

Make sure that the extract specification is in list format

Usage

```
list_extract_spec(x, allow_null = FALSE)
```

Arguments

x	(data_extract_spec or list) of data_extract_spec elements.
allow_null	(logical) whether x can be NULL.

Value

x as a list if it is not already.

---

merge_datasets *Merge the datasets on the keys*

Description

Combines/merges multiple datasets with specified keys attribute.

Usage

```
merge_datasets(
  selector_list,
  datasets,
  join_keys,
  merge_function = "dplyr::full_join",
  anl_name = "ANL"
)
```

Arguments

selector_list	(reactive) output from data_extract_multiple_srv() or a reactive named list of outputs from data_extract_srv(). When using a reactive named list, the names must be identical to the shiny ids of the respective data_extract_ui().
datasets	(named list of reactive or non-reactive data.frame) object containing data as a list of data.frame. When passing a list of non-reactive data.frame objects, they are converted to reactive data.frame objects internally.
join_keys	(join_keys) of variables used as join keys for each of the datasets in datasets. This will be used to extract the keys of every dataset.
merge_function	(character(1) or reactive) A character string of a function that accepts the arguments x, y and by to perform the merging of datasets.
anl_name	(character(1)) Name of the analysis dataset.

Details

Internally this function uses calls to allow reproducibility.

This function is often used inside a teal module server function with the selectors being the output of data_extract_srv or data_extract_multiple_srv.

```
# inside teal module server function

response <- data_extract_srv(
  id = "reponse",
  data_extract_spec = response_spec,
  datasets = datasets
)
regressor <- data_extract_srv(
  id = "regressor",
  data_extract_spec = regressor_spec,
  datasets = datasets
)
merged_data <- merge_datasets(list(regressor(), response()))
```

Value

merged_dataset list containing:

- expr (list of call) code needed to replicate merged dataset;
- columns_source (list) of column names selected for particular selector; Each list element contains named character vector where:
  - Values are the names of the columns in the ANL. In case if the same column name is selected in more than one selector it gets prefixed by the id of the selector. For example if two data_extract have id x, y, then their duplicated selected variable (for example AGE) is prefixed to be x.AGE and y.AGE;
  - Names of the vector denote names of the variables in the input dataset;
  - attr(,"dataname") to indicate which dataset variable is merged from;

  - attr(, "always selected") to denote the names of the variables which need to be always selected;
- keys (list) the keys of the merged dataset;
- filter_info (list) The information given by the user. This information defines the filters that are applied on the data. Additionally it defines the variables that are selected from the data sets.

Examples

```
library(shiny)
library(teal.data)

X <- data.frame(A = c(1, 1:3), B = 2:5, D = 1:4, E = letters[1:4], G = letters[6:9])
Y <- data.frame(A = c(1, 1, 2), B = 2:4, C = c(4, 4:5), E = letters[4:6], G = letters[1:3])
join_keys <- join_keys(join_key("X", "Y", c("A", "B")))

selector_list <- list(
  list(
    dataname = "X",
    filters = NULL,
    select = "E",
    keys = c("A", "B"),
    reshape = FALSE,
    internal_id = "x"
  ),
  list(
    dataname = "Y",
    filters = NULL,
    select = "G",
    keys = c("A", "C"),
    reshape = FALSE,
    internal_id = "y"
  )
)

data_list <- list(X = reactive(X), Y = reactive(Y))

merged_datasets <- isolate(
  merge_datasets(
    selector_list = selector_list,
    datasets = data_list,
    join_keys = join_keys
  )
)

paste(merged_datasets$expr)
```

---

merge_expression_module

Merge expression module

Description

Convenient wrapper to combine `data_extract_multiple_srv()` and `merge_expression_srv()` when no additional processing is required. Compare the example below with that found in `merge_expression_srv()`.

Usage

```
merge_expression_module(
  datasets,
  join_keys = NULL,
  data_extract,
  merge_function = "dplyr::full_join",
  anl_name = "ANL",
  id = "merge_id"
)

## S3 method for class 'reactive'
merge_expression_module(
  datasets,
  join_keys = NULL,
  data_extract,
  merge_function = "dplyr::full_join",
  anl_name = "ANL",
  id = "merge_id"
)

## S3 method for class 'list'
merge_expression_module(
  datasets,
  join_keys = NULL,
  data_extract,
  merge_function = "dplyr::full_join",
  anl_name = "ANL",
  id = "merge_id"
)
```

Arguments

`datasets`	(named `list` of `reactive` or non-`reactive` `data.frame`) object containing data as a list of `data.frame`. When passing a list of non-reactive `data.frame` objects, they are converted to reactive `data.frame` objects internally.
`join_keys`	(`join_keys`) of variables used as join keys for each of the datasets in `datasets`. This will be used to extract the `keys` of every dataset.
`data_extract`	(named `list` of `data_extract_spec`).
`merge_function`	(`character(1)`) A character string of a function that accepts the arguments `x`, `y` and `by` to perform the merging of datasets.
`anl_name`	(`character(1)`) Name of the analysis dataset.
`id`	An ID string that corresponds with the ID used to call the module's UI function.

Value

Reactive expression with output from `merge_expression_srv()`.

See Also

`merge_expression_srv()`

Examples

```
library(shiny)
library(teal.data)
library(teal.widgets)

ADSL <- data.frame(
  STUDYID = "A",
  USUBJID = LETTERS[1:10],
  SEX = rep(c("F", "M"), 5),
  AGE = rpois(10, 30),
  BMRKR1 = rlnorm(10)
)
ADLB <- expand.grid(
  STUDYID = "A",
  USUBJID = LETTERS[1:10],
  PARAMCD = c("ALT", "CRP", "IGA"),
  AVISIT = c("SCREENING", "BASELINE", "WEEK 1 DAY 8", "WEEK 2 DAY 15")
)
ADLB$AVAL <- rlnorm(120)
ADLB$CHG <- rnorm(120)

data_list <- list(
  ADSL = reactive(ADSL),
  ADLB = reactive(ADLB)
)

join_keys <- join_keys(
  join_key("ADSL", "ADSL", c("STUDYID", "USUBJID")),
  join_key("ADSL", "ADLB", c("STUDYID", "USUBJID")),
  join_key("ADLB", "ADLB", c("STUDYID", "USUBJID", "PARAMCD", "AVISIT"))
)

adsl_extract <- data_extract_spec(
  dataname = "ADSL",
  select = select_spec(
    label = "Select variable:",
    choices = c("AGE", "BMRKR1"),
    selected = "AGE",
    multiple = TRUE,
    fixed = FALSE
  )
)
adlb_extract <- data_extract_spec(
  dataname = "ADLB",
```

```
 filter = filter_spec(vars = "PARAMCD", choices = c("ALT", "CRP", "IGA"), selected = "ALT"),
  select = select_spec(
    label = "Select variable:",
    choices = c("AVAL", "CHG"),
    selected = "AVAL",
    multiple = TRUE,
    fixed = FALSE
  )
)

ui <- bslib::page_fluid(
  bslib::layout_sidebar(
    tags$div(
      verbatimTextOutput("expr"),
      dataTableOutput("data")
    ),
    sidebar = tagList(
      data_extract_ui("adsl_var", label = "ADSL selection", adsl_extract),
      data_extract_ui("adlb_var", label = "ADLB selection", adlb_extract)
    )
  )
)

server <- function(input, output, session) {
  data_q <- qenv()

  data_q <- eval_code(
    data_q,
    "ADSL <- data.frame(
        STUDYID = 'A',
        USUBJID = LETTERS[1:10],
        SEX = rep(c('F', 'M'), 5),
        AGE = rpois(10, 30),
        BMRKR1 = rlnorm(10)
      )"
  )

  data_q <- eval_code(
    data_q,
    "ADLB <- expand.grid(
        STUDYID = 'A',
        USUBJID = LETTERS[1:10],
        PARAMCD = c('ALT', 'CRP', 'IGA'),
        AVISIT = c('SCREENING', 'BASELINE', 'WEEK 1 DAY 8', 'WEEK 2 DAY 15'),
        AVAL = rlnorm(120),
        CHG = rlnorm(120)
       )"
  )

  merged_data <- merge_expression_module(
    data_extract = list(adsl_var = adsl_extract, adlb_var = adlb_extract),
    datasets = data_list,
    join_keys = join_keys,
```

```
    merge_function = "dplyr::left_join"
  )

  code_merge <- reactive({
    for (exp in merged_data()$expr) data_q <- eval_code(data_q, exp)
    data_q
  })

  output$expr <- renderText(paste(merged_data()$expr, collapse = "\n"))
  output$data <- renderDataTable(code_merge()[["ANL"]])
}

if (interactive()) {
  shinyApp(ui, server)
}
```

`merge_expression_srv` *Data merge module server*

Description

When additional processing of the `data_extract` list input is required, `merge_expression_srv()` can be combined with `data_extract_multiple_srv()` or `data_extract_srv()` to influence the `selector_list` input. Compare the example below with that found in `merge_expression_module()`.

Usage

```
merge_expression_srv(
  id = "merge_id",
  selector_list,
  datasets,
  join_keys,
  merge_function = "dplyr::full_join",
  anl_name = "ANL"
)

## S3 method for class 'reactive'
merge_expression_srv(
  id = "merge_id",
  selector_list,
  datasets,
  join_keys,
  merge_function = "dplyr::full_join",
  anl_name = "ANL"
)

## S3 method for class 'list'
merge_expression_srv(
```

```
  id = "merge_id",
  selector_list,
  datasets,
  join_keys,
  merge_function = "dplyr::full_join",
  anl_name = "ANL"
)
```

Arguments

id	An ID string that corresponds with the ID used to call the module's UI function.
selector_list	(reactive) output from data_extract_multiple_srv() or a reactive named list of outputs from data_extract_srv(). When using a reactive named list, the names must be identical to the shiny ids of the respective data_extract_ui().
datasets	(named list of reactive or non-reactive data.frame) object containing data as a list of data.frame. When passing a list of non-reactive data.frame objects, they are converted to reactive data.frame objects internally.
join_keys	(join_keys) of variables used as join keys for each of the datasets in datasets. This will be used to extract the keys of every dataset.
merge_function	(character(1) or reactive) A character string of a function that accepts the arguments x, y and by to perform the merging of datasets.
anl_name	(character(1)) Name of the analysis dataset.

Value

Reactive expression with output from merge_expression_srv().

See Also

merge_expression_module()

Examples

```
library(shiny)
library(teal.data)
library(teal.widgets)

ADSL <- data.frame(
  STUDYID = "A",
  USUBJID = LETTERS[1:10],
  SEX = rep(c("F", "M"), 5),
  AGE = rpois(10, 30),
  BMRKR1 = rlnorm(10)
)

ADLB <- expand.grid(
  STUDYID = "A",
  USUBJID = LETTERS[1:10],
  PARAMCD = c("ALT", "CRP", "IGA"),
```

```
  AVISIT = c("SCREENING", "BASELINE", "WEEK 1 DAY 8", "WEEK 2 DAY 15")
)
ADLB$AVAL <- rlnorm(120)
ADLB$CHG <- rlnorm(120)

data_list <- list(
  ADSL = reactive(ADSL),
  ADLB = reactive(ADLB)
)

join_keys <- join_keys(
  join_key("ADSL", "ADSL", c("STUDYID", "USUBJID")),
  join_key("ADSL", "ADLB", c("STUDYID", "USUBJID")),
  join_key("ADLB", "ADLB", c("STUDYID", "USUBJID", "PARAMCD", "AVISIT"))
)

adsl_extract <- data_extract_spec(
  dataname = "ADSL",
  select = select_spec(
    label = "Select variable:",
    choices = c("AGE", "BMRKR1"),
    selected = "AGE",
    multiple = TRUE,
    fixed = FALSE
  )
)
adlb_extract <- data_extract_spec(
  dataname = "ADLB",
 filter = filter_spec(vars = "PARAMCD", choices = c("ALT", "CRP", "IGA"), selected = "ALT"),
  select = select_spec(
    label = "Select variable:",
    choices = c("AVAL", "CHG"),
    selected = "AVAL",
    multiple = TRUE,
    fixed = FALSE
  )
)

ui <- bslib::page_fluid(
  bslib::layout_sidebar(
    tags$div(
      verbatimTextOutput("expr"),
      dataTableOutput("data")
    ),
    sidebar = tagList(
      data_extract_ui("adsl_var", label = "ADSL selection", adsl_extract),
      data_extract_ui("adlb_var", label = "ADLB selection", adlb_extract)
    )
  )
)

server <- function(input, output, session) {
  data_q <- qenv()
```

```
  data_q <- eval_code(
    data_q,
    "ADSL <- data.frame(
        STUDYID = 'A',
        USUBJID = LETTERS[1:10],
        SEX = rep(c('F', 'M'), 5),
        AGE = rpois(10, 30),
        BMRKR1 = rlnorm(10)
      )"
  )

  data_q <- eval_code(
    data_q,
    "ADLB <- expand.grid(
        STUDYID = 'A',
        USUBJID = LETTERS[1:10],
        PARAMCD = c('ALT', 'CRP', 'IGA'),
        AVISIT = c('SCREENING', 'BASELINE', 'WEEK 1 DAY 8', 'WEEK 2 DAY 15'),
        AVAL = rlnorm(120),
        CHG = rlnorm(120)
      )"
  )

  selector_list <- data_extract_multiple_srv(
    list(adsl_var = adsl_extract, adlb_var = adlb_extract),
    datasets = data_list
  )
  merged_data <- merge_expression_srv(
    selector_list = selector_list,
    datasets = data_list,
    join_keys = join_keys,
    merge_function = "dplyr::left_join"
  )

  code_merge <- reactive({
    for (exp in merged_data()$expr) data_q <- eval_code(data_q, exp)
    data_q
  })

  output$expr <- renderText(paste(merged_data()$expr, collapse = "\n"))
  output$data <- renderDataTable(code_merge()[["ANL"]])
}

if (interactive()) {
  shinyApp(ui, server)
}
```

---

no_selected_as_NULL *Check select choices for no choice made*

Description

Check select choices for no choice made

Usage

```
no_selected_as_NULL(x)
```

Arguments

x	(character) Word that shall be checked for NULL, empty, "–no-selection".

Value

The word or NULL.

`resolve_delayed` *Resolve delayed inputs by evaluating the code within the provided datasets*

Description

Resolve delayed inputs by evaluating the code within the provided datasets

Usage

```
resolve_delayed(x, datasets, keys)

## S3 method for class 'FilteredData'
resolve_delayed(
  x,
  datasets,
  keys = sapply(datasets$datanames(), datasets$get_keys, simplify = FALSE)
)

## S3 method for class 'list'
resolve_delayed(x, datasets, keys = NULL)
```

Arguments

x	(delayed_data, list) to resolve.
datasets	(FilteredData or named list) to use as a reference to resolve x.
keys	(named list) with primary keys for each dataset from datasets. names(keys) should match names(datasets).

Value

Resolved object.

Methods (by class)

- `resolve_delayed(FilteredData)`: Default values for `keys` parameters is extracted from `datasets`.
- `resolve_delayed(list)`: Generic method when `datasets` argument is a named list.

Examples

```
library(shiny)

ADSL <- teal.data::rADSL
isolate({
  data_list <- list(ADSL = reactive(ADSL))

  # value_choices example
  v1 <- value_choices("ADSL", "SEX", "SEX")
  v1
  resolve_delayed(v1, data_list)

  # variable_choices example
  v2 <- variable_choices("ADSL", c("BMRKR1", "BMRKR2"))
  v2
  resolve_delayed(v2, data_list)

  # data_extract_spec example
  adsl_filter <- filter_spec(
    vars = variable_choices("ADSL", "SEX"),
    sep = "-",
    choices = value_choices("ADSL", "SEX", "SEX"),
    selected = "F",
    multiple = FALSE,
    label = "Choose endpoint and Censor"
  )

  adsl_select <- select_spec(
    label = "Select variable:",
    choices = variable_choices("ADSL", c("BMRKR1", "BMRKR2")),
    selected = "BMRKR1",
    multiple = FALSE,
    fixed = FALSE
  )

  adsl_de <- data_extract_spec(
    dataname = "ADSL",
    select = adsl_select,
    filter = adsl_filter
  )

  resolve_delayed(adsl_filter, datasets = data_list)
  resolve_delayed(adsl_select, datasets = data_list)
  resolve_delayed(adsl_de, datasets = data_list)

  # nested list (arm_ref_comp)
```

```
  arm_ref_comp <- list(
    ARMCD = list(
      ref = variable_choices("ADSL"),
      comp = variable_choices("ADSL")
    )
  )

  resolve_delayed(arm_ref_comp, datasets = data_list)
})
```

`select_spec` *Column selection input specification*

Description

`select_spec` is used inside `teal` to create a `shiny::selectInput()` that will select columns from a dataset.

Usage

```
select_spec(
  choices,
  selected = if (inherits(choices, "delayed_data")) NULL else choices[1],
  multiple = length(selected) > 1 || inherits(selected, "multiple_choices"),
  fixed = FALSE,
  always_selected = NULL,
  ordered = FALSE,
  label = "Select"
)

select_spec.delayed_data(
  choices,
  selected = NULL,
  multiple = length(selected) > 1,
  fixed = FALSE,
  always_selected = NULL,
  ordered = FALSE,
  label = NULL
)

select_spec.default(
  choices,
  selected = choices[1],
  multiple = length(selected) > 1,
  fixed = FALSE,
  always_selected = NULL,
  ordered = FALSE,
  label = NULL
)
```

Arguments

choices	(character or delayed_data) object. Named character vector to define the choices of a shiny shiny::selectInput(). These have to be columns in the dataset defined in the data_extract_spec() where this is called. delayed_data objects can be created via variable_choices() or value_choices().
selected	(character or NULL or delayed_choices or delayed_data) optional named character vector to define the selected values of a shiny shiny::selectInput(). Passing a delayed_choices object defers selection until data is available. Defaults to the first value of choices or NULL for delayed data loading.
multiple	(logical) Whether multiple values shall be allowed in the shiny shiny::selectInput().
fixed	(logical) optional data_extract_spec() specific feature to hide the choices selected in case they are not needed. Setting fixed to TRUE will not allow the user to select columns. It will then lead to a selection of columns in the dataset that is defined by the developer of the app.
always_selected	(character) Additional column names from the data set that should always be selected
ordered	(logical(1)) Flags whether selection order should be tracked.
label	(character) optional, defines a label on top of this specific shiny shiny::selectInput(). The default value is "Select".

Value

A select_spec-S3 class object or delayed_select_spec-S3-class object. It contains all input values.

If select_spec, then the function double checks the choices and selected inputs.

Examples

```
# Selection with just one column allowed
select_spec(
  choices = c("AVAL", "BMRKR1", "AGE"),
  selected = c("AVAL"),
  multiple = FALSE,
  fixed = FALSE,
  label = "Column"
)

# Selection with just multiple columns allowed
select_spec(
  choices = c("AVAL", "BMRKR1", "AGE"),
  selected = c("AVAL", "BMRKR1"),
  multiple = TRUE,
  fixed = FALSE,
  label = "Columns"
)

# Selection without user access
```

```
select_spec(
  choices = c("AVAL", "BMRKR1"),
  selected = c("AVAL", "BMRKR1"),
  multiple = TRUE,
  fixed = TRUE,
  label = "Columns"
)

# Delayed version
select_spec(
  label = "Select variable:",
  choices = variable_choices("ADSL", c("BMRKR1", "BMRKR2")),
  selected = "BMRKR1",
  multiple = FALSE,
  fixed = FALSE
)

# delayed_choices passed to selected
select_spec(
  label = "Select variable:",
  choices = variable_choices("ADSL", c("BMRKR1", "BMRKR2")),
  selected = all_choices()
)

# Both below objects are semantically the same
select_spec(choices = variable_choices("ADSL"), selected = variable_choices("ADSL"))
select_spec(choices = variable_choices("ADSL"), selected = all_choices())
```

`split_by_sep` *Split by separator (matched exactly)*

Description

Split by separator (matched exactly)

Usage

```
split_by_sep(x, sep)
```

Arguments

`x`	(`character`) Character vector, each element of which is to be split. Other inputs, including a factor return themselves.
`sep`	(`character`) separator to use for splitting.

Value

List of character vectors split by `sep`. Self if `x` is not a `character`.

value_choices *Value labeling and filtering based on variable relationship*

Description

Wrapper on choices_labeled to label variable values basing on other variable values.

Usage

```
value_choices(data, var_choices, var_label = NULL, subset = NULL, sep = " - ")

## S3 method for class 'character'
value_choices(data, var_choices, var_label = NULL, subset = NULL, sep = " - ")

## S3 method for class 'data.frame'
value_choices(data, var_choices, var_label = NULL, subset = NULL, sep = " - ")
```

Arguments

data	(data.frame, character) If data.frame, then data to extract labels from. If character, then name of the dataset to extract data from once available.
var_choices	(character, delayed_variable_choices) Choice of column names.
var_label	(character) vector with labels column names.
subset	(character or function) If character, vector with values to subset. If function, then this function is used to determine the possible columns (e.g. all factor columns). In this case, the function must take only single argument "data" and return a character vector. See examples for more details.
sep	(character) separator used in case of multiple column names.

Value

named character vector or delayed_data object.

Examples

```
ADRS <- teal.data::rADRS
value_choices(ADRS, "PARAMCD", "PARAM", subset = c("BESRSPI", "INVET"))
value_choices(ADRS, c("PARAMCD", "ARMCD"), c("PARAM", "ARM"))
value_choices(ADRS, c("PARAMCD", "ARMCD"), c("PARAM", "ARM"),
  subset = c("BESRSPI - ARM A", "INVET - ARM A", "OVRINV - ARM A")
)
value_choices(ADRS, c("PARAMCD", "ARMCD"), c("PARAM", "ARM"), sep = " --- ")

# delayed version
value_choices("ADRS", c("PARAMCD", "ARMCD"), c("PARAM", "ARM"))
```

```
# functional subset
value_choices(ADRS, "PARAMCD", "PARAM", subset = function(data) {
  levels(data$PARAMCD)[1:2]
})
```

`variable_choices` *Variable label extraction and custom selection from data*

Description

Wrapper on choices_labeled to label variables basing on existing labels in data.

Usage

```
variable_choices(data, subset = NULL, fill = FALSE, key = NULL)

## S3 method for class 'character'
variable_choices(data, subset = NULL, fill = FALSE, key = NULL)

## S3 method for class 'data.frame'
variable_choices(data, subset = NULL, fill = TRUE, key = NULL)
```

Arguments

`data`	(`data.frame` or `character`) If `data.frame`, then data to extract labels from. If `character`, then name of the dataset to extract data from once available.
`subset`	(`character` or `function`) If `character`, then a vector of column names. If `function`, then this function is used to determine the possible columns (e.g. all factor columns). In this case, the function must take only single argument "data" and return a character vector. See examples for more details.
`fill`	(`logical(1)`) if `TRUE`, the function will return variable names for columns with non-existent labels; otherwise will return `NA` for them.
`key`	(`character`) vector with names of the variables, which are part of the primary key of the `data` argument. This is an optional argument, which allows to identify variables associated with the primary key and display the appropriate icon for them in the `teal.widgets::optionalSelectInput(` widget.

Value

Named `character` vector with additional attributes or `delayed_data` object.

Examples

```
library(teal.data)
ADRS <- rADRS
variable_choices(ADRS)
variable_choices(ADRS, subset = c("PARAM", "PARAMCD"))
variable_choices(ADRS, subset = c("", "PARAM", "PARAMCD"))
variable_choices(
  ADRS,
  subset = c("", "PARAM", "PARAMCD"),
  key = default_cdisc_join_keys["ADRS", "ADRS"]
)

# delayed version
variable_choices("ADRS", subset = c("USUBJID", "STUDYID"))

# functional subset (with delayed data) - return only factor variables
variable_choices("ADRS", subset = function(data) {
  idx <- vapply(data, is.factor, logical(1))
  names(data)[idx]
})
```

Index

add_no_selected_choices, 3
all_choices *(*delayed_choices*)*, 21

check_no_multiple_selection, 3
choices_labeled, 4, *45, 46*
choices_selected, *4*, 5
choices_selected(), *4*, *23*
compose_and_enable_validators, 8

data_extract_multiple_srv, 10
data_extract_multiple_srv(), *28*, *31*, *37*
data_extract_spec, 14, *14*, *16*, *20*
data_extract_spec(), *20*, *43*
data_extract_srv, 16, *17*, *25*
data_extract_srv(), *12*, *20*, *27, 28*, *31*, *37*
data_extract_ui, *16*, 19
data_extract_ui(), *28*, *31*, *37*
datanames_input, 21
delayed_choices, 21

filter_spec, *14, 15*, 23
first_choice *(*delayed_choices*)*, 21
first_choices *(*delayed_choices*)*, 21
format_data_extract, 25

get_anl_relabel_call, 26
get_dataset_prefixed_col_names, 27
get_extract_datanames, 27
get_merge_call, 28
get_relabel_call, 29

is.choices_selected *(*choices_selected*)*, 5
is_single_dataset, 29

last_choice *(*delayed_choices*)*, 21
last_choices *(*delayed_choices*)*, 21
list_extract_spec, 30

merge_datasets, 30
merge_expression_module, 32
merge_expression_module(), *36, 37*
merge_expression_srv, 36
merge_expression_srv(), *33, 34*, *37*

no_selected_as_NULL, 39

print.choices_labeled *(*choices_labeled*)*, 4

resolve_delayed, 40

select_spec, *14, 15*, 42
shiny::div, *20*
shiny::helpText(), *21*
shiny::reactive(), *27*
shiny::selectInput, *20*
shiny::selectInput(), *4*, *23*, *42, 43*
split_by_sep, 44

teal.widgets::optionalSelectInput(), *5*, *46*

value_choices, 45
value_choices(), *6*, *23*, *43*
variable_choices, 46
variable_choices(), *6*, *23*, *43*